



Control Panel Compact Type

AT-KC10C2

The “Kairos Control” panel is available in two models: 24XPT standard layout (AT-KC10C1) and 12XPT compact layout (AT-KC10C2).* The panels allow functions to be assigned freely. Indicators show the functions assigned to individual buttons. Multi-scene operation is supported with two ME layouts and two faders. Multiple panels can be used simultaneously within a single system.

Key Features

12XPT standard layout. The panels allow functions to be assigned freely.

Multi-scene operation is supported with two ME layouts and two faders.

Indicators show the functions assigned to individual buttons.

Multiple panels can be used simultaneously within a single system.

A transition fader of the panel supports A/B mode in addition to PGM/PST mode.



AT-KC10C2

<https://eu.connect.panasonic.com/pt/en/products/broadcast-proav/kc10c2>

General

Power Requirement	DC 12V, 4.0A - XLR 4pin x 2 (Redundant)
Operating Temperature	0 to 40 degree Celsius
Operating Humidity	10% to 90% (no condensation)
Weight	Approx. 8.5 kg / 18.74 lb
Dimensions (W x H x D)	600 mm x 90 mm x 420 mm 23.7 in. x 3.5 in. x 16.5 in. Excluding protrusion
Control Terminals	
LAN (Rear Panel)	RJ-45 x 1, 1GbE
USB (Rear Panel)	USB2.0 typeA x 1