



High cost-to-performance display for professional users seeking a 4K video wall solution. 49" frameless D-LED LCD, 450 cd/m², 3.5 mm bezel to bezel, 24/7 operation, portrait mode, anti-glare surface and robust display.

TH-49LFV8

Highly reliable frameless video wall display. High cost-to-performance video wall for professional users seeking a 4K video-wall solution.

Key Features

49", 450 cd/m², 3,5 mm bezel to bezel, anti-glare surface

DisplayPort UHD daisy chain functionality

A super narrow frame for optimal multi-screen layouts.

Ideal for installation in standard indoor places, wide colour viewing angle and high visibility

450 cd/m²





TH-49LFV8

<https://eu.connect.panasonic.com/pt/en/products/professional-displays/th-49lfv8>

Screen Size	49-inch (1237 mm)
Panel Type	LCD IPS Panel/D-LED
Aspect Ratio	16:9
Effective Display Area (W x H)	1077 x 607 mm(42.5" x 24.0")
Number of Pixels (H x V)	1920 x 1080 pixels
Brightness	450 cd/m2
Contrast Ratio	1400:1
Response Time	8 ms(G to G)
Viewing Angle	178°/178° (CR≥10)
Panel Surface Treatment	Anti-Glare Low-Reflection (Haze 3%)
Power Requirements	110-240 V AC, 50/60 Hz
Power Consumption	220 W
Standby Condition	Approx. 0.5 W
Dimensions (W x H x D)	1077.7 x 607.9 x 103.9 mm(42.5" x 24.0" x 4.1")
Bezel Width	L/T:2.25 mm(0.088"),R/B:1.25 mm(0.049")
Weight	Approx.22.0kg(48.5 lbs) TBD
Wall-Hanging Pitch	VESA compliant 400 x 400 mm(15.8" x 15.8")