



**42" LCD IPS Panel, 500 cd/m<sup>2</sup>, Shadowsense  
Multitouch, OpenPort Platform, HTML5, narrow 6.3  
mm bezel**

## TH-42AF1-SST

Combines the accurate and robust ShadowSense™ Touch technology and the performance of a stand-alone solution with the Android™-based OpenPort Platform™, ideal for installations such as interactive POS and way finding signage.

### Key Features

42", 500cd/m<sup>2</sup>, 24/7 Operation

10-point multi-touch Interactive Display using ShadowSense™ Technology

The touch technology is immune to the ambient light and works even in bright environments.

High-performance SoC (System on a Chip) featuring a 1 GHz quad-core CPU, 1 GB of memory, and 8 GB internal storage.

Simple installation and easy operation. No need for external devices and cables.

**500** cd/m<sup>2</sup>





## TH-42AF1-SST

<https://eu.connect.panasonic.com/pt/en/products/professional-displays/th-42af1-sst>

<b>Screen Size</b>	42-inch (1064 mm)
<b>Panel Type</b>	LCD IPS Panel/LED
<b>Aspect Ratio</b>	16:9
<b>Effective Display Area (W x H)</b>	984 x 574 mm
<b>Number of Pixels (H x V)</b>	1920 x 1080 pixels
<b>Brightness</b>	500 cd/m2
<b>Contrast Ratio</b>	1300:1
<b>Dynamic Contrast</b>	50000:1
<b>Response Time</b>	8 ms (GtoG)
<b>Viewing Angle (Horizontal/Vertical)</b>	178°/178°(CR≥10)
<b>Power Requirements</b>	110-127/220-240 V AC,50/60 Hz
<b>Power Consumption</b>	160W
<b>Power Off Condition</b>	Approx.0.3W (TBD)
<b>Standby Condition</b>	Approx.0.5W (TBD)
<b>Dimensions (W x H x D)</b>	1032 x 622 x 90mm (with handle)
<b>Dimensions (W x H x D) Excluding Handle Part</b>	1032 x 622 x 76mm
<b>Bezel Width</b>	48mm
<b>Weight</b>	Approx. 33,5 kg
<b>Wall-Hanging Pitch</b>	VESA Compliant 400 x 400 mm(15.8" x 15.8")
<b>Operating Environment</b>	Temperature : 0°C to 40°C(32°F to 104°F)/Humidity: 20-80% (non-condensation)
<b>Panel Surface Treatment</b>	Anti-Glare
<b>Haze</b>	10%