



WINDOWS 11 PRO FULLY RUGGED TABLET WITH 12" OUTDOOR FULL-HD DISPLAY

TOUGHBOOK 33 mk4 Tablet

TOUGHBOOK 33 TABLET, the 12.0" fully rugged device with hot swappable twin batteries and highly configurable capabilities brings unrivalled flexibility and performance for mobile business computing. Thanks to the optional detachable keyboard, the TOUGHBOOK 33 TABLET offers the best of all worlds for mobile workers. Target industries for the device include field service workers, maintenance and service technicians in utilities and telecommunications, as well as government agencies, defence, the police and other emergency services.

Key Features

Intel Core™ i5-1345U vPro™ Processor or Intel Core™ i7 1370P vPro™ Processor

Windows 11 Pro

12.0" Active Matrix (TFT) colour LCD 2160 x 1440 (QHD) LCD with sunlight-viewable glove-enabled capacitive touchscreen (up to $1.200 cd/m^2$), IP55 Digitiser

IP65 Water and dust resistant*** Tested against MILSTD810H***

Long battery life of up to 7.5 hours with hot swap













TOUGHBOOK 33 mk4 Tablet

Yesterday's Legend, Today's Leader.

TOUGH YET VERSATILE

The Panasonic TOUGHBOOK 33mk4 is a cutting-edge, rugged tablet designed for mobile workers, featuring out-of-the-box 5G connectivity that enhances performance, reliability, and data transfer speeds in various environments. This model can connect to 5G standalone networks, catering to the increasing demand for quick, secure data transfer in the context of IoT and AI applications. It boasts improved processing power with options for the Intel® Core™ i5 or i7 processors (both 13th generation, equipped with Intel vPro® Technology).

https://eu.connect.panasonic.com/se /en/toughbook/toughbook-33series/toughbook-33-mk4-tablet

| Model | C-33mk4, 16GB RAM, 512GB SSD, 2x standard battery pack, IP55 digitiser pen |
|-------------------------------------|---|
| Operating System | Windows® 11 Pro |
| Mobile Computing Platform | Intel® Core™ i5-1345U vPro™ Processor or Intel® Core™ i7 1370P vPro™ Processor |
| Graphic Chip | Intel® Iris Xe Graphics (Built-in CPU) |
| RAM | 16GB (max. 32GB) DDR4 |
| itorage | 512GB OPAL NVMe SSD (up to 2TB optional) |
| LCD | 12.0" Active Matrix (TFT) colour LCD 2160 x 1440 (QHD) LCD with sunlight-viewable |
| | glove enabled capacitive touchscreen (up to 1.200cd/m²), IP55 Digitiser |
| Wireless | Bluetooth: 5.3 + EDR Class 1 |
| | Wireless LAN: Intel Wi-Fi6E AX211 |
| | Mobile Broadband*: 4G or 5G with physical SIM and eSIM support/ 5G comes with |
| | extended battery |
| | GPS*: U-Blox NEO-M9 Series |
| | LAN: IEEE 802.3 10Base-T / IEEE 802.3u 100BASE-TX / IEEE 802.3ab 1000BASE-T |
| Interfaces | Micro SD/SDXC Memory Card: project based |
| | Configuration port (Tablet)**: Serial, 2D Barcode Reader, 2nd USB 2.0 |
| | USB 3.2 Gen 1 Type A : x1 |
| | Thunderbolt 4: x1 |
| | USB 2.0**: x1 |
| | HDMI: x1 |
| | LAN Port: x1 |
| | Headset: x1 |
| | DC-in: x1 |
| | Port Replicator: x1 |
| | Dual Antenna Connector: x1 |
| | Business Expansion Module**: Smart Card Reader, NFC, Fingerprint Reader |
| ront Camera | 2 MP with IR / privacy shutter (Windows Hello compliant) |
| Rear Camera | 8 mpixel with autofocus and LED flash |
| ound | WAVE and MIDI playback, Intel High Definition Audio subsystem support |
| Security | TPM (TCG V2.0 compliant) Password security (supervisor password, user password, har |
| | disc lock) Integrated hardware security lock slot |
| Pointing device: Touchscreen (Touch | Dual Touch (10 Finger touch (Capacitive) & Digitizer) |
| panel) | · · · · · · · · · · · · · · · · |
| Dimensions: Main Unit (WxHxD) | Standard Battery: 308.0 mm × 243.6 mm × 21.6 mm / 12.1" × 9.6" × 0.9" (without |
| | protruding parts) |
| | Extended Battery: 308.0 mm x 243.6 mm x 32.1 mm / 12.1" x 9.6" x 1.3" (without |
| | protruding parts) |
| Weight: Main Unit Battery Life | Standard Battery: 1.54kg / 3.4lb |
| | Extended Battery: 1.9kg / 4.1lb |
| | Standard: Approx 7.5 hours (Mobile Mark™ 25) |
| | Extended: Approx 15.5 hours (Mobile Mark™ 25) |
| Power Supply: AC Adaptor | Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 4.06A |
| ower Supply: Battery | Standard: x2 Li-Ion (3 cell, 22Whr) |
| rower supply, battery | Extended: x2 Li-Ion (6 cell, 22 Whr) optional |
| tower Supply Hat Swan | |
| ower Supply: Hot Swap | Hot swap, Standby function, ACPI BIOS |
| Prop resistance | MIL-STD 810H, 150cm*** |
| Oust resistance | IEC529 (JIS C0920) IP6x*** |
| Vater resistance | IEC529 (JIS C0920) IPx5*** |
| Operating temperature | MIL-STD 810H, -29 °C to 60 °C *** |
| ncluded in the box | Power Supply, Power Cord, Display cleaning cloth and User Manual |
| ootnote Description | * Optional |
| | ** One option exclusive possible in configuration port/ business expansion module |
| | *** Tested by an independent third party lab following MIL-STD-810H and IEC529, |
| | Continue 12.4.12.6.2.14.2.5 and 14.2.5 |

TOUGHBOOK 33: November 2024

Intel, the Intel logo, Intel Core, Intel vPro, Core Inside and vPro Inside are trademarks of Intel Corporation in the U.S. and other countries. Microsoft® and Windows® are registered trademarks of Microsoft® Corporation of the United States and/or other countries. All other brand names shown are the registered trademarks of the relevant companies. All rights reserved. All working conditions, times and figures quoted are optimum or ideal levels and may differ as a result of individual and local circumstances.

Mobile Solutions Business Division - Europe, Panasonic Connect GmbH, Hagenauer Straße 43, 65203 Wiesbaden, Germany

Sections 13.4, 13.6.2, 14.2.5 and 14.3