



Equipped with advanced professional features offering a slim, lightweight, and scalable solution which simplifies any installations. 98", 4K Ultra HD panel, Intel® Smart Display Module (Intel® SDM), 24/7 operation, portrait, 4K Digital link, narrow bezel

TH-98SQ1

98" 4K professional and stylish digital display. Equipped with advanced professional features including Intel Smart Display Module and offering a slim, lightweight, and scalable solution which simplifies any installations.

Key Features

98", 500 cd/m², 4K IPS panel with slim and stylish design and 24/7 operation

High image quality through HDR support (HLG system) that displays light and dark images in a realistic way

4K USB Media Player: eliminates the need for external devices and allows updates via LAN

High expandability with ultra-slim Intel® SDM (Intel® Smart Display Module), DisplayPort connection for daisy-chain signage, multiple screen function (quad, PinP, PbyP) and 4K DIGITAL LINK

Flexible and light installation either in portrait or landscape



Media
Player

4K
PROFESSIONAL

500 cd/m²

intel.
smart display
module ready

Narrow





TH-98SQ1

<https://eu.connect.panasonic.com/en/products/professional-displays/th-98sq1>

| | |
|--|---|
| Screen size (diagonal) (inch) | 98-inch (2477 mm) |
| Screen size (diagonal) (mm) | 2477 mm |
| Aspect Ratio | 16:9 |
| Panel Type | IPS Panel/ Direct-LED |
| Effective display area (W x H) (mm) | 2158.8 x 1214.3 mm |
| Effective display area (W x H) (inch) | 84.9 x 47.8 inch |
| Resolution | 3840 x 2160 |
| Brightness (typ.) | 500 cd/m2 |
| Contrast Ratio | 1300:1 (Typ) |
| Response Time | 8 ms (G to G) |
| Viewing angle [(T/B)/(L/R)] | 178°/178° (CR≥10) |
| Panel Surface Treatment | Anti-Grare Type (Haze 28%) |
| Terminals HDMI In | HDMI TYPE-A Connector x 2 |
| Terminals DVI-D IN/AUDIO IN (L/R) | DVI-D 24-pin x 1 / Stereo Mini Jack (M3) x 2 (Shared with PC In) |
| Terminals PC IN/AUDIO IN (L/R) | Mini D-sub 15-pin x 1 / Stereo Mini Jack (M3) x 2 (Shared with DVI-D In) |
| Terminals DisplayPort IN | DisplayPort x 1 |
| Terminals DisplayPort OUT | DisplayPort x 1 |
| Terminals USB | USB Connector (TYPE A) x 2, DC 5 V/2 A (USB 3.0 supported) |
| Terminals Serial | D-sub 9-pin x 1, RS-232C Compatible |
| Terminal LAN | RJ45 x 1, 10 BASE-T / 100 BASE-TX, Compatible with PLink™ |
| Terminal DIGITAL LINK | RJ45 x 1, 100 BASE-TX, Compatible with long reach mode and PLink™ |
| Terminals Slot | Intel® SDM specification Corresponding size SDM-S / SDM-L, Supply power 12 V / 5.5 A, 3.3 V / 1.1 A |
| Terminals IR IN / OUT | Stereo Mini Jack (M3) x 1 / x 1 |
| Terminals Audio Out | 30 W [15 W + 15 W] 10% THD |
| Built-in Speaker | 20 W [10 W + 10 W] |
| Power Requirements | 110-240 V AC, 50 Hz/60 Hz |
| Power Consumption | 685 W |
| Power Off Condition | Approx. 0.3 W |
| Stand-by Condition | Approx. 0.5 W |
| Dimensions (W x H x D) (mm) | 2194 x 1249 x 90 mm |
| Dimensions (W x H x D) (inch) | 86.4" x 49.2" x 3.5" |
| Bezel width (mm) | 16.0 mm (T/B/L/R) |
| Bezel width (inch) | 0.63 inch (T/B/L/R) |
| Weight (kg) | Approx. 90.0 kg |
| Weight (lbs.) | Approx. 198.5 lbs |
| Gross Weight (kg) | Approx. 138.0 kg |
| Gross Weight (lbs.) | Approx. 304.3 lbs |
| Wall-hanging pitch (mm) | 800 x 500 mm VESA Compliant |
| Wall-hanging pitch (inch) | 31.5 x 19.7 inch VESA Compliant |
| Orientation | Landscape / Portrait |
| Tilting angle | Landscape setting: 0 - 20 degrees forward/backward Portrait setting: 0 - 20 degrees forward/backward |
| Operating Time | 24 h/day |
| Operating environment Temperature | 0 °C to 40 °C |
| Operating Environment Humidity | 20% to 80% (Non-condensation) |