# SPEC FILE

## Smoke cut filter unit

### Description


The smoke cut filter is an air filter unit for a Panasonic projector, for when the projector is used at events or other situations where smoke, fog or haze is being generated as a special effect.


Specifications	Dimensions (W $\times$ H $\times$ D):	482 × 60 × 480 mm
		(18-29/32" × 2-3/8" × 18-31/32")
	Weight:	Approx. 1.5 kg* (3.3 lbs*)
	Applicable projector:	PT-EX16K
		<ul> <li>Average value. May differ depending on models.</li> </ul>

### Caution:

- When the filter is attached, be sure to switch the filter type on the projector's onscreen menu.
- The filter can be used for approximately 24 hours in smoky, foggy or hazy environments. Note that the filter cannot be reused. After use, replace it with an unused filter.
- The operating temperature range is 5°C-40°C (41°F-104°F) when used at altitudes of 500 meters (1,640 feet) or less above sea level. The filter cannot be used when the ambient temperature is 40°C (104°F) or higher. The operating temperature range is 5°C-30°C (41°F-86°F) when used at altitudes between 500 and 1,400 meters (1,640 and 4,593 feet) above sea level. The filter cannot be used at altitudes of 1,400 meters (4,593 feet) or more above sea level or when the ambient temperature is 35°C (95°F) or higher.

#### Dimensions





unit : mm (inch) NOTE: This illustration is not drawn to scale.

ET-SFE16



Weights and dimensions shown are approximate. Specifications subject to change without notice.

