

Control Commands

**Model No. PT-FW430U / FW430E / FW430EA
PT-FX400U / FX400E / FX400EA**

CONTENTS

1. BASIC FORMAT	7
2. BASIC CONTROL COMMAND	8
2.1. Power ON (LAMP ON)	8
2.2. Power OFF (STNDBY).....	8
2.3. VOLUME (+) Key.....	8
2.4. VOLUME (–) Key.....	8
2.5. INPUT SELECT	9
2.6. FREEZE.....	9
2.7. MENU Key	9
2.8. RETURN Key.....	9
2.9. ENTER Key.....	10
2.10. UP (↑) Key.....	10
2.11. DOWN (↓) Key.....	10
2.12. LEFT (←) Key	10
2.13. RIGHT (→) Key.....	10
2.14. DEFAULT Key	10
2.15. AUTO SETUP	11
2.16. AV MUTE	11
2.17. DIGITAL ZOOM (+) Key.....	11
2.18. DIGITAL ZOOM (–) Key.....	11
2.19. INDEX-WINDOW	11
2.20. FUNCTION 1	12
2.21. FUNCTION 2	12
2.22. FUNCTION 3	12
2.23. SIDE BY SIDE.....	12
2.24. COMPUTER SEARCH.....	12

2.25.	PAGE UP Key	13
2.26.	PAGE DOWN Key.....	13
2.27.	MULTI-LIVE Key	13
2.28.	KEYSTONE selected item display	13
2.29.	ECO Key	13
2.30.	Numeric Key	14
2.31.	PICTURE MODE	14
2.32.	CONTRAST	14
2.33.	BRIGHTNESS.....	15
2.34.	COLOR	15
2.35.	TINT	15
2.36.	SHARPNESS.....	16
2.37.	COLOR TEMPERATURE.....	16
2.38.	DAYLIGHT VIEW	16
2.39.	DIGITAL CINEMA REALITY.....	17
2.40.	NOISE REDUCTION.....	17
2.41.	TV SYSTEM.....	17
2.42.	RGB/YPbPr.....	18
2.43.	CONTRAST - RED.....	18
2.44.	CONTRAST - GREEN.....	18
2.45.	CONTRAST - BLUE.....	19
2.46.	BRIGHTNESS - RED	19
2.47.	BRIGHTNESS - GREEN	19
2.48.	BRIGHTNESS - BLUE	20
2.49.	KEYSTONE	20
2.50.	SHIFT H	20
2.51.	SHIFT V	21
2.52.	OVER SCAN.....	21
2.53.	DOT CLOCK	21
2.54.	CLOCK PHASE	22
2.55.	ASPECT.....	22
2.56.	FRAME LOCK.....	22
2.57.	LANGUAGE	23
2.58.	INPUT GUIDE	23
2.59.	OSD DESIGN	23
2.60.	WARNING MESSAGE	24
2.61.	DVI-I DIGITAL/ANALOG	24
2.62.	EDID Setting	24
2.63.	DVI SIGNAL LEVEL.....	25
2.64.	HDMI SIGNAL LEVEL.....	25
2.65.	CLOSED CAPTION SETTING.....	25
2.66.	SCREEN FORMAT	26

2.67. SCREEN POSITION	26
2.68. STARTUP LOGO	26
2.69. AUTO SETUP	27
2.70. SIGNAL SEARCH	27
2.71. BACK COLOR	27
2.72. WIDE MODE	27
2.73. SXGA MODE	28
2.74. PROJECTOR ID	28
2.75. INITIAL START UP	28
2.76. INSTALLATION	28
2.77. HIGH ALTITUDE MODE	29
2.78. LAMP POWER	29
2.79. SCHEDULE	29
2.80. ECO MANAGEMENT	30
2.81. AMBIENT LIGHT DETECTION	30
2.82. SIGNAL DETECTION	30
2.83. AV MUTE DETECTION	31
2.84. NO SIGNAL SHUT-OFF	31
2.85. STANDBY MODE	31
2.86. EMULATE	32
2.87. AUDIO SETTING - VOLUME	32
2.88. AUDIO SETTING - BALANCE	33
2.89. AUDIO SETTING - IN STANDBY MODE	33
2.90. AUDIO SETTING - POWER BUTTON BEEP	33
2.91. AUDIO SETTING – AUDIO IN SELECT	34
2.92. TEST PATTERN	34
2.93. TEST PATTERN 2	35
2.94. SCHEDULE (PROGRAM SET)	35
2.95. SCHEDULE (PROGRAM EDIT)	36
2.96. SET DATE	36
2.97. SET TIME	37
2.98. NTP SYNCHRONIZATION	37
2.99. WIRELESS LAN	37
2.100. VGA60/480p SET	38
2.101. SELF CHECK	38
2.102. SIDE BY SIDE	38
2.103. SIDE BY SIDE – SUB INPUT	39
2.104. FUNCTION BUTTON 1	39
2.105. FUNCTION BUTTON 1 - 2	39
2.106. FUNCTION BUTTON 2	40
2.107. FUNCTION BUTTON 3	40
2.108. AUDIO MUTE	40

2.109. WIRELESS LAN - OFF	41
2.110. EXT OPTION	41
2.111. Query POWER.....	42
2.112. Query INPUT SELECT.....	42
2.113. Query FREEZE	42
2.114. Query AUTO SETUP.....	43
2.115. Query AV MUTE.....	43
2.116. Query INDEX-WINDOW	43
2.117. Query PICTURE MODE.....	43
2.118. Query CONTRAST	44
2.119. Query BRIGHTNESS	44
2.120. Query COLOR	44
2.121. Query TINT	45
2.122. Query SHARPNESS	45
2.123. Query COLOR TEMPERATURE.....	45
2.124. Query DAYLIGHT VIEW	46
2.125. Query DIGITAL CINEMA REALITY	46
2.126. Query NOISE REDUCTION.....	46
2.127. Query TV SYSTEM.....	47
2.128. Query RGB/YPbPr	47
2.129. Query CONTRAST - RED	47
2.130. Query CONTRAST - GREEN	48
2.131. Query CONTRAST - BLUE	48
2.132. Query BRIGHTNESS - RED	48
2.133. Query BRIGHTNESS - GREEN	49
2.134. Query BRIGHTNESS - BLUE	49
2.135. Query KEYSTONE.....	49
2.136. Query SHIFT H	50
2.137. Query SHIFT V.....	50
2.138. Query OVER SCAN	50
2.139. Query DOT CLOCK	51
2.140. Query CLOCK PHASE.....	51
2.141. Query ASPECT	51
2.142. Query FRAME LOCK	52
2.143. Query LANGUAGE	52
2.144. Query INPUT GUIDE	52
2.145. Query OSD DESIGN.....	53
2.146. Query WARNING MESSAGE	53
2.147. Query DVI-I DIGITAL/ANALOG.....	53
2.148. Query EDID Setting	54
2.149. Query DVI SIGNAL LEVEL	54
2.150. Query HDMI SIGNAL LEVEL	54

2.151. Query CLOSED CAPTION SETTING	55
2.152. Query SCREEN FORMAT	55
2.153. Query SCREEN POSITION	55
2.154. Query STARTUP LOGO.....	56
2.155. Query STARTUP LOGO.....	56
2.156. Query SIGNAL SEARCH	56
2.157. Query BACK COLOR.....	56
2.158. Query WIDE MODE	57
2.159. Query SXGA MODE.....	57
2.160. Query INITIAL START UP	57
2.161. Query INSTALLATION	57
2.162. Query HIGH ALTITUDE MODE.....	58
2.163. Query LAMP POWER.....	58
2.164. Query SCHEDULE.....	58
2.165. Query ECO MANAGEMENT.....	59
2.166. Query AMBIENT LIGHT DETECTION	59
2.167. Query SIGNAL DETECTION.....	59
2.168. Query AV MUTE DETECTION	60
2.169. Query NO SIGNAL SHUT-OFF	60
2.170. Query STANDBY MODE	60
2.171. Query EMULATE.....	61
2.172. Query AUDIO SETTING - VOLUME	61
2.173. Query AUDIO SETTING - BALANCE.....	62
2.174. Query AUDIO SETTING - IN STANDBY MODE.....	62
2.175. Query AUDIO SETTING - POWER BUTTON BEEP	62
2.176. Query AUDIO SETTING – AUDIO IN SELECT	63
2.177. Query SCHEDULE (PROGRAM SET)	64
2.178. Query SCHEDULE (PROGRAM EDIT).....	65
2.179. Query DATE AND TIME	65
2.180. Query DATE	66
2.181. Query TIME.....	66
2.182. Query NTP SYNCHRONIZATION	66
2.183. Query VGA60 / 480p.....	67
2.184. Query DVI SELECT	67
2.185. Query SIDE BY SIDE	67
2.186. Query SIDE BY SIDE – SUB INPUT	68
2.187. Query FUNCTION BUTTON 1	68
2.188. Query FUNCTION BUTTON 1 - 2	68
2.189. Query FUNCTION BUTTON 2	69
2.190. Query FUNCTION BUTTON 3	69
2.191. Query RUNTIME - LAMP	69
2.192. Query LAMP STATUS.....	70

2.193. Query TEMP INFORMATION.....	70
2.194. Query SERIAL NUMBER	70
2.195. Query MAC ADDRESS	70
2.196. Query RUNTIME - PROJECTOR.....	71
2.197. Query LAMP PART No.....	71
2.198. Query LAMP SERIAL NUMBER	71
2.199. Query CCONTROL PANEL OPERATION	72
3. APPENDIX TABHLE.....	72
3.1. SCHEDULE CONTROL COMMAND LIST.....	72
3.2. FNC COMMAND PARAMETERS	73

1. BASIC FORMAT

Transmission from the computer begins with STX, and then the command, parameter and ETX are set in order.
Add parameters according to the details of control.

Basic control command (without parameter)

Start (STX)	ID	Separator (semicolon)	Command	End (ETX)
1 byte	4 bytes	1 byte	3 bytes	1 byte

Basic control command (with parameter)

Start (STX)	ID	Separator (semicolon)	Command	Separator (Colon)	Parameters Undefined	End (ETX)
1 byte	4 bytes	1 byte	3 bytes	1 byte	length	1 byte

ID of the basic control command

Add ID according to the details of control.

When not add ID, it is transmitted as "ID All".

ID	4 bytes String
ID All	ADZZ
ID1	AD01
ID2	AD02
ID3	AD03
ID4	AD04
ID5	AD05
ID6	AD06

Response (Callback) of the basic control command

In the period when the command can be accepted

Differs according to each command

In the period when the command cannot be accepted

Hexadecimal	02h	45h	52h	34h	30h	31h	03h
Character	E	R	4	0	1		

In case of the parameter error or REMOTE2 effective

Hexadecimal	02h	45h	52h	34h	30h	32h	03h
Character	E	R	4	0	2		

Attention:

- No command may be sent or received for 10 to 60 seconds after the lamp starts lighting. They sending お願い any command after that period has elapsed.
- When sending several commands, be sure to wait for a response from the projector, and send the next command after 0.5 seconds or more pass.
- It might take time by the time the response returns because the command is processed in the projector.
Set the time-out to 10 seconds or longer

Note:

- This projector will respond to the computer only in the following case:
When the ID that sent accorded with the ID of the projector.

2. BASIC CONTROL COMMAND

Explanatory notes

- : Enable
- ✗: Disable
- △: Refer to the note.

2.1. Power ON (LAMP ON)

Hexadecimal	02h	50h	4Fh	4Eh	03h
Character	P	O	N		

■ Response (Callback)

In the period when the command can be accepted (This command in power-on condition is included.)

Hexadecimal	02h	50h	4Fh	4Eh	03h
Character	P	O	N		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Note:

- When you confirm whether to have succeeded in power-on, confirm it by QPW (Query Power) command after receiving the callback of PON command.

2.2. Power OFF (STNDBY)

Hexadecimal	02h	50h	4Fh	46h	03h
Character	P	O	F		

■ Response (Callback)

In the period when the command can be accepted (This command in power-on condition is included.)

Hexadecimal	02h	50h	4Fh	46h	03h
Character	P	O	F		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Note:

- When you confirm whether to have succeeded in power-off, confirm it by QPW (Query Power) command after receiving the callback of PON command.

2.3. VOLUME (+) Key

Hexadecimal	02h	41h	55h	55h	03h
Character	A	U	U	U	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	41h	55h	55h	03h
Character	A	U	U	U	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
✗	△	✗	✗

■ Note:

- "IN STANDBY MODE" is "ON" only when, STANDBY when available.

2.4. VOLUME (-) Key

Hexadecimal	02h	41h	55h	44h	03h
Character	A	U	U	D	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	41h	55h	44h	03h
Character	A	U	U	D	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
✗	△	✗	✗

■ Note:

- "IN STANDBY MODE" is "ON" only when, STANDBY when available.

2.5. INPUT SELECT

Hexadecimal Character	02h I	49h I	49h S	53h :	3Ah :	*1 *2	*3 *4	*5 *6	03h
-----------------------	----------	----------	----------	----------	----------	----------	----------	----------	-----

■ Parameters (*1,*2,*3,*4,*5,*6)

COMPUTER1			DVI-I		
Hexadecimal Character	52h R	47h G	31h 1	52h R	47h G
VIDEO			S-VIDEO		
Hexadecimal Character	56h V	49h I	44h D	53h S	56h V
DVI-I			NETWORK		
Hexadecimal Character	44h D	56h V	49h I	4Eh N	57h W
HDMI					
Hexadecimal Character	48h H	44h D	31h 1		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h I	49h I	49h S	53h :	3Ah :	*1 *2	*3 *4	*5 *6	03h
-----------------------	----------	----------	----------	----------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	o

■ Note:

- "IN STANDBY MODE" is "ON" only when, STANDBY when available.
- DVI SELECT COMMAND is effective for RG2 in the case of COMPUTER2.

2.6. FREEZE

Hexadecimal Character	02h O	4Fh F	46h Z	5Ah :	3Ah :	*1 *2	03h
-----------------------	----------	----------	----------	----------	----------	----------	-----

■ Parameters (*1,*2)

	Freeze OFF	Freeze ON
Hexadecimal Character	30h 0	31h 1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh F	46h Z	5Ah :	3Ah :	*1 *2	03h
-----------------------	----------	----------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.7. MENU Key

Hexadecimal Character	02h O	4Fh M	4Dh N	4Eh :	03h
-----------------------	----------	----------	----------	----------	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh M	4Dh N	4Eh :	03h
-----------------------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
o	x	o	x

2.8. RETURN Key

Hexadecimal Character	02h O	4Fh B	42h K	4Bh :	03h
-----------------------	----------	----------	----------	----------	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh B	42h K	4Bh :	03h
-----------------------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
o	x	o	x

2.9. ENTER Key

Hexadecimal	02h	4Fh	45h	4Eh	03h
Character	O	E	N		

■Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	4Fh	45h	4Eh	03h
Character	O	E	N		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
<input type="radio"/>	<input checked="" type="checkbox"/>	<input type="radio"/>	<input checked="" type="checkbox"/>

2.10. UP (↑) Key

Hexadecimal	02h	4Fh	43h	55h	03h
Character	O	C	U		

■Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	4Fh	43h	55h	03h
Character	O	C	U		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
<input type="radio"/>	<input checked="" type="checkbox"/>	<input type="radio"/>	<input checked="" type="checkbox"/>

2.11. DOWN (↓) Key

Hexadecimal	02h	4Fh	43h	44h	03h
Character	O	C	D		

■Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	4Fh	43h	44h	03h
Character	O	C	D		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
<input type="radio"/>	<input checked="" type="checkbox"/>	<input type="radio"/>	<input checked="" type="checkbox"/>

2.12. LEFT (←) Key

Hexadecimal	02h	4Fh	43h	4Ch	03h
Character	O	C	L		

■Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	4Fh	43h	4Ch	03h
Character	O	C	L		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
<input type="radio"/>	<input checked="" type="checkbox"/>	<input type="radio"/>	<input checked="" type="checkbox"/>

2.13. RIGHT (→) Key

Hexadecimal	02h	4Fh	43h	52h	03h
Character	O	C	R		

■Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	4Fh	43h	52h	03h
Character	O	C	R		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
<input type="radio"/>	<input checked="" type="checkbox"/>	<input type="radio"/>	<input checked="" type="checkbox"/>

2.14. DEFAULT Key

Hexadecimal	02h	4Fh	53h	54h	03h
Character	O	S	T		

■Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	4Fh	53h	54h	03h
Character	O	S	T		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
<input type="radio"/>	<input checked="" type="checkbox"/>	<input type="radio"/>	<input checked="" type="checkbox"/>

2.15. AUTO SETUP

Hexadecimal Character	02h O	4Fh A	41h S	53h S	03h
--------------------------	----------	----------	----------	----------	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh A	41h S	53h S	03h
--------------------------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	△	x

■ Note:

- "SIGNAL SEARCH" is "ON" only when, NO SIGNAL when available.

2.16. AV MUTE

Hexadecimal Character	02h O	4Fh S	53h H	48h :	3Ah *1	03h *2
--------------------------	----------	----------	----------	----------	-----------	-----------

■ Parameters (*1,*2)

	AV MUTE OFF	AV MUTE ON
Hexadecimal Character	30h 0	31h 1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh S	53h H	48h :	3Ah *1	03h *2
--------------------------	----------	----------	----------	----------	-----------	-----------

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	○	○

2.17. DIGITAL ZOOM (+) Key

Hexadecimal Character	02h D	44h Z	5Ah U	55h U	03h
--------------------------	----------	----------	----------	----------	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h D	44h Z	5Ah U	55h U	03h
--------------------------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.18. DIGITAL ZOOM (-) Key

Hexadecimal Character	02h D	44h Z	5Ah D	44h D	03h
--------------------------	----------	----------	----------	----------	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h D	44h Z	5Ah D	44h D	03h
--------------------------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.19. INDEX-WINDOW

Hexadecimal Character	02h O	4Fh I	49h X	58h X	03h
--------------------------	----------	----------	----------	----------	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh I	49h X	58h X	03h
--------------------------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.20. FUNCTION 1

Hexadecimal Character	02h F	46h C	43h 1	31h	03h
--------------------------	----------	----------	----------	-----	-----

■Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h F	46h C	43h 1	31h	03h
--------------------------	----------	----------	----------	-----	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	x

2.21. FUNCTION 2

Hexadecimal Character	02h F	46h C	43h 2	32h	03h
--------------------------	----------	----------	----------	-----	-----

■Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h F	46h C	43h 1	31h	03h
--------------------------	----------	----------	----------	-----	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	x

2.22. FUNCTION 3

Hexadecimal Character	02h F	46h C	43h 3	33h	03h
--------------------------	----------	----------	----------	-----	-----

■Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h F	46h C	43h 1	31h	03h
--------------------------	----------	----------	----------	-----	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	x

2.23. SIDE BY SIDE

Hexadecimal Character	02h O	4Fh D	44h 57h	57h W	03h
--------------------------	----------	----------	------------	----------	-----

■Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh D	44h 1	57h	03h
--------------------------	----------	----------	----------	-----	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	x

■Note:

- FW430 Only

2.24. COMPUTER SEARCH

Hexadecimal Character	02h O	4Fh P	50h C	43h	03h
--------------------------	----------	----------	----------	-----	-----

■Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh P	50h C	43h	03h
--------------------------	----------	----------	----------	-----	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	x

2.25. PAGE UP Key

Hexadecimal Character	02h O	4Fh U	55h P	50h P	03h
■ Response (Callback)					
In the period when the command can be accepted					
Hexadecimal Character	02h O	4Fh U	55h P	50h P	03h
Acceptability					
SECURITY	STANDBY	NO SIGNAL	AV MUTE		
x	x	x	x		

2.26. PAGE DOWN Key

Hexadecimal Character	02h O	4Fh D	44h D	50h P	03h
■ Response (Callback)					
In the period when the command can be accepted					
Hexadecimal Character	02h O	4Fh D	44h D	50h P	03h
Acceptability					
SECURITY	STANDBY	NO SIGNAL	AV MUTE		
x	x	x	x		

2.27. MULTI-LIVE Key

Hexadecimal Character	02h O	4Fh M	4Dh M	4Ch L	03h
■ Response (Callback)					
In the period when the command can be accepted					
Hexadecimal Character	02h O	4Fh M	4Dh M	4Ch L	03h
Acceptability					
SECURITY	STANDBY	NO SIGNAL	AV MUTE		
x	x	x	x		

2.28. KEYSTONE selected item display

Hexadecimal Character	02h K	75h S	83h S	84h T	03h
■ Response (Callback)					
In the period when the command can be accepted					
Hexadecimal Character	02h K	75h S	83h S	84h T	03h
Acceptability					
SECURITY	STANDBY	NO SIGNAL	AV MUTE		
○	x	○	x		

2.29. ECO Key

Hexadecimal Character	02h O	4Fh E	45h E	43h C	03h
■ Response (Callback)					
In the period when the command can be accepted					
Hexadecimal Character	02h O	4Fh E	45h E	43h C	03h
Acceptability					
SECURITY	STANDBY	NO SIGNAL	AV MUTE		
x	x	○	x		

2.30. Numeric Key

Hexadecimal Character	02h O	4Fh N	45h K	43h :	3Ah *	*1 *	03h
-----------------------	----------	----------	----------	----------	----------	---------	-----

■ Parameters (*1,*2)

Hexadecimal Character	1 31h 1	2 32h 2	3 33h 3	4 34h 4	5 35h 5	6 36h 6
-----------------------	---------------	---------------	---------------	---------------	---------------	---------------

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh E	45h C	43h :	3Ah *	*1 *	03h
-----------------------	----------	----------	----------	----------	----------	---------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	○	x

2.31. PICTURE MODE

Hexadecimal Character	02h V	56h P	50h M	4Dh :	3Ah *	*1 *	*3 *	*5 *	03h
-----------------------	----------	----------	----------	----------	----------	---------	---------	---------	-----

■ Parameters (*1,*2,*3,*4,*5,*6)

	DYNAMIC			NATURAL			STANDARD			BLACK BOARD		
Hexadecimal Character	44h D	59h Y	4Eh N	4Eh N	41h A	54h T	53h S	54h T	44h D	42h B	42h B	44h D
	CINEMA			WHITE BOARD								
Hexadecimal Character	43h C	49h I	4Eh N	57h W	42h B	44h D						

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h V	56h P	50h M	4Dh :	3Ah *	*1 *	*3 *	*5 *	03h
-----------------------	----------	----------	----------	----------	----------	---------	---------	---------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

■ Note:

- NAT : Still image , CIN : Moving image

2.32. CONTRAST

Hexadecimal Character	02h V	56h C	43h N	4Eh :	3Ah *	*1 *	*3 *	*5 *	03h
-----------------------	----------	----------	----------	----------	----------	---------	---------	---------	-----

■ Parameters (*1,*2,*3,*4,*5,*6)

	-32			-31			-30		
Hexadecimal Character	2Dh -	33h 3	32h 2	2Dh -	33h 3	31h 1	2Dh -	33h 3	30h 0
	30			31			32		
Hexadecimal Character	30h 0	33h 3	30h 0	30h 0	33h 3	31h 1	30h 0	33h 3	32h 2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h V	56h C	43h N	4Eh :	3Ah *	*1 *	*3 *	*5 *	03h
-----------------------	----------	----------	----------	----------	----------	---------	---------	---------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.33. BRIGHTNESS

Hexadecimal Character	02h	56h	42h	52h	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

■ Parameters (*1,*2,*3,*4,*5,*6)

Hexadecimal Character	-32			-31			-30		
Hexadecimal Character	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal Character	30h	33h	30h	30h	33h	31h	30h	33h	32h
	0	3	0	0	3	1	0	3	2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	42h	52h	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.34. COLOR

Hexadecimal Character	02h	56h	43h	4Fh	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

■ Parameters (*1,*2,*3,*4,*5,*6)

Hexadecimal Character	-32			-31			-30		
Hexadecimal Character	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal Character	30h	33h	30h	30h	33h	31h	30h	33h	32h
	0	3	0	0	3	1	0	3	2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	43h	4Fh	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

■ Note:

- This command is acceptable only when moving image is displayed. In other cases, ER401 is returned.

2.35. TINT

Hexadecimal Character	02h	56h	54h	4Eh	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

■ Parameters (*1,*2,*3,*4,*5,*6)

Hexadecimal Character	-32			-31			-30		
Hexadecimal Character	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal Character	30h	33h	30h	30h	33h	31h	30h	33h	32h
	0	3	0	0	3	1	0	3	2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	54h	4Eh	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

■ Note:

- This command is acceptable only when moving image is displayed. In other cases, ER401 is returned.

2.36. SHARPNESS

Hexadecimal Character	02h V	56h S	53h R	52h :	3Ah *	*1 2	*3 4	*5 6	03h
-----------------------	----------	----------	----------	----------	----------	---------	---------	---------	-----

■ Parameters (*1,*2,*3,*4,*5,*6)

Hexadecimal Character	-06			-05			-04		
	2Dh -	30h 0	36h 6	2Dh -	30h 0	35h 5	2Dh -	30h 0	34h 4
Hexadecimal Character	13			14			15		
	30h 0	31h 1	33h 3	30h 0	31h 1	34h 4	30h 0	31h 1	35h 5

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h V	56h S	53h R	52h :	3Ah *	*1 2	*3 4	*5 6	03h
-----------------------	----------	----------	----------	----------	----------	---------	---------	---------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

■ Note:

- This setting range varies according to input signal. If out of range, ER402 is returned.

2.37. COLOR TEMPERATURE

Hexadecimal Character	02h O	4Fh T	54h E	45h :	3Ah *	*1 2	03h	
-----------------------	----------	----------	----------	----------	----------	---------	-----	--

■ Parameters (*1,*2)

	LOW	DEFAULT	HIGH
Hexadecimal Character	30h 0	31h 1	32h 2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh T	54h E	45h :	3Ah *	*1 2	03h	
-----------------------	----------	----------	----------	----------	----------	---------	-----	--

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.38. DAYLIGHT VIEW

Hexadecimal Character	02h V	56h X	58h X	58h :	3Ah D	44h L	4Ch V	56h I	49h
Hexadecimal Character	30h 0	3Dh =	2Dh +	*1 *2	*3 *4	*5 *6	*7 *8	*9 *10	03h

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

FRONT INSTALLATION

	OFF				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	30h 0
AUTO					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	31h 1
ON					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	32h 2

REAR INSTALLATION

	OFF				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	30h 0
ON					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	31h 1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h V	56h X	58h X	58h :	3Ah D	44h L	4Ch V	56h I	49h
Hexadecimal Character	30h 0	3Dh =	2Dh +	*1 *2	*3 *4	*5 *6	*7 *8	*9 *10	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.39. DIGITAL CINEMA REALITY

Hexadecimal Character	02h O	4Fh P	50h D	44h :	3Ah *2	*1	03h
--------------------------	----------	----------	----------	----------	-----------	----	-----

■ Parameters (*1,*2)

	OFF	ON
Hexadecimal Character	30h 0	31h 1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh P	50h D	44h :	3Ah *2	*1	03h
--------------------------	----------	----------	----------	----------	-----------	----	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

■ Note:

- This command is available only when an interlaced signal is inputted. In other cases, ER401 is returned.

2.40. NOISE REDUCTION

Hexadecimal Character	02h V	56h N	4Eh R	52h :	3Ah *2	*1	03h
--------------------------	----------	----------	----------	----------	-----------	----	-----

■ Parameters (*1,*2)

	OFF	ON
Hexadecimal Character	30h 0	31h 1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h V	56h N	4Eh R	52h :	3Ah *2	*1	03h
--------------------------	----------	----------	----------	----------	-----------	----	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

■ Note:

- This command is acceptable only when the input is VIDEO or S-VIDEO. In other cases, ER401 is returned.

2.41. TV SYSTEM

Hexadecimal Character	02h V	56h S	53h G	47h :	3Ah *2	*1	*3	*5	03h *6
--------------------------	----------	----------	----------	----------	-----------	----	----	----	-----------

■ Parameters (*1,*2,*3,*4,*5,*6)

Hexadecimal Character	AUTO			NTSC			NTSC4.43			PAL		
	41h A	55h U	54h T	4Eh N	54h T	53h S	4Eh N	34h 4	34h 4	50h P	41h A	4Ch L
	PAL-M						PAL-N					
Hexadecimal Character	50h P	41h A	4Dh M	50h P	41h A	4Eh N	53h S	45h E	43h C			

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h V	56h S	53h G	47h :	3Ah *2	*1	*3	*5	03h *6
--------------------------	----------	----------	----------	----------	-----------	----	----	----	-----------

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	x

■ Note:

- This command is acceptable only when the input is VIDEO or S-VIDEO. In other cases, ER401 is returned.

2.42. RGB/YPbPr

Hexadecimal Character	02h O	4Fh R	52h F	46h :	3Ah *2	*1	03h
--------------------------	----------	----------	----------	----------	-----------	----	-----

■ Parameters (*1,*2)

	RGB	YPbPr	AOUT
Hexadecimal Character	30h 0	31h 1	32h 2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh R	52h F	46h :	3Ah *2	*1	03h
--------------------------	----------	----------	----------	----------	-----------	----	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	x	x

2.43. CONTRAST - RED

Hexadecimal Character	02h V	56h C	57h 1	52h :	3Ah *2	*1	*3	*5	03h *6
--------------------------	----------	----------	----------	----------	-----------	----	----	----	-----------

■ Parameters (*1,*2,*3,*4,*5,*6)

	-32			-31			-30		
Hexadecimal Character	2Dh —	33h 3	32h 2	2Dh —	33h 3	31h 1	2Dh —	33h 3	30h 0
	30			31			32		
Hexadecimal Character	30h 0	33h 3	30h 0	30h 0	33h 3	31h 1	30h 0	33h 3	32h 2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h V	56h C	57h 1	52h :	3Ah *2	*1	*3	*5	03h *6
--------------------------	----------	----------	----------	----------	-----------	----	----	----	-----------

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.44. CONTRAST - GREEN

Hexadecimal Character	02h V	56h C	57h 2	47h :	3Ah *2	*1	*3	*5	03h *6
--------------------------	----------	----------	----------	----------	-----------	----	----	----	-----------

■ Parameters (*1,*2,*3,*4,*5,*6)

	-32			-31			-30		
Hexadecimal Character	2Dh —	33h 3	32h 2	2Dh —	33h 3	31h 1	2Dh —	33h 3	30h 0
	30			31			32		
Hexadecimal Character	30h 0	33h 3	30h 0	30h 0	33h 3	31h 1	30h 0	33h 3	32h 2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h V	56h C	57h 2	47h :	3Ah *2	*1	*3	*5	03h *6
--------------------------	----------	----------	----------	----------	-----------	----	----	----	-----------

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.45. CONTRAST - BLUE

Hexadecimal Character	02h	56h	57h	42h	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

■ Parameters (*1,*2,*3,*4,*5,*6)

-32			-31			-30			
Hexadecimal Character	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal Character	30h	33h	30h	30h	33h	31h	30h	33h	32h
	0	3	0	0	3	1	0	3	2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	57h	42h	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.46. BRIGHTNESS - RED

Hexadecimal Character	02h	56h	57h	52h	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

■ Parameters (*1,*2,*3,*4,*5,*6)

-32			-31			-30			
Hexadecimal Character	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal Character	30h	33h	30h	30h	33h	31h	30h	33h	32h
	0	3	0	0	3	1	0	3	2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	57h	52h	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.47. BRIGHTNESS - GREEN

Hexadecimal Character	02h	56h	57h	52h	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

■ Parameters (*1,*2,*3,*4,*5,*6)

-32			-31			-30			
Hexadecimal Character	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal Character	30h	33h	30h	30h	33h	31h	30h	33h	32h
	0	3	0	0	3	1	0	3	2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	57h	52h	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.48. BRIGHTNESS - BLUE

Hexadecimal Character	02h	56h	57h	52h	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

■ Parameters (*1,*2,*3,*4,*5,*6)

	-32			-31			-30		
Hexadecimal Character	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal Character	30h	33h	30h	30h	33h	31h	30h	33h	32h
	0	3	0	0	3	1	0	3	2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	57h	52h	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.49. KEYSTONE

Hexadecimal Character	02h	4Fh	4Bh	53h	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

■ Parameters (*1,*2,*3,*4,*5,*6)

	-32			-31			-30		
Hexadecimal Character	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal Character	30h	33h	30h	30h	33h	31h	30h	33h	32h
	0	3	0	0	3	1	0	3	2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	4Fh	4Bh	53h	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	x

2.50. SHIFT H

Hexadecimal Character	02h	56h	48h	50h	3Ah	*1 *2	*3 *4	*5 *6	*7 *8	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	----------	-----

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8)

	-127				-126			
Hexadecimal Character	2Dh	33h	32h	37h	2Dh	33h	32h	36h
	-	1	2	7	-	1	2	6
	126				127			
Hexadecimal Character	30h	33h	32h	36h	30h	33h	32h	37h
	0	1	2	6	0	1	2	7

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	48h	50h	3Ah	*1 *2	*3 *4	*5 *6	*7 *8	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

■ Note:

- This command is not acceptable when the input is NETWORK. In this case, ER401 is returned.

2.51. SHIFT V

Hexadecimal Character	02h V	56h V	56h P	50h :	3Ah *	*1 *2	*3 *4	*5 *6	03h
-----------------------	----------	----------	----------	----------	----------	----------	----------	----------	-----

■ Parameters (*1,*2,*3,*4,*5,*6)

Hexadecimal Character	-64			-63			-62		
	2Dh -	36h 6	34h 4	2Dh -	36h 6	33h 3	2Dh -	36h 6	32h 2
Hexadecimal Character	62			63			64		
	30h 0	36h 6	32h 2	30h 0	36h 6	33h 3	30h 0	36h 6	34h 4

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h V	56h V	56h P	50h :	3Ah *	*1 *2	*3 *4	*5 *6	03h
-----------------------	----------	----------	----------	----------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

■ Note:

- This command is acceptable except when the input is NETWORK. Or, this command is acceptable when the input is NETWORK and ASPECT is H-FIT (for FW430 only). In other cases, ER401 is returned.

2.52. OVER SCAN

Hexadecimal Character	02h M	4Dh O	4Fh V	56h :	3Ah *	*1 *2	03h
-----------------------	----------	----------	----------	----------	----------	----------	-----

■ Parameters (*1,*2,)

Hexadecimal Character	0	1	2	3
	30h 0	31h 1	32h 2	33h 3

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h M	4Dh O	4Fh V	56h :	3Ah *	*1 *2	03h
-----------------------	----------	----------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

■ Note:

- This command is available only when moving image is displayed. In other cases, ER401 is returned.

2.53. DOT CLOCK

Hexadecimal Character	02h V	56h D	44h C	43h :	3Ah *	*1 *2	*3 *4	*5 *6	03h
-----------------------	----------	----------	----------	----------	----------	----------	----------	----------	-----

■ Parameters (*1,*2,*3,*4,*5,*6)

Hexadecimal Character	-32			-31			-30		
	2Dh -	33h 3	32h 2	2Dh -	33h 3	31h 1	2Dh -	33h 3	30h 0
Hexadecimal Character	30			31			32		
	30h 0	33h 3	30h 0	30h 0	33h 3	31h 1	30h 0	33h 3	32h 2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h V	56h D	44h C	43h :	3Ah *	*1 *2	*3 *4	*5 *6	03h
-----------------------	----------	----------	----------	----------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

■ Note:

- Only when the input is COMPUTER IN, and still image is displayed, this command is acceptable. In other cases, ER401 is returned.

2.54. CLOCK PHASE

Hexadecimal Character	02h	56h	43h	50h	3Ah	*1 :	*2 :	*3 :	*5 :	03h
-----------------------	-----	-----	-----	-----	-----	---------	---------	---------	---------	-----

■ Parameters (*1,*2,*3,*4,*5,*6)

Hexadecimal Character	-16			-15			-14		
	2Dh	31h	36h	2Dh	31h	35h	2Dh	31h	34h
Hexadecimal Character	-	1	6	-	1	5	-	1	4
	14			15			16		
Hexadecimal Character	30h	31h	34h	30h	31h	35h	30h	31h	36h
	0	1	4	0	1	5	0	1	6

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	43h	50h	3Ah	*1 :	*2 :	*3 :	*5 :	03h
-----------------------	-----	-----	-----	-----	-----	---------	---------	---------	---------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

■ Note:

- This command is acceptable only when the input is COMPUTER IN. In other cases, ER401 is returned.

2.55. ASPECT

Hexadecimal Character	02h	56h	53h	31h	3Ah	*1 :	*2 :	*3 :	03h
-----------------------	-----	-----	-----	-----	-----	---------	---------	---------	-----

■ Parameters (*1,*2,*3,*4)

▪ FX400

Hexadecimal Character	AUTO		NORMAL		WIDE		S4:3		NATIVE	
	30h	30h	30h	31h	30h	32h	30h	33h	30h	35h
Hexadecimal Character	0	0	0	1	0	2	0	3	0	5
	FULL		H-FIT		V-FIT					
Hexadecimal Character	30h	36h	30h	39h	31h	30h				
	0	6	0	9	1	0				

▪ FW430

Hexadecimal Character	AUTO		S4:3		NORMAL		NATIVE		FULL	
	30h	30h	30h	31h	30h	32h	30h	35h	30h	36h
Hexadecimal Character	0	0	0	1	0	2	0	5	0	6
	H-FIT		V-FIT							
Hexadecimal Character	30h	39h	31h	30h						
	0	9	1	0						

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	53h	31h	3Ah	*1 :	*2 :	*3 :	03h
-----------------------	-----	-----	-----	-----	-----	---------	---------	---------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.56. FRAME LOCK

Hexadecimal Character	02h	56h	46h	4Ch	3Ah	*1 :	03h
-----------------------	-----	-----	-----	-----	-----	---------	-----

■ Parameters (*1,*2)

Hexadecimal Character	OFF		ON	
	30h	31h		
Character	0	1		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	46h	4Ch	3Ah	*1 :	03h
-----------------------	-----	-----	-----	-----	-----	---------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.57. LANGUAGE

Hexadecimal Character	02h O	4Fh L	4Ch G	47h :	3Ah :	*1 *2	*3 *4	*5 *6	03h
--------------------------	----------	----------	----------	----------	----------	----------	----------	----------	-----

■ Parameters (*1,*2,*3,*4,*5,*6,)

Hexadecimal Character	English			German			French		
	45h E	4Eh N	47h G	44h D	45h E	55h U	46h F	52h R	41h A
Hexadecimal Character	Spanish			Italian			Japanese		
	45h E	53h S	50h P	49h I	54h T	4Ch L	4Ah J	50h P	4Eh N
Hexadecimal Character	Chinese			Russian			Korean		
	43h C	48h H	49h I	52h R	55h U	53h S	4Bh K	4Fh O	52h R
Hexadecimal Character	Portuguese			Swedish			Norwegian		
	50h P	4Fh O	52h R	53h S	56h V	45h E	4Eh N	4Fh O	52h R
Hexadecimal Character	Danish			Polish			Czech		
	44h D	41h A	4Eh N	50h P	4Fh O	4Ch L	43h C	45h E	53h S
Hexadecimal Character	Hungarian			Thai					
	4Dh M	41h A	47h G	54h T	48h H	41h A			

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh L	4Ch G	47h :	3Ah :	*1 *2	*3 *4	*5 *6	03h
--------------------------	----------	----------	----------	----------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.58. INPUT GUIDE

Hexadecimal Character	02h O	4Fh I	49h D	44h :	3Ah :	*1 *2	03h
--------------------------	----------	----------	----------	----------	----------	----------	-----

■ Parameters (*1,*2)

Hexadecimal Character	OFF 0	SIMPLE 1	DETAILED 2
--------------------------	----------	-------------	---------------

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh I	49h D	44h :	3Ah :	*1 *2	03h
--------------------------	----------	----------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.59. OSD DESIGN

Hexadecimal Character	02h M	4Dh O	4Fh D	44h :	3Ah :	*1 *2	03h
--------------------------	----------	----------	----------	----------	----------	----------	-----

■ Parameters (*1,*2)

Hexadecimal Character	TYPE1 30h 0	TYPE2 31h 1	TYPE3 32h 2
--------------------------	-------------------	-------------------	-------------------

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h M	4Dh O	4Fh D	44h :	3Ah :	*1 *2	03h
--------------------------	----------	----------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.60. WARNING MESSAGE

Hexadecimal Character	02h	56h	58h	58h	3Ah	57h	4Dh	44h	49h
Character	V	X	X	:	W	M	D	I	
Hexadecimal Character	30h	3Dh	2Dh	*1	*3	*5	*7	*9	03h

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

OFF				
Hexadecimal Character	30h	30h	30h	30h
Character	0	0	0	0
ON				
Hexadecimal Character	30h	30h	30h	30h
Character	0	0	0	1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	58h	58h	3Ah	57h	4Dh	44h	49h
Character	V	X	X	:	W	M	D	I	
Hexadecimal Character	30h	3Dh	2Dh	*1	*3	*5	*7	*9	03h
Character	0	=	+	*2	*4	*6	*8	*10	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	o

2.61. DVI-I DIGITAL/ANALOG

Hexadecimal Character	02h	56h	58h	58h	3Ah	44h	44h	41h	49h
Character	V	X	X	:	D	D	A	I	
Hexadecimal Character	30h	3Dh	2Dh	*1	*3	*5	*7	*9	03h

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

DIGITAL				
Hexadecimal Character	30h	30h	30h	30h
Character	0	0	0	0
ANALOG				
Hexadecimal Character	30h	30h	30h	31h
Character	0	0	0	1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	58h	58h	3Ah	44h	44h	41h	49h
Character	V	X	X	:	D	D	A	I	
Hexadecimal Character	30h	3Dh	2Dh	*1	*3	*5	*7	*9	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	x

2.62. EDID Setting

Hexadecimal Character	02h	4Fh	45h	44h	3Ah	*1	03h
Character	O	E	D	:	*	2	

■ パラメーター(*1,*2)

EDID1 (Moving image)		EDID2(PC)
Hexadecimal Character	31h	32h
Character	1	2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	4Fh	45h	44h	3Ah	*1	03h
Character	O	E	D	:	*	2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.63. DVI SIGNAL LEVEL

Hexadecimal Character	02h	56h V	58h X	58h X	3Ah :	44h D	56h V	49h I	49h I
Hexadecimal Character	30h 0	3Dh =	2Dh +	*1 *2	*3 *4	*5 *6	*7 *8	*9 *10	03h 03h

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

0-255(PC)				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0
16-235				
Hexadecimal Character	30h 0	30h 0	30h 0	31h 1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h V	58h X	58h X	3Ah :	44h D	56h V	49h I	49h I
Hexadecimal Character	30h 0	3Dh =	2Dh +	*1 *2	*3 *4	*5 *6	*7 *8	*9 *10	03h 03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	o

2.64. HDMI SIGNAL LEVEL

Hexadecimal Character	02h	56h V	58h X	58h X	3Ah :	48h H	53h S	4Ch L	49h I
Hexadecimal Character	30h 0	3Dh =	2Dh +	*1 *2	*3 *4	*5 *6	*7 *8	*9 *10	03h 03h

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

0-1023				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0
64-940				
Hexadecimal Character	30h 0	30h 0	30h 0	31h 1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h V	58h X	58h X	3Ah :	48h H	53h S	4Ch L	49h I
Hexadecimal Character	30h 0	3Dh =	2Dh +	*1 *2	*3 *4	*5 *6	*7 *8	*9 *10	03h 03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	o

2.65. CLOSED CAPTION SETTING

Hexadecimal Character	02h	4Fh O	43h C	43h C	3Ah :	*1 *2	03h
-----------------------	-----	----------	----------	----------	----------	----------	-----

■ Parameters (*1,*2)

	OFF	CC1	CC2	CC3	CC4
Hexadecimal Character	30h 0	31h 1	32h 2	33h 3	34h 4

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	4Fh O	43h C	43h C	3Ah :	*1 *2	03h
-----------------------	-----	----------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

■ Note:

- Input signal is 480i (YPbPr) or NTSC, this command is available.

2.66. SCREEN FORMAT

Hexadecimal Character	02h	56h	53h	46h	3Ah	*1 *2	03h
-----------------------	-----	-----	-----	-----	-----	----------	-----

■ Parameters (*1,*2)

	16:10	16:9
Hexadecimal Character	30h 0	31h 1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	53h	46h	3Ah	*1 *2	03h
-----------------------	-----	-----	-----	-----	-----	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	x

■ Note:

- This command is available only for FW430.

2.67. SCREEN POSITION

Hexadecimal Character	02h	56h	58h	58h	3Ah	56h	53h	50h	49h
Hexadecimal Character	31h	3Dh	2Dh	*1 +	*3 *2	*5 *4	*7 *6	*9 *8	03h *10

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

	LOW				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	30h 0
CENTER					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	31h 1
HIGHT					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	32h 2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	58h	58h	3Ah	56h	53h	50h	49h
Hexadecimal Character	30h	3Dh	2Dh	*1 +	*3 *2	*5 *4	*7 *6	*9 *8	03h *10

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	x

■ Note:

- This command is available only for FW430.

2.68. STARTUP LOGO

Hexadecimal Character	02h	4Dh	4Ch	4Fh	3Ah	*1 *2	03h
-----------------------	-----	-----	-----	-----	-----	----------	-----

■ Parameters (*1,*2)

	OFF	DEFAULT	TEXT	USER
Hexadecimal Character	30h 0	31h 1	32h 2	32h 2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	4Dh	4Ch	4Fh	3Ah	*1 *2	03h
Hexadecimal Character	M	L	O	:	3Ah	: *2	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.69. AUTO SETUP

Hexadecimal Character	02h O	4Fh S	53h S	53h :	3Ah *2	*1	03h
--------------------------	----------	----------	----------	----------	-----------	----	-----

■ Parameters (*1,*2)

	BUTTON	AUTO
Hexadecimal Character	30h 0	31h 1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh S	53h S	53h :	3Ah *2	*1	03h
--------------------------	----------	----------	----------	----------	-----------	----	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.70. SIGNAL SEARCH

Hexadecimal Character	02h O	4Fh S	53h R	52h :	3Ah *2	*1	03h
--------------------------	----------	----------	----------	----------	-----------	----	-----

■ Parameters (*1,*2)

	OFF	ON
Hexadecimal Character	30h 0	31h 1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh S	53h R	52h :	3Ah *2	*1	03h
--------------------------	----------	----------	----------	----------	-----------	----	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.71. BACK COLOR

Hexadecimal Character	02h O	4Fh B	42h C	43h :	3Ah *2	*1	03h
--------------------------	----------	----------	----------	----------	-----------	----	-----

■ Parameters (*1,*2)

	BLUE	BLACK	DEFAULT	USER
Hexadecimal Character	30h 0	31h 1	32h 2	33h 3

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh B	42h C	43h :	3Ah *2	*1	03h
--------------------------	----------	----------	----------	----------	-----------	----	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	x

2.72. WIDE MODE

Hexadecimal Character	02h O	4Fh X	58h G	47h :	3Ah *2	*1	03h
--------------------------	----------	----------	----------	----------	-----------	----	-----

■ Parameters (*1,*2)

	OFF	ON	AUTO
Hexadecimal Character	30h 0	31h 1	32h 2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh X	58h G	47h :	3Ah *2	*1	03h
--------------------------	----------	----------	----------	----------	-----------	----	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.73. SXGA MODE

Hexadecimal	02h	4Fh	53h	58h	3Ah	*1	03h
Character	O	S	X	:	*	2	

■ Parameters (*1,*2)

	SXGA	SXGA+
Hexadecimal	30h	31h
Character	0	1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	4Fh	53h	58h	3Ah	*1	03h
Character	O	S	X	:	*	2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.74. PROJECTOR ID

Hexadecimal	02h	52h	49h	53h	3Ah	*1	03h
Character	R	I	S	:	*	2	

■ Parameters (*1,*2)

	ALL	ID 1	ID 2	ID 3	ID 4	ID 5	ID 6
Hexadecimal	30h	31h	32h	33h	34h	35h	36h
Character	0	1	2	3	4	5	6

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	52h	49h	53h	3Ah	*1	03h
Character	R	I	S	:	*	2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.75. INITIAL START UP

Hexadecimal	02h	4Fh	50h	59h	3Ah	*1	03h
Character	O	P	Y	:	*	2	

■ Parameters (*1,*2)

	STANDBY	ON	LAST MEMORY
Hexadecimal	30h	31h	32h
Character	0	1	2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	4Fh	50h	59h	3Ah	*1	03h
Character	O	P	Y	:	*	2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	o

2.76. INSTALLATION

Hexadecimal	02h	4Fh	49h	4Ch	3Ah	*1	03h
Character	O	I	L	:	*	2	

■ Parameters (*1,*2)

	FRONT/DESK	REAR/DESK	FRONT / CEILING	REAR/CEILING
Hexadecimal	30h	31h	32h	33h
Character	0	1	2	3

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	4Fh	49h	4Ch	3Ah	*1	03h
Character	O	I	L	:	*	2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	x

2.77. HIGH ALTITUDE MODE

Hexadecimal Character	02h O	4Fh F	46h M	4Dh :	3Ah *2	*1	03h
-----------------------	----------	----------	----------	----------	-----------	----	-----

■ Parameters (*1,*2)

	OFF	ON
Hexadecimal Character	30h 0	31h 1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh F	46h M	4Dh :	3Ah *2	*1	03h
-----------------------	----------	----------	----------	----------	-----------	----	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.78. LAMP POWER

Hexadecimal Character	02h O	4Fh L	4Ch P	50h :	3Ah *2	*1	03h
-----------------------	----------	----------	----------	----------	-----------	----	-----

■ Parameters (*1,*2)

	ECO	NORMAL
Hexadecimal Character	30h 0	31h 1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh L	4Ch P	50h :	3Ah *2	*1	03h
-----------------------	----------	----------	----------	----------	-----------	----	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.79. SCHEDULE

Hexadecimal Character	02h V	56h X	58h X	58h :	3Ah *1	53h S	43h C	48h H	49h I
Hexadecimal Character	30h 0	3Dh =	2Dh +	58h *2	3Ah *3	53h *5	43h *7	48h *9	49h 03h

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

	OFF				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	30h 0
ON					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	31h 1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h V	56h X	58h X	58h :	3Ah *1	53h S	43h C	48h H	49h I
Hexadecimal Character	30h 0	3Dh =	2Dh +	58h *2	3Ah *3	53h *5	43h *7	48h *9	49h 03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.80. ECO MANAGEMENT

Hexadecimal Character	02h	56h	58h	58h	3Ah	45h	43h	4Fh	49h
	Character	V	X	X	:	E	C	O	I
Hexadecimal Character	30h	3Dh	2Dh	*1	*3	*5	*7	*9	03h

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

	OFF				
Hexadecimal Character	30h	30h	30h	30h	30h
ON					
Hexadecimal Character	30h	30h	30h	30h	31h

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	58h	58h	3Ah	45h	43h	4Fh	49h
	Character	V	X	X	:	E	C	O	I
Hexadecimal Character	30h	3Dh	2Dh	*1	*3	*5	*7	*9	03h
Character	0	=	+	*2	*4	*6	*8	*10	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.81. AMBIENT LIGHT DETECTION

Hexadecimal Character	02h	56h	58h	58h	3Ah	45h	43h	4Fh	49h
	Character	V	X	X	:	E	C	O	I
Hexadecimal Character	31h	3Dh	2Dh	*1	*3	*5	*7	*9	03h

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

	OFF				
Hexadecimal Character	30h	30h	30h	30h	30h
ON					
Hexadecimal Character	30h	30h	30h	30h	31h

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	58h	58h	3Ah	45h	43h	4Fh	49h
	Character	V	X	X	:	E	C	O	I
Hexadecimal Character	31h	3Dh	2Dh	*1	*3	*5	*7	*9	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.82. SIGNAL DETECTION

Hexadecimal Character	02h	56h	58h	58h	3Ah	45h	43h	4Fh	49h
	Character	V	X	X	:	E	C	O	I
Hexadecimal Character	32h	3Dh	2Dh	*1	*3	*5	*7	*9	03h

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

	OFF				
Hexadecimal Character	30h	30h	30h	30h	30h
ON					
Hexadecimal Character	30h	30h	30h	30h	31h

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	58h	58h	3Ah	45h	43h	4Fh	49h
	Character	V	X	X	:	E	C	O	I
Hexadecimal Character	32h	3Dh	2Dh	*1	*3	*5	*7	*9	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.83. AV MUTE DETECTION

Hexadecimal Character	02h	56h	58h	58h	3Ah	45h	43h	4Fh	49h
	V	X	X	:	E	C	O	I	
Hexadecimal Character	33h	3Dh	2Dh	*1	*3	*5	*7	*9	03h

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

	OFF				
Hexadecimal Character	30h	30h	30h	30h	30h
	0	0	0	0	0
	ON				
Hexadecimal Character	30h	30h	30h	30h	31h
	0	0	0	0	1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	58h	58h	3Ah	45h	43h	4Fh	49h
	V	X	X	:	E	C	O	I	
Hexadecimal Character	33h	3Dh	2Dh	*1	*3	*5	*7	*9	03h
	3	=	+	*2	*4	*6	*8	*10	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.84. NO SIGNAL SHUT-OFF

Hexadecimal Character	02h	4Fh	41h	46h	3Ah	*1	*3	03h
	V	O	A	F	:	*2	*4	

■ Parameters (*1,*2,*3,*4)

	OFF		15	60
Hexadecimal Character	30h	30h	31h	35h
	0	0	1	5

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	4Fh	41h	46h	3Ah	*1	*3	03h
	V	O	A	F	:	*2	*4	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.85. STANDBY MODE

Hexadecimal Character	02h	56h	58h	58h	3Ah	53h	54h	4Dh	49h
	V	X	X	:	S	T	M	I	
Hexadecimal Character	30h	3Dh	2Dh	*1	*3	*5	*7	*9	03h

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

	NORMAL				
Hexadecimal Character	30h	30h	30h	30h	30h
	0	0	0	0	0
	ECO				
Hexadecimal Character	30h	30h	30h	30h	33h
	0	0	0	0	3

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	58h	58h	3Ah	53h	54h	4Dh	49h
	V	X	X	:	S	T	M	I	
Hexadecimal Character	30h	3Dh	2Dh	*1	*3	*5	*7	*9	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.86. EMULATE

Hexadecimal Character	02h	56h	58h	58h	3Ah	45h	4Dh	55h	49h
Hexadecimal Character	30h	3Dh	2Dh	*1	*3	*5	*7	*9	03h

■Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

DEFAULT				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 1
D3500				
Hexadecimal Character	30h 0	30h 0	30h 0	32h 2
D4000				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 3
D/W5k Series				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 4
D/W/Z6k Series				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 5
L730				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 6
L780				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 7
L735				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 8
L785				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 9
LB/W Series				
Hexadecimal Character	30h 0	30h 0	30h 0	31h 1
				30h 0

■Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	58h	58h	3Ah	45h	4Dh	55h	49h
Hexadecimal Character	30h	3Dh	2Dh	*1	*3	*5	*7	*9	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	o

2.87. AUDIO SETTING - VOLUME

Hexadecimal Character	02h	41h	56h	4Ch	3Ah	*1	*3	*5	03h
Hexadecimal Character	A	V	L	:	*2	*4	*6	*8	03h

■Parameters (*1,*2,*3,*4,*5,*6)

Hexadecimal Character	0			1			2		
	30h 0	30h 0	30h 0	30h 0	30h 0	31h 1	30h 0	30h 0	32h 2
Hexadecimal Character	61			62			63		
	30h 0	36h 6	31h 1	30h 0	36h 6	32h 2	30h 0	36h 6	33h 3

■Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	41h	56h	4Ch	3Ah	*1	*3	*5	03h
Hexadecimal Character	A	V	L	:	*2	*4	*6	*8	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	△	x	x

■Note:

- During STANDBY, this command is available only when "IN STANDBY MODE "is ON.

2.88. AUDIO SETTING - BALANCE

Hexadecimal Character	02h	41h	42h	4Ch	3Ah	*1 :	*2 :	*3 :	*5 :	03h
		A	B	L	:					

■ Parameters (*1,*2,*3,*4,*5,*6)

Hexadecimal Character	-16			-15			-14		
	2Dh	31h	36h	2Dh	31h	35h	2Dh	31h	34h
Hexadecimal Character	-	1	6	-	1	5	-	1	4
Hexadecimal Character	14			15			16		
	30h	31h	34h	30h	31h	35h	30h	31h	36h
	0	1	4	0	1	5	0	1	6

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	41h	42h	4Ch	3Ah	*1 :	*2 :	*3 :	*5 :	03h
		A	B	L	:					

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	△	x	x

■ Note:

- During STANDBY, this command is available only when "IN STANDBY MODE" is ON.

2.89. AUDIO SETTING - IN STANDBY MODE

Hexadecimal Character	02h	56h	58h	58h	3Ah	41h	53h	42h	49h
		V	X	X	:	A	S	B	I

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

Hexadecimal Character	OFF				
	30h	30h	30h	30h	30h
ON					
Hexadecimal Character	30h	30h	30h	30h	31h
	0	0	0	0	1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	58h	58h	3Ah	41h	53h	42h	49h
		V	X	X	:	A	S	B	I

Hexadecimal Character	30h	3Dh	2Dh	*1	*3	*5	*7	*9	03h
	0	=	+	*2	*4	*6	*8	*10	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	○	○	○

2.90. AUDIO SETTING - POWER BUTTON BEEP

Hexadecimal Character	02h	56h	58h	58h	3Ah	42h	45h	50h	49h
		V	X	X	:	B	E	P	I

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

Hexadecimal Character	OFF				
	30h	30h	30h	30h	30h
ON					
Hexadecimal Character	30h	30h	30h	30h	33h
	0	0	0	0	3

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	58h	58h	3Ah	42h	45h	50h	49h
		V	X	X	:	B	E	P	I

Hexadecimal Character	30h	3Dh	2Dh	*1	*3	*5	*7	*9	03h
	0	=	+	*2	*4	*6	*8	*10	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	○	○	○

2.91. AUDIO SETTING – AUDIO IN SELECT

Hexadecimal Character	02h	56h V	58h X	58h X	3Ah :	41h A	49h I	4Eh N	49h I
Hexadecimal Character	*1 *2	3Dh =	2Dh +	*3 *4	*5 *6	*7 *8	*9 *10	*11 *12	03h

■Parameters (*1,*2)

	COMPUTER1	DVI-I	HDMI
Hexadecimal Character	30h 0	32h 2	33h 3
	VIDEO	S-VIDEO	NETWORK
Hexadecimal Character	34h 4	35h 5	36h 6

■Parameters (*3,*4,*5,*6,*7,*8,*9,*10,*11,*12)

	AUDIO IN 1				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	30h 0
	AUDIO IN 2				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	31h 1
	AUDIO IN 3				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	32h 2
	HDMI AUDIO IN				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	33h 3
	NETWORK AUDIO IN				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	34h 4

■Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h V	58h X	58h X	3Ah :	41h A	49h I	4Eh N	49h I
Hexadecimal Character	*1 *2	3Dh =	2Dh +	*3 *4	*5 *6	*7 *8	*9 *10	*11 *12	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	x

■Note:

- Can choose "HDMI AUDIO IN", when HDMI input only.
- Can choose "NETWORK AUDIO IN", when NETWORK input only.

2.92. TEST PATTERN

Hexadecimal Character	02h	4Fh O	53h S	56h V	03h
-----------------------	-----	----------	----------	----------	-----

■Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	4Fh O	53h S	56h V	03h
-----------------------	-----	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	x

2.93. TEST PATTERN 2

Hexadecimal Character	02h O	4Fh T	54h S	53h :	3Ah *	*1 2	03h
-----------------------	----------	----------	----------	----------	----------	---------	-----

■ Parameters (*1,*2)

	All whit	Color bars	White cross on black background	Black cross on white background	Cross hatch
Hexadecimal Character	30h 0	31h 1	32h 2	33h 3	34h 4
	Dots	Vertical lines	Horizontal lines	Focus	
Hexadecimal Character	35h 5	36h 6	37h 7	38h 8	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh T	54h S	53h :	3Ah *	*1 2	03h
-----------------------	----------	----------	----------	----------	----------	---------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	x

2.94. SCHEDULE (PROGRAM SET)

Hexadecimal Character	02h V	56h X	58h X	58h :	3Ah S	53h P	50h G	49h I
Hexadecimal Character	*1 *2	3Dh =	2Dh +	*3 *4	*5 *6	*7 *8	*9 *10	*11 *12

■ Parameters (*1,*2)

	SUN	MON	TUE	WED	THU	FRI	SAT
Hexadecimal Character	30h 0	31h 1	32h 2	33h 3	34h 4	35h 5	36h 6

■ Parameters (*3,*4,*5,*6,*7,*8,*9,*10,*11,*12)

	OFF (Disable set)				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	30h 0
PROGRAM1					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	31h 1
PROGRAM2					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	32h 2
PROGRAM3					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	33h 3
PROGRAM4					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	34h 4
PROGRAM5					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	35h 5
PROGRAM6					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	36h 6
PROGRAM7					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	37h 7

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h V	56h X	58h X	58h :	3Ah S	53h P	50h G	49h I
Hexadecimal Character	*1 *2	3Dh =	2Dh +	*3 *4	*5 *6	*7 *8	*9 *10	*11 *12

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.95. SCHEDULE (PROGRAM EDIT)

Hexadecimal Character	02h	56h	58h	58h	3Ah	53h	43h	43h	53h	*1
Hexadecimal Character	3Dh	*3	*5	*7	*9	*11	*13	*15	*17	*2

■ Parameters (*1, *2)

program from No.						
Hexadecimal Character	31h	32h	33h	34h	35h	36h
Character	1	2	3	4	5	6

■ Parameters (*3, *4, *5, *6)

COMMAND No. (decimal number) 01~16				
Hexadecimal Character	30h	31h	...	36h
Character	0	1		6

■ Parameters (*7, *8, *9, *10)

COMMAND 00~FF				
Hexadecimal Character	30h	30h	...	46h
Character	0	0		F

□ Refer to "3.1 SCHEDULE CONTROL COMMAND LIST" of the APPENDIX TABLE.

■ Parameters (*11, *12, *13, *14)

Hour 00~23				
Hexadecimal Character	30h	30h	...	33h
Character	0	0		3

■ Parameters (*15, *16, *17, *18)

Minute 00~59				
Hexadecimal Character	30h	30h	...	39h
Character	0	0		9

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	58h	58h	3Ah	53h	43h	43h	53h	*1
Hexadecimal Character	V	X	X	:	S	C	C	S	*2	
Hexadecimal Character	3Dh	*3	*5	*7	*9	*11	*13	*15	*17	03h
Hexadecimal Character	=	*4	*6	*8	*10	*12	*14	*16	*18	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.96. SET DATE

Hexadecimal Character	02h	54h	53h	44h	3Ah	:
Hexadecimal Character	*y1	*y2	*y3	*y4	*m1	*m2

■ Parameters

*y1~*y4 : Year (4 digits)

*m1~*m2 : Month (2 digits)

*d1~*d2 : Day (2 digits)

*w : Day of the week (Mon = 1, Tue = 2, Wed = 3, Thu = 4, Fri = 5, Sat = 6, Sun = 7)

Set it by UTC (Coordinated Universal Time).

Example : Tuesday, April 1, 2008

Hexadecimal Character	*y1	*y2	*y3	*y4	*m1	*m2	*d1	*d2	*w
Character	32h	30h	30h	38h	30h	34h	30h	31h	32h

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	54h	53h	44h	3Ah	*y1	*y2
Hexadecimal Character	T	S	D	:			

Hexadecimal Character	*y3	*y4	*m1	*m2	*d1	*d2	*w
Character							03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.97. SET TIME

Hexadecimal Character	02h	54h	53h	54h	3Ah		
Hexadecimal Character	*h1	*h2	*m1	*m2	*s1	*s2	03h

■ Parameters

*h1~*h2 : Hour (2 digits)

*m1~*m2 : Minute (2 digits)

*s1~*s2 : Second (2 digits)

Set it by UTC (Coordinated Universal Time).

Example: 3 seconds at 3:45 p.m.

Hexadecimal Character	*h1	*h2	*m1	*m2	*s1	*s2	
Hexadecimal Character	31h	35h	34h	35h	30h	33h	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	54h	53h	54h	3Ah		
Hexadecimal Character	*h1	*h2	*m1	*m2	*s1	*s2	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.98. NTP SYNCHRONIZATION

Hexadecimal Character	02h	56h	58h	58h	3Ah	4Eh	54h	50h	49h
Hexadecimal Character	30h	3Dh	2Dh	*1	*3	*5	*7	*9	03h

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

OFF				
Hexadecimal Character	30h	30h	30h	30h
ON				
Hexadecimal Character	30h	30h	30h	31h

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	58h	58h	3Ah	4Eh	54h	50h	49h
Hexadecimal Character	30h	3Dh	2Dh	*1	*3	*5	*7	*9	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.99. WIRELESS LAN

Hexadecimal Character	02h	4Fh	4Eh	53h	3Ah	*1	*3	*5	03h
Hexadecimal Character	O	N	S	:		*2	*4	*6	

■ Parameters (*1,*2,*3,*4,*5,*6,)

Character	OFF			1			2		
	30h	30h	30h	30h	30h	31h	30h	30h	32h
Character	0	0	0	0	0	1	0	0	2
	3			4			USER1		
Character	30h	30h	33h	30h	30h	34h	30h	30h	35h
	0	0	3	0	0	4	0	0	5
USER2			USER3			S-MAP			
Character	30h	30h	36h	30h	30h	37h	30h	30h	38h
	0	0	6	0	0	7	0	0	8

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	4Fh	4Eh	53h	3Ah	*1	*3	*5	03h
Hexadecimal Character	O	N	S	:		*2	*4	*6	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.100. VGA60/480p SET

Hexadecimal	02h	4Fh	56h	35h	3Ah	*1	03h
Character	O	V	5	5	:	*2	

■ Parameters (*1,*2)

	VGA60	480p	AUTO
Hexadecimal	30h	31h	32h
Character	0	1	2

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	4Fh	56h	35h	3Ah	*1	03h
Character	O	V	5	5	:	*2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.101. SELF CHECK

Hexadecimal	02h	4Fh	53h	43h	03h
Character	O	V	S	C	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	4Fh	53h	43h	03h
Character	O	V	S	C	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
o	x	o	x

2.102. SIDE BY SIDE

Hexadecimal	02h	4Fh	50h	50h	3Ah	*1	03h
Character	O	V	P	P	:	*2	

■ Parameters (*1,*2)

	OFF	ON
Hexadecimal	30h	31h
Character	0	1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	4Fh	50h	50h	3Ah	*1	03h
Character	O	V	P	P	:	*2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	x

■ Note:

- This command is available only for FW430.

2.103. SIDE BY SIDE – SUB INPUT

Hexadecimal Character	02h	53h	49h	53h	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

■ Parameters (*1,*2,*3,*4,*5,*6,)

Hexadecimal Character	COMPUTER1			NETWORK		
	R	G	I	N	W	P
VIDEO				S-VIDEO		
Character	V	I	D	S	V	D
DVI-I				HDMI		
Character	D	V	I	H	D	1

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	53h	49h	53h	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	△	△

■ Note:

- △ : Acceptable only at the time of "SIDE BY SIDE" mode.

2.104. FUNCTION BUTTON 1

Hexadecimal Character	02h	4Fh	46h	43h	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

■ Parameters (*1,*2,*3,*4,*5,*6,)

Hexadecimal Character	Parameters								
	Refer to "3.2 FNC COMMAND PARAMETERS" of the APPENDIX TABLE.								

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	4Fh	46h	43h	3Ah	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	-----	-----	-----	-----	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	o	o	o

2.105. FUNCTION BUTTON 1 - 2

Hexadecimal Character	02h	56h	58h	58h	3Ah	46h	4Eh	43h	49h
Hexadecimal Character	30h	3Dh	2Dh	*1 *2	*3 *4	*5 *6	*7 *8	*9 *10	03h

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

Hexadecimal Character	Parameters								
	Refer to "3.2 FNC COMMAND PARAMETERS" of the APPENDIX TABLE.								

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h	58h	58h	3Ah	46h	4Eh	43h	49h
Hexadecimal Character	30h	3Dh	2Dh	*1 *2	*3 *4	*5 *6	*7 *8	*9 *10	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.106. FUNCTION BUTTON 2

Hexadecimal Character	02h	56h V	58h X	58h X	3Ah :	46h F	4Eh N	43h C	49h I
Hexadecimal Character	31h 1	3Dh =	2Dh +	*1 *2	*3 *4	*5 *6	*7 *8	*9 *10	03h

■Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

		Parameters							
Hexadecimal Character		Refer to "3.2 FNC COMMAND PARAMETERS" of the APPENDIX TABLE.							

■Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h V	58h X	58h X	3Ah :	46h F	4Eh N	43h C	49h I
Hexadecimal Character	31h 1	3Dh =	2Dh +	*1 *2	*3 *4	*5 *6	*7 *8	*9 *10	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.107. FUNCTION BUTTON 3

Hexadecimal Character	02h	56h V	58h X	58h X	3Ah :	46h F	4Eh N	43h C	49h I
Hexadecimal Character	32h 2	3Dh =	2Dh +	*1 *2	*3 *4	*5 *6	*7 *8	*9 *10	03h

■Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

		Parameters							
Hexadecimal Character		Refer to "3.2 FNC COMMAND PARAMETERS" of the APPENDIX TABLE.							

■Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	56h V	58h X	58h X	3Ah :	46h F	4Eh N	43h C	49h I
Hexadecimal Character	32h 2	3Dh =	2Dh +	*1 *2	*3 *4	*5 *6	*7 *8	*9 *10	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	x	x

2.108. AUDIO MUTE

Hexadecimal Character	02h	41h A	4Dh M	54h T	3Ah :	*1 *2	03h
-----------------------	-----	----------	----------	----------	----------	----------	-----

■Parameters (*1,*2)

Hexadecimal Character	30h 0	31h 1
-----------------------	----------	----------

■Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	41h A	4Dh M	54h T	3Ah :	*1 *2	03h
-----------------------	-----	----------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	△	x	x

■Note:

- "IN STANDBY MODE" is "ON" only when, STANDBY when available.

2.109. WIRELESS LAN - OFF

Hexadecimal Character	02h O	4Fh R	52h C	43h :	3Ah *1 *2	03h
--------------------------	----------	----------	----------	----------	-----------------	-----

■ Parameters (*1,*2)

Hexadecimal Character	OFF 31h 1
--------------------------	-----------------

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh R	52h C	43h :	3Ah *1 *2	03h
--------------------------	----------	----------	----------	----------	-----------------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	o	x

2.110. EXT OPTION

Hexadecimal Character	02h O	4Fh H	48h M	4Dh :	03h
--------------------------	----------	----------	----------	----------	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h O	4Fh H	48h M	4Dh :	03h
--------------------------	----------	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
o	x	o	x

2.111. Query POWER

Hexadecimal	02h	51h	50h	57h	03h
Character	Q	P	W		

■Response (Callback)

OFF

Hexadecimal	02h	30h	30h	31h	03h
Character	0	0	0	1	

ON

Hexadecimal	02h	30h	30h	31h	03h
Character	0	0	0	1	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE	
○	○	○	○	

2.112. Query INPUT SELECT

Hexadecimal	02h	51h	49h	4Eh	03h
Character	Q	I	N		

■Response (Callback)

COMPUTER

Hexadecimal	02h	52h	47h	31h	03h
Character	R	G	1		

DVI-I

Hexadecimal	02h	52h	47h	32h	03h
Character	R	G	2		

VIDEO

Hexadecimal	02h	56h	49h	44h	03h
Character	V	I	D		

S-VIDEO

Hexadecimal	02h	53h	56h	44h	03h
Character	S	V	D		

DVI

Hexadecimal	02h	44h	56h	49h	03h
Character	D	~V	I		

NETWORK

Hexadecimal	02h	4Eh	57h	50h	03h
Character	N	W	P		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE	
○	x	○	○	

■Note:

- DVI SELECT COMMAND is effective for RG2 in the case of COMPUTER2.

2.113. Query FREEZE

Hexadecimal	02h	51h	46h	5Ah	03h
Character	Q	F	Z		

■Response (Callback)

OFF

Hexadecimal	02h	30h	03h
Character	0		

ON

Hexadecimal	02h	31h	03h
Character	1		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE	
○	x	x	○	

2.114. Query AUTO SETUP

Hexadecimal	02h	51h	41h	53h	03h
Character		Q	A	S	
■ Response (Callback)					
OFF					
Hexadecimal	02h	30h	03h		
Character		0			
ON					
Hexadecimal	02h	31h	03h		
Character		1			
Acceptability					
SECURITY	STANDBY	NO SIGNAL	AV MUTE		
○	○	○	○		

2.115. Query AV MUTE

Hexadecimal	02h	51h	53h	48h	03h
Character		Q	S	H	
■ Response (Callback)					
OFF					
Hexadecimal	02h	31h	03h		
Character		0			
ON					
Hexadecimal	02h	31h	03h		
Character		1			
Acceptability					
SECURITY	STANDBY	NO SIGNAL	AV MUTE		
○	✗	○	○		

2.116. Query INDEX-WINDOW

Hexadecimal	02h	51h	49h	58h	03h
Character		Q	I	X	
■ Response (Callback)					
OFF					
Hexadecimal	02h	30h	03h		
Character		0			
50%					
Hexadecimal	02h	31h	03h		
Character		1			
75%					
Hexadecimal	02h	32h	03h		
Character		2			
100%					
Hexadecimal	02h	33h	03h		
Character		3			
Acceptability					
SECURITY	STANDBY	NO SIGNAL	AV MUTE		
○	✗	✗	✗		

2.117. Query PICTURE MODE

Hexadecimal	02h	51h	50h	4Dh	03h
Character		Q	P	M	
■ Response (Callback)					
In the period when the command can be accepted					
Hexadecimal	02h	*1	*3	*5	03h
Character		*2	*4	*6	
Acceptability					
SECURITY	STANDBY	NO SIGNAL	AV MUTE		
○	✗	✗	○		

■ Parameters (*1,*2,*3,*4,*5,*6)

	DYNAMIC			NATURAL			STANDARD			BLACK BOARD		
Hexadecimal	44h	59h	4Eh	4Eh	41h	54h	53h	54h	44h	42h	42h	44h
Character	D	Y	N	N	A	T	S	T	D	B	B	D
	CINEMA			WHITE BOARD								
Hexadecimal	43h	49h	4Eh	57h	42h	44h						
Character	C	I	N	W	B	D						

■ Note:

- When input the Moving image, "NATURAL" is not returned.
- When input the Still image, "CINEMA" is not returned.

2.118. Query CONTRAST

Hexadecimal Character	02h	51h	56h	52h	03h
	Q	V	R		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1 *2	*3 *4	*5 *6	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	-32			-31			-30		
Hexadecimal Character	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal Character	30h	33h	30h	30h	33h	31h	30h	33h	32h
	0	3	0	0	3	1	0	3	2

2.119. Query BRIGHTNESS

Hexadecimal Character	02h	51h	56h	42h	03h
	Q	V	R	B	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1 *2	*3 *4	*5 *6	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	-32			-31			-30		
Hexadecimal Character	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal Character	30h	33h	30h	30h	33h	31h	30h	33h	32h
	0	3	0	0	3	1	0	3	2

2.120. Query COLOR

Hexadecimal Character	02h	51h	56h	43h	03h
	Q	V	R	C	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1 *2	*3 *4	*5 *6	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	-32			-31			-30		
Hexadecimal Character	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal Character	30h	33h	30h	30h	33h	31h	30h	33h	32h
	0	3	0	0	3	1	0	3	2

■ Note:

- This command is acceptable only when moving image is displayed. In other cases, ER401 is returned.

2.121. Query TINT

Hexadecimal Character	02h	51h	56h	54h	03h
	Q	V	T		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1	*3	*5	03h
		*2	*4	*6	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	-32			-31			-30		
Hexadecimal Character	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
	-	3	2	-	3	1	-	3	0
Hexadecimal Character	30h	33h	30h	30h	33h	31h	30h	33h	32h
	0	3	0	0	3	1	0	3	2

■ Note:

- This command is acceptable only when moving image is displayed. In other cases, ER401 is returned.

2.122. Query SHARPNESS

Hexadecimal Character	02h	51h	56h	53h	03h
	Q	V	T	S	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1	*3	*5	03h
		*2	*4	*6	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	-06			-05			-04		
Hexadecimal Character	2Dh	30h	36h	2Dh	30h	35h	2Dh	30h	34h
	-	0	6	-	0	5	-	0	4
Hexadecimal Character	30h	31h	33h	30h	31h	34h	30h	31h	35h
	0	1	3	0	1	4	0	1	5

2.123. Query COLOR TEMPERATURE

Hexadecimal Character	02h	51h	54h	45h	03h
	Q	V	T	E	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1	03h
		*2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2)

	LOW	DEFAULT	HIGH
Hexadecimal Character	30h	31h	32h
	0	1	2

2.124. Query DAYLIGHT VIEW

Hexadecimal Character	02h	51h	56h	58h	3Ah	44h	4Ch	56h	49h	30h	03h
	Q	V	X	:	D	L	V	I	O		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	44h	4Ch	56h	49h	30h	3Dh	2Dh
	D	L	V	I	O	=		+
Hexadecimal Character	*1	*3	*5	*7	*9	03h		
	*2	*4	*6	*8	*10			

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

FRONT INSTALLATION

OFF				
Hexadecimal Character	30h	30h	30h	30h
	0	0	0	0
AUTO				
Hexadecimal Character	30h	30h	30h	30h
	0	0	0	0
ON				
Hexadecimal Character	30h	30h	30h	30h
	0	0	0	0
				32h
				2

REAR INSTALLATION

OFF				
Hexadecimal Character	30h	30h	30h	30h
	0	0	0	0
ON				
Hexadecimal Character	30h	30h	30h	30h
	0	0	0	0
				31h
				1

2.125. Query DIGITAL CINEMA REALITY

Hexadecimal Character	02h	51h	50h	44h	03h
	Q	P	D		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1	03h
		*2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2)

	OFF	ON
Hexadecimal Character	30h	31h
	0	1

■ Note:

- This command is available only when an interlaced signal is inputted. In other cases, ER401 is returned.

2.126. Query NOISE REDUCTION

Hexadecimal Character	02h	51h	4Eh	52h	03h
	Q	N	R		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1	03h
		*2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2)

	OFF	ON
Hexadecimal Character	30h	31h
	0	1

■ Note:

- This command is acceptable only when the input is VIDEO or S-VIDEO. In other cases, ER401 is returned.

2.127. Query TV SYSTEM

Hexadecimal	02h	51h	53h	47h	03h
Character	Q	S	G		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	*3	*5	03h
Character		*2	*4	*6	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	○	○

■ Parameters (*1,*2,*3,*4,*5,*6)

Hexadecimal	AUTO			NTSC			NTSC4.43			PAL		
	41h	55h	54h	4Eh	54h	53h	4Eh	34h	34h	50h	41h	4Ch
Character	A	U	T	N	T	S	N	4	4	P	A	L
Hexadecimal	PAL-M			PAL-N			SECAM					
	50h	41h	4Dh	50h	41h	4Eh	53h	45h	43h			
Character	P	A	M	P	A	N	S	E	C			

■ Note:

- This command is acceptable only when the input is VIDEO or S-VIDEO. In other cases, ER401 is returned.

2.128. Query RGB/YpbPr

Hexadecimal	02h	51h	52h	46h	03h
Character	Q	R	F		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	03h
Character		*2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2)

Hexadecimal	RGB	YpbPr	AUTO
Character	30h	31h	32h
	0	1	2

2.129. Query CONTRAST - RED

Hexadecimal	02h	51h	43h	31h	03h
Character	Q	C	1		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	*3	*5	03h
Character		*2	*4	*6	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6)

Hexadecimal	-32			-31			-30		
	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
Character	—	3	2	—	3	1	—	3	0
	30			31			32		
Hexadecimal	30h	33h	30h	30h	33h	31h	30h	33h	32h
Character	0	3	0	0	3	1	0	3	2

2.130. Query CONTRAST - GREEN

Hexadecimal	02h	51h	43h	32h	03h
Character	Q	C	2		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	*3	*5	03h
Character		*2	*4	*6	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	-32			-31			-30		
Hexadecimal	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
Character	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal	30h	33h	30h	30h	33h	31h	30h	33h	32h
Character	0	3	0	0	3	1	0	3	2

2.131. Query CONTRAST - BLUE

Hexadecimal	02h	51h	43h	33h	03h
Character	Q	C	3		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	*3	*5	03h
Character		*2	*4	*6	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	-32			-31			-30		
Hexadecimal	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
Character	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal	30h	33h	30h	30h	33h	31h	30h	33h	32h
Character	0	3	0	0	3	1	0	3	2

2.132. Query BRIGHTNESS - RED

Hexadecimal	02h	51h	42h	31h	03h
Character	Q	C	B	1	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	*3	*5	03h
Character		*2	*4	*6	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	-32			-31			-30		
Hexadecimal	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
Character	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal	30h	33h	30h	30h	33h	31h	30h	33h	32h
Character	0	3	0	0	3	1	0	3	2

2.133. Query BRIGHTNESS - GREEN

Hexadecimal	02h	51h	42h	32h	03h
Character	Q	B	2		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	*3	*5	03h
Character		*2	*4	*6	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	-32			-31			-30		
Hexadecimal	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
Character	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal	30h	33h	30h	30h	33h	31h	30h	33h	32h
Character	0	3	0	0	3	1	0	3	2

2.134. Query BRIGHTNESS - BLUE

Hexadecimal	02h	51h	42h	33h	03h
Character	Q	B	2		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	*3	*5	03h
Character		*2	*4	*6	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	-32			-31			-30		
Hexadecimal	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
Character	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal	30h	33h	30h	30h	33h	31h	30h	33h	32h
Character	0	3	0	0	3	1	0	3	2

2.135. Query KEYSTONE

Hexadecimal	02h	51h	4Bh	53h	03h
Character	Q	K	S		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	*3	*5	03h
Character		*2	*4	*6	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	-32			-31			-30		
Hexadecimal	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
Character	-	3	2	-	3	1	-	3	0
	30			31			32		
Hexadecimal	30h	33h	30h	30h	33h	31h	30h	33h	32h
Character	0	3	0	0	3	1	0	3	2

2.136. Query SHIFT H

Hexadecimal Character	02h	51h	48h	50h	03h
	Q	H	P		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1 *2	*3 *4	*5 *6	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	-127				-126				-125			
Hexadecimal Character	2Dh	31h	32h	37h	2Dh	31h	32h	36h	2Dh	31h	32h	35h
	-	1	2	7	-	1	2	6	-	1	2	5
	125				126				127			
Hexadecimal Character	31h	32h	35h	31h	32h	36h	31h	32h	37h	1	2	7
	1	2	5	1	2	6	1	2	7			

■ Note:

- This command is not acceptable when the input is NETWORK. In this case, ER401 is returned.

2.137. Query SHIFT V

Hexadecimal Character	02h	51h	56h	50h	03h
	Q	V	P		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1 *2	*3 *4	*5 *6	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	-64			-63			-62		
Hexadecimal Character	2Dh	36h	34h	2Dh	36h	33h	2Dh	36h	32h
	-	6	4	-	6	3	-	6	2
	62			63			64		
Hexadecimal Character	36h	32h	36h	33h	36h	34h	6	1	4
	6	2	6	3	6				

■ Note:

- This command is acceptable except when the input is NETWORK. Or, this command is acceptable when the input is NETWORK and ASPECT is H-FIT (for FW430 only). In other cases, ER401 is returned.

2.138. Query OVER SCAN

Hexadecimal Character	02h	51h	4Fh	56h	03h
	Q	O		V	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1 *2	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2)

	0%	3%	5%	7%
Hexadecimal Character	30h	31h	32h	33h
	0	1	2	3

2.139. Query DOT CLOCK

Hexadecimal Character	02h	51h	44h	43h	03h
-----------------------	-----	-----	-----	-----	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6)

Hexadecimal Character	-32			-31			-30		
	2Dh	33h	32h	2Dh	33h	31h	2Dh	33h	30h
Hexadecimal Character	—	3	2	—	3	1	—	3	0
	30			31			32		
Hexadecimal Character	30h	33h	30h	30h	33h	31h	30h	33h	32h
	0	3	0	0	3	1	0	3	2

■ Note:

- Only when the input is COMPUTER IN, and still image is displayed, this command is acceptable. In other cases, ER401 is returned.

2.140. Query CLOCK PHASE

Hexadecimal Character	02h	51h	43h	50h	03h
-----------------------	-----	-----	-----	-----	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1 *2	*3 *4	*5 *6	03h
-----------------------	-----	----------	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6)

Hexadecimal Character	-16			-15			-14		
	2Dh	31h	36h	2Dh	31h	36h	2Dh	31h	36h
Hexadecimal Character	—	1	6	—	1	6	—	1	4
	14			15			16		
Hexadecimal Character	30h	31h	34h	30h	31h	35h	30h	31h	36h
	0	1	4	0	1	5	0	1	6

■ Note:

- This command is acceptable only when the input is COMPUTER IN. In other cases, ER401 is returned.

2.141. Query ASPECT

Hexadecimal Character	02h	51h	53h	31h	03h
-----------------------	-----	-----	-----	-----	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1 *2	*3 *4	03h
-----------------------	-----	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4)

FX400

Hexadecimal Character	AUTO		NORMAL		WIDE		S4:3		NATIVE	
	30h	30h	30h	31h	30h	32h	30h	33h	30h	35h
	FULL		H-FIT		V-FIT					
Character	0	6	0	9	1	0				

FW430

Hexadecimal Character	AUTO		S4:3		NORMAL		NATIVE		FULL	
	30h	30h	30h	31h	30h	32h	30h	35h	30h	36h
	H-FIT		V-FIT							
Character	0	9	1	0						

2.142. Query FRAME LOCK

Hexadecimal	02h	51h	46h	4Ch	03h
Character	Q	F	L		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	03h
Character		*2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2)

	OFF	ON
Hexadecimal	30h	31h
Character	0	1

2.143. Query LANGUAGE

Hexadecimal	02h	51h	4Ch	47h	03h
Character	Q	L	G		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	*3	*5	03h
Character		*2	*4	*6	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	English			German			French		
Hexadecimal	45h	4Eh	47h	44h	45h	55h	46h	52h	41h
Character	E	N	G	D	E	Ü	F	R	A
	Spanish			Italian			Japanese		
Hexadecimal	45h	53h	50h	49h	54h	4Ch	4Ah	50h	4Eh
Character	E	S	P	I	T	L	J	P	N
	Chinese			Russian			Korean		
Hexadecimal	43h	48h	49h	52h	55h	53h	4Bh	4Fh	52h
Character	C	H	I	R	U	S	K	O	R
	Portuguese			Swedish			Norwegian		
Hexadecimal	50h	4Fh	52h	53h	56h	45h	4Eh	4Fh	52h
Character	P	O	R	S	V	E	N	O	R
	Danish			Polish			Czech		
Hexadecimal	44h	41h	4Eh	50h	4Fh	4Ch	43h	45h	53h
Character	D	A	N	P	O	L	C	E	S
	Hungarian			Thai					
Hexadecimal	4Dh	41h	47h	54h	48h	41h			
Character	M	A	G	T	H	A			

2.144. Query INPUT GUIDE

Hexadecimal	02h	51h	44h	49h	03h
Character	Q	D	I		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	03h
Character		*2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2)

	OFF	SIMPLE	DETAILED
Hexadecimal	30h	31h	32h
Character	0	1	2

2.145. Query OSD DESIGN

Hexadecimal Character	02h Q	51h O	4Fh D	44h .	03h ..
■ Response (Callback)					
In the period when the command can be accepted					
Hexadecimal Character	02h *1 *2	*1 *2	03h		
Acceptability					
SECURITY	STANDBY	NO SIGNAL	AV MUTE		
○	○	○	○		
■ Parameters (*1,*2)					
	TYPE1	TYPE2	TYPE3		
Hexadecimal Character	30h 0	31h 1	32h 2		

2.146. Query WARNING MESSAGE

Hexadecimal Character	02h Q	51h V	56h X	58h :	3Ah W	57h M	4Dh D	44h I	49h 0	30h 03h
■ Response (Callback)										
In the period when the command can be accepted										
Hexadecimal Character	02h *1 *2	57h *3 *4	4Dh *5 *6	44h *7 *8	49h *9 *10	30h 0	3Dh =	2Dh +		
Acceptability										
SECURITY	STANDBY	NO SIGNAL	AV MUTE							
○	○	○	○							
■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)										
	OFF									
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	30h 0					
	ON									
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	31h 1					

2.147. Query DVI-I DIGITAL/ANALOG

Hexadecimal Character	02h Q	51h V	56h X	58h :	3Ah D	44h D	44h A	41h I	49h 0	30h 03h
■ Response (Callback)										
In the period when the command can be accepted										
Hexadecimal Character	02h *1 *2	44h *3 *4	44h *5 *6	41h *7 *8	49h *9 *10	30h 0	3Dh =	2Dh +		
Acceptability										
SECURITY	STANDBY	NO SIGNAL	AV MUTE							
○	○	○	○							
■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)										
	DIGITAL									
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	30h 0					
	ANALOG									
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	31h 1					

2.148. Query EDID Setting

Hexadecimal Character	02h Q	51h E	45h D	44h D	03h .
--------------------------	----------	----------	----------	----------	----------

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h .	*1 *2	03h .
--------------------------	----------	----------	----------

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2)

	EDID1 (Moving image)	EDID2(PC)
Hexadecimal Character	31h 1	32h 2

2.149. Query DVI SIGNAL LEVEL

Hexadecimal Character	02h Q	51h V	56h X	58h :	3Ah D	44h D	56h V	49h I	49h I	30h 0	03h .
--------------------------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h D	44h V	56h I	49h I	49h I	30h 0	3Dh =	2Dh +
Hexadecimal Character	*1 *2	*3 *4	*5 *6	*7 *8	*9 *10	03h .		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

	0-255(PC)				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	30h 0
16-235					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	31h 1

2.150. Query HDMI SIGNAL LEVEL

Hexadecimal Character	02h Q	51h V	56h X	58h :	3Ah H	48h S	53h L	4Ch I	49h I	30h 0	03h .
--------------------------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h H	48h S	53h L	4Ch I	49h I	30h 0	3Dh =	2Dh +
Hexadecimal Character	*1 *2	*3 *4	*5 *6	*7 *8	*9 *10	03h .		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

	0-1023				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	30h 0
64-940					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	31h 1

2.151. Query CLOSED CAPTION SETTING

Hexadecimal Character	02h Q	51h C	43h C	43h C	03h
--------------------------	----------	----------	----------	----------	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h *1 *2	*1 *2	03h
--------------------------	-----------------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2)

	OFF	CC1	CC2	CC3	CC4
Hexadecimal Character	30h 0	31h 1	32h 2	33h 3	34h 4

■ Note:

- Input signal is 480i (YPbPr) or NTSC, this command is available.

2.152. Query SCREEN FORMAT

Hexadecimal Character	02h Q	51h S	53h F	46h F	03h
--------------------------	----------	----------	----------	----------	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h *1 *2	*1 *2	03h
--------------------------	-----------------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	○	○

■ Parameters (*1,*2)

	16:10	16:9
Hexadecimal Character	30h 0	31h 1

■ Note:

- This command is available only for FW430.

2.153. Query SCREEN POSITION

Hexadecimal Character	02h Q	51h V	56h X	58h :	3Ah V	59h S	53h P	50h I	49h 1	31h 03h
--------------------------	----------	----------	----------	----------	----------	----------	----------	----------	----------	------------

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h V	59h S	53h P	50h I	49h 1	31h =	3Dh 03h	2Dh +
Hexadecimal Character	*1 *2	*3 *4	*5 *6	*7 *8	*9 *10			

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

	LOW				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	30h 0
CENTER					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	31h 1
HIGH					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	32h 2

■ Note:

- This command is available only for FW430.

2.154. Query STARTUP LOGO

Hexadecimal Character	02h Q	51h L	4Ch O	4Fh O	03h
■ Response (Callback)					
In the period when the command can be accepted					
Hexadecimal Character	02h *1 *2	51h *2	03h		
Acceptability					
SECURITY	STANDBY	NO SIGNAL	AV MUTE		
○	○	○	○		
■ Parameters (*1,*2)					
	OFF	DEFAULT	TEXT	USER	
Hexadecimal Character	30h 0	31h 1	32h 2	32h 2	

2.155. Query STARTUP LOGO

Hexadecimal Character	02h Q	51h S	53h S	53h S	03h
■ Response (Callback)					
In the period when the command can be accepted					
Hexadecimal Character	02h *1 *2	51h *2	03h		
Acceptability					
SECURITY	STANDBY	NO SIGNAL	AV MUTE		
○	x	○	○		
■ Parameters (*1,*2)					
	BUTTON	AUTO			
Hexadecimal Character	30h 0	31h 1			

2.156. Query SIGNAL SEARCH

Hexadecimal Character	02h Q	51h S	53h R	52h R	03h
■ Response (Callback)					
In the period when the command can be accepted					
Hexadecimal Character	02h *1 *2	51h *2	03h		
Acceptability					
SECURITY	STANDBY	NO SIGNAL	AV MUTE		
○	x	○	○		
■ Parameters (*1,*2)					
	OFF	ON			
Hexadecimal Character	30h 0	31h 1			

2.157. Query BACK COLOR

Hexadecimal Character	02h Q	51h B	42h C	43h C	03h
■ Response (Callback)					
In the period when the command can be accepted					
Hexadecimal Character	02h *1 *2	51h *2	03h		
Acceptability					
SECURITY	STANDBY	NO SIGNAL	AV MUTE		
○	x	○	○		
■ Parameters (*1,*2)					
	BLUE	BLACK	DEFAULT	USER	
Hexadecimal Character	30h 0	31h 1	32h 2	33h 3	

2.158. Query WIDE MODE

Hexadecimal	02h	51h	58h	47h	03h
Character	Q	X	G		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	03h
Character		*2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2)

	OFF	ON	AUTO
Hexadecimal	30h	31h	32h
Character	0	1	2

2.159. Query SXGA MODE

Hexadecimal	02h	51h	53h	58h	03h
Character	Q	S	X		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	03h
Character		*2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	x	○

■ Parameters (*1,*2)

	SXGA	SXGA+
Hexadecimal	30h	31h
Character	0	1

2.160. Query INITIAL START UP

Hexadecimal	02h	51h	50h	59h	03h
Character	Q	S	P	Y	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	03h
Character		*2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2)

	STANDBY	ON	LAST MEMORY
Hexadecimal	30h	31h	32h
Character	0	1	2

2.161. Query INSTALLATION

Hexadecimal	02h	51h	53h	50h	03h
Character	Q	S	X	P	

■ Response (Callback)

Hexadecimal	02h	*1	03h
Character		*2	

■ Parameters (*1,*2)

	FRONT/DESK	REAR/DESK	FRONT / CEILING	REAR/CEILING
Hexadecimal	30h	31h	32h	33h
Character	0	1	2	3

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

2.162. Query HIGH ALTITUDE MODE

Hexadecimal	02h	51h	46h	4Dh	03h
Character	Q	F	M		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	03h
Character		*2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2)

	OFF	ON
Hexadecimal	30h	31h
Character	0	1

2.163. Query LAMP POWER

Hexadecimal	02h	51h	4Ch	50h	03h
Character	Q	L	P		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	03h
Character		*2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2)

	ECO	NORMAL
Hexadecimal	30h	31h
Character	0	1

2.164. Query SCHEDULE

Hexadecimal	02h	51h	56h	58h	3Ah	53h	43h	48h	49h	30h	03h
Character	Q	V	X		:	S	C	H	I	0	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	53h	43h	48h	49h	30h	3Dh	2Dh
Character	S	C	H	I	0	=	+	
Hexadecimal	*1	*3	*5	*7	*9	03h		
Character	*2	*4	*6	*8	*10			

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

	OFF				
Hexadecimal	30h	30h	30h	30h	30h
Character	0	0	0	0	0
	ON				
Hexadecimal	30h	30h	30h	30h	31h
Character	0	0	0	0	1

2.165. Query ECO MANAGEMENT

Hexadecimal Character	02h	51h	56h	58h	3Ah	45h	43h	4Fh	49h	30h	03h
	Q	V	X	:	E	C	O	I	O	0	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	45h	43h	4Fh	49h	30h	3Dh	2Dh
	E	C	O	I	O	=		+
Hexadecimal Character	*1	*3	*5	*7	*9	03h		
Hexadecimal Character	*2	*4	*6	*8	*10			

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

Hexadecimal Character	OFF				
Character	30h	30h	30h	30h	30h
Character	0	0	0	0	0

Hexadecimal Character	ON				
Character	30h	30h	30h	30h	31h

2.166. Query AMBIENT LIGHT DETECTION

Hexadecimal Character	02h	51h	56h	58h	3Ah	45h	43h	4Fh	49h	31h	03h
	Q	V	X	:	E	C	O	I	1	1	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	45h	43h	4Fh	49h	31h	3Dh	2Dh
	E	C	O	I	O	=		+
Hexadecimal Character	*1	*3	*5	*7	*9	03h		
Hexadecimal Character	*2	*4	*6	*8	*10			

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

Hexadecimal Character	OFF				
Character	30h	30h	30h	30h	30h
Character	0	0	0	0	0

Hexadecimal Character	ON				
Character	30h	30h	30h	30h	31h

2.167. Query SIGNAL DETECTION

Hexadecimal Character	02h	51h	56h	58h	3Ah	45h	43h	4Fh	49h	32h	03h
	Q	V	X	:	E	C	O	I	2	2	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	45h	43h	4Fh	49h	32h	3Dh	2Dh
	E	C	O	I	O	=		+
Hexadecimal Character	*1	*3	*5	*7	*9	03h		
Hexadecimal Character	*2	*4	*6	*8	*10			

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

Hexadecimal Character	OFF				
Character	30h	30h	30h	30h	30h
Character	0	0	0	0	0

Hexadecimal Character	ON				
Character	30h	30h	30h	30h	31h

2.168. Query AV MUTE DETECTION

Hexadecimal Character	02h	51h	56h	58h	3Ah	45h	43h	4Fh	49h	33h	03h
-----------------------	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	45h	43h	4Fh	49h	33h	3Dh	2Dh
Hexadecimal Character	*1	*3	*5	*7	*9	03h	=	+

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

Hexadecimal Character	OFF				
Hexadecimal Character	30h	30h	30h	30h	30h
ON					
Hexadecimal Character	30h	30h	30h	30h	31h
Character	0	0	0	0	1

2.169. Query NO SIGNAL SHUT-OFF

Hexadecimal Character	02h	51h	41h	46h	03h
-----------------------	-----	-----	-----	-----	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1 *2	*3 *4	03h
-----------------------	-----	----------	----------	-----

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4)

Setting of 15-60 minutes is possible by a unit for five minutes.

Hexadecimal Character	OFF		15	60
Character	30h	30h	31h	35h
Character	0	0	1	5
Character	36h	36h	36h	30h
Character	6	6	6	0

2.170. Query STANDBY MODE

Hexadecimal Character	02h	51h	56h	58h	3Ah	53h	54h	4Dh	49h	30h	03h
-----------------------	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	53h	54h	4Dh	49h	33h	3Dh	2Dh
Hexadecimal Character	*1 *2	*3 *4	*5 *6	*7 *8	*9 *10	03h	=	+

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

Hexadecimal Character	NORMAL				
Hexadecimal Character	30h	30h	30h	30h	30h
ECO					
Hexadecimal Character	30h	30h	30h	30h	33h
Character	0	0	0	0	3

2.171. Query EMULATE

Hexadecimal Character	02h	51h	56h	58h	3Ah	45h	4Dh	55h	49h	30h	03h
	Q	V	X	:	E	M	U	I	O		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	45h	4Dh	55h	49h	30h	3Dh	2Dh
	E	M	Ü	I	O	=		+
Hexadecimal Character	*1	*3	*5	*7	*9	03h		
Hexadecimal Character	*2	*4	*6	*8	*10			

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

DEFAULT				
Hexadecimal Character	30h	30h	30h	30h
	0	0	0	0
31h				
D3500				
Hexadecimal Character	30h	30h	30h	30h
	0	0	0	0
32h				
D4000				
Hexadecimal Character	30h	30h	30h	30h
	0	0	0	0
33h				
D/W5k Series				
Hexadecimal Character	30h	30h	30h	30h
	0	0	0	0
34h				
D/W/Z6k Series				
Hexadecimal Character	30h	30h	30h	30h
	0	0	0	0
35h				
L730				
Hexadecimal Character	30h	30h	30h	30h
	0	0	0	0
36h				
L780				
Hexadecimal Character	30h	30h	30h	30h
	0	0	0	0
37h				
L735				
Hexadecimal Character	30h	30h	30h	30h
	0	0	0	0
38h				
L785				
Hexadecimal Character	30h	30h	30h	30h
	0	0	0	0
39h				
LB/W Series				
Hexadecimal Character	30h	30h	30h	31h
	0	0	0	1
30h				

2.172. Query AUDIO SETTING - VOLUME

Hexadecimal Character	02h	51h	41h	56h	03h
	Q	A	V		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1	*3	*5	03h
		*2	*4	*6	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	△	○	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	0	1	2
Hexadecimal Character	30h	30h	30h
	0	0	0
	31h	31h	31h
	0	0	0
	32h	32h	32h
	0	0	0
	33h	33h	33h
	6	6	6
	1	1	1
	36h	36h	36h
	0	0	0
	32h	32h	32h
	6	6	6
	2	2	2
	30h	30h	30h
	0	0	0
	36h	36h	36h
	6	6	6
	33h	33h	33h
	3	3	3

■ Note:

- During STANDBY, this command is available only when "IN STANDBY MODE" is ON.

2.173. Query AUDIO SETTING - BALANCE

Hexadecimal Character	02h	51h	42h	4Ch	03h
	Q	B	L		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1 *2	*3 *4	*5 *6	03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	△	○	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	-16			-15			-14		
Hexadecimal Character	2Dh	31h	36h	2Dh	31h	35h	2Dh	31h	34h
	-	1	6	-	1	5	-	1	4
	14			15			16		
Hexadecimal Character	30h	36h	31h	30h	31h	35h	30h	31h	36h
	0	1	4	0	1	5	0	1	6

■ Note:

- During STANDBY, this command is available only when "IN STANDBY MODE" is ON.

2.174. Query AUDIO SETTING - IN STANDBY MODE

Hexadecimal Character	02h	51h	56h	58h	3Ah	41h	53h	42h	49h	30h	03h
	Q	V	X	:	A	S	B	I	0		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	41h	53h	42h	49h	30h	3Dh	2Dh
		A	S	B	I	0	=	+
Hexadecimal Character	*1	*3	*5	*7	*9	03h		
	*2	*4	*6	*8	*10			

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

	OFF				
Hexadecimal Character	30h	30h	30h	30h	30h
	0	0	0	0	0
	ON				
Hexadecimal Character	30h	30h	30h	30h	31h
	0	0	0	0	1

2.175. Query AUDIO SETTING - POWER BUTTON BEEP

Hexadecimal Character	02h	51h	56h	58h	3Ah	42h	45h	50h	49h	30h	03h
	Q	V	X	:	A	B	E	P	I	0	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	42h	45h	50h	49h	30h	3Dh	2Dh
		B	E	P	I	0	=	+
Hexadecimal Character	*1	*3	*5	*7	*9	03h		
	*2	*4	*6	*8	*10			

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

	OFF				
Hexadecimal Character	30h	30h	30h	30h	30h
	0	0	0	0	0
	ON				
Hexadecimal Character	30h	30h	30h	30h	31h
	0	0	0	0	1

2.176. Query AUDIO SETTING – AUDIO IN SELECT

Hexadecimal Character	02h	51h	56h	58h	3Ah	41h	53h	42h	49h	*1 *2	30h	03h
-----------------------	-----	-----	-----	-----	-----	-----	-----	-----	-----	----------	-----	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	41h	53h	42h	49h	*1 *2	3Dh	2Dh
Hexadecimal Character	*3 *4	*5 *6	*7 *8	*9 *10	*11 *12		03h	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2)

	COMPUTER IN		DVI-I IN		HDMI IN
Hexadecimal Character	30h 0		32h 2		33h 3
	VIDEO IN		S-VIDEO IN		NETWORK IN
Hexadecimal Character	34h 4		35h 5		36h 6

■ Parameters (*3,*4,*5,*6,*7,*8,*9,*10,*11,*12)

	AUDIO IN 1				
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	30h 0
AUDIO IN 2					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	31h 1
AUDIO IN 3					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	32h 2
HDMI AUDIO IN					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	33h 3
NETWORK AUDIO IN					
Hexadecimal Character	30h 0	30h 0	30h 0	30h 0	34h 4

2.177. Query SCHEDULE (PROGRAM SET)

Hexadecimal Character	02h	51h	56h	58h	3Ah	41h	53h	42h	49h	*1	03h
	Q	V	X	:	S	P	G	I		*2	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	41h	53h	42h	49h	*1	3Dh	2Dh
	S	P	G	I		*2	=	+
Hexadecimal Character	*1	*3	*5	*7	*9	03h		
	*2	*4	*6	*8	*10			

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2)

	SUN	MON	TUE	WED	THU	FRI	SAT
Hexadecimal Character	30h	31h	32h	33h	34h	35h	36h
	0	1	2	3	4	5	6

■ Parameters (*3,*4,*5,*6,*7,*8,*9,*10,*11,*12)

	OFF (Disable set)				
Hexadecimal Character	30h	30h	30h	30h	30h
	0	0	0	0	0
	PROGRAM1				
Hexadecimal Character	30h	30h	30h	30h	31h
	0	0	0	0	1
	PROGRAM2				
Hexadecimal Character	30h	30h	30h	30h	32h
	0	0	0	0	2
	PROGRAM3				
Hexadecimal Character	30h	30h	30h	30h	33h
	0	0	0	0	3
	PROGRAM4				
Hexadecimal Character	30h	30h	30h	30h	34h
	0	0	0	0	4
	PROGRAM5				
Hexadecimal Character	30h	30h	30h	30h	35h
	0	0	0	0	5
	PROGRAM6				
Hexadecimal Character	30h	30h	30h	30h	36h
	0	0	0	0	6
	PROGRAM7				
Hexadecimal Character	30h	30h	30h	30h	37h
	0	0	0	0	7

2.178. Query SCHEDULE (PROGRAM EDIT)

Hexadecimal Character	02h Character	51h Q	56h V	58h X	3Ah :	53h S	43h C	43h C	53h S	*1 *2
Hexadecimal Character	02h Character	*3 =	*5 *4	03h *6						

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h Character	53h S	43h C	43h C	53h S	*1 *2	3Dh =	*3 *4	*5 *6
Hexadecimal Character	*7 *8	*9 *10	*11 *12	*13 *14	*15 *16	*17 *18	03h 03h		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2)

program from No.						
Hexadecimal Character	31h 1	32h 2	33h 3	34h 4	35h 5	36h 6
Hexadecimal Character	37h 7					

■ Parameters (*3,*4,*5,*6)

COMMAND No. (decimal number) 01~16					
Hexadecimal Character	30h 0	31h 1	...	31h 1	36h 6

■ Parameters (*7,*8,*9,*10)

COMMAND 00~FF					
Hexadecimal Character	30h 0	30h 0	...	46h F	46h F

□ Refer to "3.1 SCHEDULE CONTROL COMMAND LIST" of the APPENDIX TABLE.

■ Parameters (*11,*12,*13,*14)

Hour 00~23					
Hexadecimal Character	30h 0	30h 0	...	32h 2	33h 3

■ Parameters (*15,*16,*17,*18)

Minute 00~59					
Hexadecimal Character	30h 0	30h 0	...	35h 5	39h 9

2.179. Query DATE AND TIME

Hexadecimal Character	02h Character	51h Q	43h C	54h T	03h
-----------------------	------------------	----------	----------	----------	---------

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h Character	*Y1 *h1	*Y2 *h2	*Y3 *m1	*Y4 *m2	*M1 *s1	*M2 *s2	*D1 *t1	*D2 *t2
Hexadecimal Character									03h 03h

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters

*Y1~*Y4 : Year (4 digits)

*M1~*M2 : Month (2 digits)

*D1~*D2 : Day (2 digits)

*h1~*h2 : Hour (2 digits)

*m1~*m2 : Minute (2 digits)

*s1~*s2 : Second (2 digits)

*t1~*t2 : Time zone (2 digits)

Example : In the case of April 1, 2008 12:00:00 (+00:00)

		*Y1 32 h	*Y2 30h	*Y3 30h	*Y4 38h	*M1 30h	*M2 34h	*D1 30ah	*D2 31h
Hexadecimal Character	02h Character	2	0	0	8	0	4	0	1
	*h1	*h2	*m1	*m2	*s1	*s2	*t1	*t2	
Hexadecimal Character	31h Character	1	2	0	0	0	0	d	03h 03h

2.180. Query DATE

Hexadecimal	02h	51h	47h	44h	03h
Character	Q	G	D		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*y1	*y2	*y3	*y4	*m1	*m2	*d1	*d2	*w	03h
Character											

■ Parameters (*1,*2,*3,*4,*5,*6)

*y1~*y4 : Year (4 digits)

*m1~*m2 : Month (2 digits)

*d1~*d2 : Day (2 digits)

*w : Day of the week (Mon = 1, Tue = 2, Wed = 3, Thu = 4, Fri = 5, Sat = 6, Sun = 7)

Set it by UTC (Coordinated Universal Time).

Example : Tuesday, April 1, 2008

Hexadecimal	*y1	*y2	*y3	*y4	*m1	*m2	*d1	*d2	*w
Character	32h	30h	30h	38h	30h	34h	30h	31h	31h
Character	2	0	0	8	0	4	0	1	2

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

2.181. Query TIME

Hexadecimal	02h	51h	47h	54h	03h
Character	Q	G	T		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*h1	*h2	*m1	*m2	*s1	*s2	03h
Character								

■ Parameters

*h1~*h2 : Hour (2 digits)

*m1~*m2 : Minute (2 digits)

*s1~*s2 : Second (2 digits)

Set it by UTC (Coordinated Universal Time).

Example: 3 seconds at 3:45 p.m.

Hexadecimal	*h1	*h2	*m1	*m2	*s1	*s2
Character	31h	35h	34h	35h	30h	33h
Character	1	5	4	5	0	3

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

2.182. Query NTP SYNCHRONIZATION

Hexadecimal	02h	51h	56h	58h	3Ah	4Eh	54h	50h	49h	30h	03h
Character	Q	V	X		:	N	T	P	I	0	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	4Eh	54h	50h	49h	30h	3Dh	2Dh
Character		N	T	P	I	0	=	+
Hexadecimal	*1	*3	*5	*7	*9	03h		
Character	*2	*4	*6	*8	*10			

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

OFF				
Hexadecimal	30h	30h	30h	30h
Character	0	0	0	0
ON				
Hexadecimal	30h	30h	30h	31h
Character	0	0	0	1

2.183. Query VGA60 / 480p

Hexadecimal	02h	51h	56h	35h	03h
Character	Q	V	V	5	
■ Response (Callback)					
In the period when the command can be accepted					
Hexadecimal	02h	*1	03h		
Character		*2			
Acceptability					
SECURITY	STANDBY	NO SIGNAL	AV MUTE		
○	x	x	○		
■ Parameters (*1,*2)					
	VGA60	480p	AUTO		
Hexadecimal	30h	31h	32h		
Character	0	1	2		

2.184. Query DVI SELECT

Hexadecimal	02h	51h	56h	58h	3Ah	44h	53h	43h	49h	30h	03h
Character	Q	V	V	X	:	D	S	C	I	0	
■ Response (Callback)											
In the period when the command can be accepted											
Hexadecimal	02h	44h	5.h	43h	49h	30h	3Dh	2Dh			
Character		D	S	C	I	0	=	+			
Hexadecimal	*1	*3	*5	*7	*9	03h					
Character	*2	*4	*6	*8	*10						
Acceptability											
SECURITY	STANDBY	NO SIGNAL	AV MUTE								
○	○	○	○								
■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)											
	DVI										
Hexadecimal	30h	30h	30h	30h	30h						
Character	0	0	0	0	0						
	COMPUTER2										
Hexadecimal	30h	30h	30h	30h	31h						
Character	0	0	0	0	1						

2.185. Query SIDE BY SIDE

Hexadecimal	02h	51h	50h	50h	03h
Character	Q	P	P	P	
■ Response (Callback)					
In the period when the command can be accepted					
Hexadecimal	02h	*1	03h		
Character		*2			
Acceptability					
SECURITY	STANDBY	NO SIGNAL	AV MUTE		
○	○	○	○		
■ Parameters (*1,*2)					
	OFF	ON			
Hexadecimal	30h	31h			
Character	0	1			

■ Note:

- This command is available only for FW430.

2.186. Query SIDE BY SIDE – SUB INPUT

Hexadecimal	02h	51h	49h	53h	03h
Character	Q	I	S		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	*3	*5	03h
Character		*2	*4	*6	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	x	△	△

■ Parameters (*1,*2,*3,*4,*5,*6)

	COMPUTER1			DVI-I		
Hexadecimal	52h	47h	31h	52h	47h	32h
Character	R	G	1	R	G	2
	VIDEO			S-VIDEO		
Hexadecimal	56h	49h	44h	53h	56h	44h
Character	V	I	D	S	V	D
	DVI-I			HDMI		
Hexadecimal	44h	56h	49h	48h	44h	31h
Character	D	V	I	H	D	1
	NETWORK					
Hexadecimal	4Eh	57h	50h			
Character	N	W	P			

■ Note:

- This command is available only for FW430.
- △ : Acceptable only at the time of "SIDE BY SIDE" mode.

2.187. Query FUNCTION BUTTON 1

Hexadecimal	02h	51h	46h	43h	03h
Character	Q	F	C		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	*3	*5	03h
Character		*2	*4	*6	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6)

	Parameters							
Hexadecimal	Refer to "3.2 FNC COMMAND PARAMETERS" of the APPENDIX TABLE.							
Character								

2.188. Query FUNCTION BUTTON 1 - 2

Hexadecimal	02h	51h	56h	58h	3Ah	46h	4Eh	43h	49h	30h	03h
Character	Q	V	X	X	:	F	N	C	I	0	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	46h	4Eh	43h	49h	30h	3Dh	2Dh
Character	F	N	C	I	0		=	+
Hexadecimal	*1	*3	*5	*7	*9	03h		
Character	*2	*4	*6	*8	*10			

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

	Parameters									
Hexadecimal	Refer to "3.2 FNC COMMAND PARAMETERS" of the APPENDIX TABLE.									
Character										

2.189. Query FUNCTION BUTTON 2

Hexadecimal Character	02h	51h	56h	58h	3Ah	46h	4Eh	43h	49h	31h	03h
-----------------------	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	46h	4Eh	43h	49h	31h	3Dh	2Dh
Hexadecimal Character	*1	*3	*5	*7	*9	03h		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

	Parameters
Hexadecimal Character	Refer to "3.2 FNC COMMAND PARAMETERS" of the APPENDIX TABLE.

2.190. Query FUNCTION BUTTON 3

Hexadecimal Character	02h	51h	56h	58h	3Ah	46h	4Eh	43h	49h	32h	03h
-----------------------	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	46h	4Eh	43h	49h	32h	3Dh	2Dh
Hexadecimal Character	*1	*3	*5	*7	*9	03h		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

	Parameters
Hexadecimal Character	Refer to "3.2 FNC COMMAND PARAMETERS" of the APPENDIX TABLE.

2.191. Query RUNTIME - LAMP

Hexadecimal Character	02h	51h	24h	4Ch	03h
-----------------------	-----	-----	-----	-----	-----

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal Character	02h	*1	*3	*5	*7	03h
Character	*2	*4	*6	*8	*10	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6)

Hexadecimal Character	0 h				1 h			
	30h	30h	30h	30h	30h	30h	30h	31h
Character	0	0	0	0	0	0	0	1
	9998 h							
Hexadecimal Character	39h	39h	39h	38h	39h	39h	39h	39h
Character	9	9	9	8	9	9	9	9

■ Note:

- If the lamp runtime cannot be accessed, 0000 is returned.

2.192. Query LAMP STATUS

Hexadecimal	02h	51h	24h	53h	03h	
Character	Q	\$	S		03h	
■ Response (Callback)						
Lamp OFF						
Hexadecimal	02h	30h	03h			
Character	0					
In turning ON						
Hexadecimal	02h	31h	03h			
Character	1					
Lamp ON						
Hexadecimal	02h	32h	03h			
Character	2					
In turning OFF						
Hexadecimal	02h	33h	03h			
Character	3					
Acceptability						
SECURITY	STANDBY	NO SIGNAL	AV MUTE			
○	○	○	○			

2.193. Query TEMP INFORMATION

Hexadecimal	02h	51h	4Dh	41h	3Ah	*1	03h
Character	Q	T	M	:	*	*2	03h

■ Parameters (*1,*2)

	Intake air	Exhaust air
Hexadecimal	30h	31h
Character	0	1

■ Response (Callback)

Example: 20°C (68°F)

Hexadecimal	02h	30h	30h	32h	30h	2Fh	30h	30h	36h	38h	03h
Character	0	0	0	2	0	/	0	0	6	8	

Example: -10°C (14°F)

Hexadecimal	02h	2Dh	30h	31h	30h	2Fh	30h	30h	31h	34h	03h
Character	-	0	1	0	0	/	0	0	1	4	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

2.194. Query SERIAL NUMBER

Hexadecimal	02h	51h	53h	4Eh	03h
Character	Q	S	S	N	03h

■ Response (Callback)

Example: SB12345678

Hexadecimal	02h	41h	42h	31h	32h	33h	34h	35h	36h	37h	38h	03h
Character	S	B	1	2	3	4	5	6	7	8		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	○	○

2.195. Query MAC ADDRESS

Hexadecimal	02h	51h	4Dh	41h	03h
Character	Q	M	M	A	03h

■ Response (Callback)

Example: AB0102030405

Hexadecimal	02h	41h	42h	30h	31h	30h	32h	30h	33h	30h	34h	30h	35h	03h
Character	A	B	0	1	0	2	0	3	0	4	0	5		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	x	○	○

2.196. Query RUNTIME - PROJECTOR

Hexadecimal	02h	51h	56h	58h	3Ah	52h	54h	4Dh	49h	30h	03h
Character	Q	V	X	:	R	T	M	I	O		

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	52h	54h	4Dh	49h	30h	3Dh	2Dh
Character	R	T	M	I	O	=	+	
Hexadecimal	*1	*3	*5	*7	*9	03h		
Character	*2	*4	*6	*8	*10			

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

Example: 55 hours

Hexadecimal	30h	30h	30h	35h	35h
Character	0	0	0	5	5

2.197. Query LAMP PART No.

Hexadecimal	02h	51h	56h	58h	3Ah	4Ch	4Dh	4Eh	53h	30h	03h
Character	Q	V	X	:	L	M	M	N	S	0	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	4Ch	4Dh	4Eh	53h	30h	3Dh
Character	L	M	M	N	S	0	=
Hexadecimal	*1	*3	*5	*7	*9	03h	
Character	*2	*4	*6	*8	*10		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

Example: ET-LAF100

Hexadecimal	45h	54h	2Dh	4Ch	41h	46h	31h	30h	30h
Character	E	T	-	L	A	F	1	0	0

■ Note:

- This figure of the parameter fluctuates.

2.198. Query LAMP SERIAL NUMBER

Hexadecimal	02h	51h	56h	58h	3Ah	4Ch	53h	4Eh	53h	30h	03h
Character	Q	V	X	:	L	M	S	N	S	0	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	4Ch	53h	4Eh	53h	30h	3Dh
Character	L	S	N	S	0		=
Hexadecimal	*1	*3	*5	*7	*9	03h	
Character	*2	*4	*6	*8	*10		

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
x	○	○	○

■ Parameters (*1,*2,*3,*4,*5,*6,*7,*8,*9,*10)

Example: 12345-67890

Hexadecimal	31h	32h	33h	34h	35h	2Dh	36h	37h	38h	39h	30h
Character	1	2	3	4	5	-	6	7	8	9	0

■ Note:

- This figure of the parameter fluctuates

2.199. Query CCONTROL PANEL OPERATION

Hexadecimal	02h	51h	50h	44h	03h
Character		Q	P	K	

■ Response (Callback)

In the period when the command can be accepted

Hexadecimal	02h	*1	03h
Character		*2	

Acceptability

SECURITY	STANDBY	NO SIGNAL	AV MUTE
○	○	○	○

■ Parameters (*1,*2)

	ENABLE	DISABLE
Hexadecimal	30h	31h
Character	0	1

3. APPENDIX TABHLE

3.1. SCHEDULE CONTROL COMMAND LIST

Classification	Control Command	Function
POWER CONTROL	10	STANDBY
	11	POWER - ON
AV MUTE	20	AV MUTE - OFF
	21	AV MUTE - ON
INPUT SELECT	31	COMPUTER - IN
	41	VIDEO – IN
	42	S-VIDEO - IN
	51	DVI-I - IN
	53	HDMI - IN
	61	NETWORK - IN
LAMP POWER	70	LAMP POWER - NORMAL
	71	LAMP POWER - ECO
SIDE BY SIDE	90	SIDE BY SIDE - OFF
	91	SIDE BY SIDE - ON
IN STANDBY MODE	A0	IN STANDBY MODE(AUDIO) - OFF
	A1	IN STANDBY MODE(AUDIO) - ON
AUDIO IN VOLUME	C0~FF	VOLUME LEVEL 0~63

3.2. FNC COMMAND PARAMETERS

Parameters	Function name	Parameters	Function name
0000	DISABLE	0053	HDMI SIGNAL LEVEL
0001	PICTURE	0054	CLOSED CAPTION
0002	POSITION	0055	CLOSED CAPTION MODE
0003	LANGUAGE	0056	SCREEN FORMAT
0004	DISPLAY OPTION	0057	SCREEN POSITION
0005	PROJECTOR SETUP	0058	OTHER FUNCTIONS - AUTO SETUP
0006	SECURITY	0059	FREEZE
0007	NETWORK	0060	AV MUTE
0008	PICTURE MODE	0061	INDEX WINDOW
0009	CONTRAST	0062	DIGITAL ZOOM
0010	BRIGHTNESS	0063	SIDE BY SIDE
0011	COLOR	0064	STATUS
0012	TINT	0065	PROJECTOR - ID
0013	SHARPNESS	0066	INITIAL START UP
0014	COLOR TEMPERATURE	0067	PROJECTION METHOD
0015	ADVANCED MENU	0068	HIGH ALTITUDE MODE
0016	DAYLIGHT VIEW	0069	LAMP POWER
0017	DIGITAL CINEMA REALITY	0070	SCHEDULE
0018	NOISE REDUCTION	0071	ECO MANAGEMENT
0019	TV-SYSTEM	0072	EMULATE
0020	RGB/YpbPr	0073	FUNCTION BUTTON
0021	CONTRAST - R	0074	AUDIO SETTING
0022	CONTRAST - G	0075	DATE AND TIME
0023	CONTRAST - B	0076	TEST PATTERN
0024	BRIGHTNESS - R	0077	AUTO POWER SAVE
0025	BRIGHTNESS - G	0078	AMBIENT LIGHT DETECTION
0026	BRIGHTNESS - B	0079	SIGNAL DETECTION
0027	KEYSTONE	0080	AV MUTE DETECTION
0028	SHIFT	0081	NO SIGNAL SHUT-OFF
0029	SHIFT V	0082	STANDBY MODE
0030	DOT CLOCK	0083	VOLUME
0031	CLOCK PHASE	0084	BALANCE
0032	OVER SCAN	0085	IN STANDBY MODE
0033	ASPECT	0086	POWER BUTTON BEEP
0034	FRAME LOCK	0087	AUDIO IN SELECT- VIDEO
0035	ON-SCREEN DISPLAY	0088	AUDIO IN SELECT- S-VIDEO
0036	DVI-I IN	0089	AUDIO IN SELECT- COMPUTER
0037	HDMI IN	0090	AUDIO IN SELECT- DVI-I
0038	CLOSED CAPTION	0091	AUDIO IN SELECT- HDMI
0039	SCREEN SETTING	0092	AUDIO IN SELECT- NETWORK
0040	STARTUP LOGO	0093	TIME ZONE
0041	AUTO SETUP	0094	DATE AND TIME
0042	SIGNAL SEARCH	0095	WIRED LAN
0043	BACK COLOR	0096	WIRELESS LAN
0044	WIDE MODE	0097	NAME CHANGE
0045	SXGA MODE	0098	PASSWORD
0046	OTHER FUNCTIONS	0099	PASSWORD CHANGE
0047	INPUT GUIDE	0100	NETWORK CONTROL
0048	OSD DESIGN	0101	LIVE MODE CUT IN
0049	WARNING MESSAGE	0102	COMPUTER SEARCH
0050	DVI-I DIGITAL/ANALOG	0103	MULTI-LIVE
0051	DVI EDID	0104	NETWORK STATUS
0052	DVI SIGNAL LEVEL		