



Set content

Model Type	TY-CSP1
Number	1
Carton dimensions	140 mm x 325 mm x 172 mm (5.52" x 12.80" x 6.78")
Gross weight	1600 g (3.53 lbs)
Accessories	USB Type-C to Type-C cable (Approx.1.0 m) USB Type-C to Type-A cable (Approx.1.8 m) AC Adaptor (including AC plugs) Lens cover Cable lock fitting Screw (M2.6 x 12) Cable tie

PRODUCT SPECIFICATION

(design and specification subject to change without notice)

SPECIFICATION	
CAMERA	
Camera sensor	1/2.7" 5MP CMOS
Shooting pixels	2560 x 1440 x 4
Viewing angle	360 (H) x 60 (V)
Camera units	4
Lens FOV (Field of view)	140 (D) / 140 (H) / 103 (V)
F number of the lens	2.5
Lens TTL	14.7 mm (0.58")
Opt Distortion	<-14.9 %
USB video format	UVC 1.5 1280 x 720 @ 30fps, 1920 x 1080 @ 30fps Motion JPEG
MIC	
Microphone	MEMS microphone array
MIC units	7
Beam forming	Supported
MIC sensitivity	-35 dBFS
SN ratio	68.75 dBA
MIC pick up distance	Up to 5 m (16.4 ft)
SPEAKER	
Speaker out	1.5 W (When supplying power from USB Type-C) or 3 W (When AC adaptor is connected)
Noise canceling	AEC/AGC/DNR/Keyboard noise suppression
USB sound format	UAC Revision 1.0
TERMINALS	
USB	USB Type-C (USB2.0)
Power	DC plug
ELECTRICAL	
Power	USB Type-C (5 V/3 A) or AC adaptor DC 12 V/2 A
Power consumption (when outputting video)	11W
MECHANICAL	
Dimension (Diameter x Height)	φ 64 mm (2.52") x 285 mm (11.23") (Operation base φ 100 mm (3.94"))
Weight	950 g/2.1 lbs
Color	black
Security slot	Noble Wedge lock (with mounting surfaces of 11 mm φ or less.)
ENVIRONMENTAL	
Operating Environment	Temperature : 0 °C to 40 °C (32 °F to 104 °F) Humidity : 20% to 80% (Non condensation)
Usable altitude range	0 m to 2800 m / 0 ft to 9186 ft
UPC Code	885170391277
Features	
Video display modes (View)	Single / Dual / Multi / Surround / Stable
The operation of button	Changing Mode / Adjustment of volume / Audio mute
Application	PressIT360 application Support OS : Microsoft Windows (Windows 10/Windows 11), / macOS

DIMENSIONS

Units : mm [inch]

