



### Product specification (design and specification subject to change without notice)

#### ■ SLOT Compatibility

Intel® SDM specification

#### ■ Terminal

DIGITAL LINK IN / LAN	RJ45 x 1 For network connection, For DIGITAL LINK connection 100BASE-TX, Long reach mode, Compatible with HDCP2.2
DIGITAL LINK OUT	RJ45 x 1 For DIGITAL LINK connection Long reach mode, Compatible with HDCP2.2

#### ■ Mechanical

Dimensions (W x H x D)	W 7.68" x H 0.99" x D 4.85" (195 x 25 x 123.2 mm)
Weight	0.6 lb (280 g)
Carton size (W x H x D)	W 12.6" x H 2.3" x D 12.5" (319 x 56 x 316 mm)
Gross weight	1.7 lb (750 g)
Accessories	Operating Instructions x1

#### ■ Recommended cable

LAN cable (STP cable of CAT5e or higher)

#### ■ Supported signal

Resolution	Motion picture-related signal: 480/60p, 576/50p to 4096 x 2160 Still picture-related signal: 640 x 480 to 3840 x 2400 (Non-interlace)
Dot clock frequency	25 MHz to 297 MHz

\* Image signals that can be displayed by displays and projectors depend on the performance of the displays and projectors.

#### ■ Max. Transmission distance

150 m (Long reach mode, 1080/60p (4:4:4 24bit) or lower resolution)
100 m (1080/60p (4:4:4 36bit) or lower resolution)
50 m (4K/60p (4:2:0) or lower resolution)

### ● This product is a DIGITAL LINK terminal board that can be used by attaching it to our displays and projectors.

\* This product does not work by itself.

\* This product will not work if it is installed on a product other than the corresponding model. Please check our website for compatible models.

\* Please consult with a professional engineer or dealer to install or remove this product.

### DIMENSIONS

Cautions: This drawing is not a scale  
Units : inches (mm)

