



Presto! PageManager 9

Presto! BizCard 6

KV-S1015C DOCUMENT SCANNER

Compact design for greater convenience.

The Panasonic KV-S1015C scanner features a slim and compact body, ideal for small offices / home offices, and offers easy operation with advanced features.

- Compact but high speed duplex colour scanner
KV-S1015C is able to scan at the speed of 20 pages per minute and 40 images per minute in duplex mode.
- Ready to use
The KV-S1015C is delivered complete with a software solution featuring Biz Card to scan Business Cards and convert the data which they hold into a searchable database and Page Manager to store, organize and edit digital documents produced by the KV-S1015C.

- Easy to use
Simply press the button and send documents to three pre-registered destinations such as a folder, an email address or a printer.

Features

- Modern slim & compact design
- High-speed colour scanning at 20ppm / 40ipm
- 50 Sheet Automatic Document Feeder
- 3 customisable Single Touch Scan Keys
- Active Double Feed Prevention Roller System
- Simple Touch Free Scanning
- Embossed Card Scanning
- Cloud Connectivity

KV-S1015C PRODUCT GUIDE AND SPECIFICATIONS

Easy

Single Touch Scan

Simply press the button and send documents to three pre-registered destinations.



Reliable

Active Double Feed Prevention

The rotating double feed roller ensures the preceding documents are kept in the feeding area while the top page is fed into the scanner, thus preventing double feeding.



Quick

Touch Free Scanning

For smaller scan jobs, Touch Free Scanning is convenient for manual paper feeding - just insert documents directly into the scanner.



Flatbed Scanner
KV-SS081

Model		KV-S1015C
SCANNER TYPE		Duplex Sheet Feed Scanning
SCANNER TECHNOLOGY		1-Line CIS (Contact Image Sensor)
SCANNING SPEED*1 (A4, Portrait)		Up to 20 ppm / 40 ipm (Binary 200 dpi) Up to 20 ppm / 40 ipm (Colour 200 dpi)
RESOLUTION (Colour and B/W)		Resolution : 100 - 600dpi (1dpi step) Optical : 300/600dpi
AUTOMATIC DETECTION		Ultrasonic Double Feed Detection
IMAGE COMPRESSION		JPEG (Grayscale/Colour)
IMAGE OUTPUT		Binary, Grayscale, Colour, MultiStream (Colour & Binary or Gray & Binary)
BINARY MODE HALFTONE		Dither, Error Diffusion
IMAGE CONTROL		Automatic Binary/Color Distinction, Multi Color Drop Out, Blank Page Removal, Double Exposure, Smooth Background, Automatic Cropping, De-skewing, Dynamic Threshold, White Level From Paper, Image Emphasis (5 steps), Gamma Correction, Automatic Separation, Noise Reduction, Shadow Removal, Mirror Image, Monochrome Reversing, 2-Page Separation and much more.
OTHER FUNCTIONS		Separation sheet, Single Touch Scan
DOCUMENT	SIZE (ADF)	Minimum 48 mm x 70 mm (1.9 in. x 2.8 in.) length Maximum 216 mm x 2,540 mm (8.5 in. x 100 in.) length
	WEIGHT/THICKNESS*2	Single 40 - 209 g/m ² (11 lbs. - 55 lbs.) Continuous 40 - 209 g/m ² (11 lbs. - 55 lbs.) Card Up to approx. 0.76 mm (0.03 in.) in thickness + embossing (ISO standard 7810 ID-1 card scanning including embossed card)
AUTOMATIC DOCUMENT FEEDER		Up to 50 sheets (20 lbs., 80 g/m ²), 3 hard cards (ISO 7810 ID-1)
SUPPORTED OPERATING SYSTEM		Windows® XP SP3 or later (32-bit), Windows Vista® SP2 or later (32/64-bit), Windows® 7 and Windows® 8 (32/64-bit)
INTERFACE		High-Speed USB 2.0, Up to 480 Mbps transfer rate
POWER REQUIREMENT		AC 100 - 120 V 50/60 Hz, AC 200 - 240 V 50/60 Hz
POWER CONSUMPTION		Scanning mode 17 W or less Idle mode 4.5 W or less Sleep mode 1.6 W or less Power off mode 0.3 W or less
OPERATING ENVIRONMENT		Temperature 10 °C - 35 °C (50 °F - 95 °F) Temperature 10 °C - 35 °C (50 °F - 95 °F)
STORAGE ENVIRONMENT		Temperature 0 °C - 40 °C (32 °F - 104 °F) Humidity 10 % RH - 80 % RH
EXTERNAL DIMENSIONS*3 (W x D x H)		303 mm x 177 mm x 137 mm (11.9 in. x 7 in. x 5.4 in.) without Feed tray
WEIGHT*3		2.7 kg (5.9 lbs.)
ACCESSORIES		DVD-ROM : Drivers and Utilities for Windows / Manuals Driver software - ISIS / TWAIN Application software - Image Capture Plus (without OCR) Presto! PageManager 9*4*5, Presto! BizCard 6*4 Safety Guide, Quick Reference Guide, Mixed batch card guide, AC adapter & Power cord, USB cable
OPTIONS	ROLLER EXCHANGE KIT	KV-SS059 (Double-feed prevention roller x 1, Paper feed roller x 1)
	ROLLER CLEANING PAPER	KV-SS03
	FLATBED SCANNER	KV-SS081

*1 The scanning speed differs depending on the host computer, the operating system, the application, the measuring method, the quantity of data in the image, and the paper type. The scanning speed depends on a measuring method of Panasonic.

*2 "Weight in pounds" of paper represents the weight of 500 (432 x 559 mm / 17 x 22 inches) sheets.

*3 Dimensions and weight are approximate.

*4 Presto! PageManager and Presto! BizCard are either registered trademarks or trademarks of NewSoft Technology Corporation in the United States and/or other countries.

*5 The edition of Presto! PageManager 9 included with this unit is different to the commercially available one.

Trademarks and registered trademarks

- ENERGY STAR and the ENERGY STAR mark are registered U.S. marks.

- ISIS® is a registered trademark or trademark of EMC Corporation in the United States and other countries.

- Microsoft®, Windows® and Windows Vista® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

- All other brand or product names are the property of their respective holders.

• Design and specifications are subject to change without notice.

This Product is designed to reduce hazardous chemical substances along with the RoHS directive.

Panasonic
BUSINESS