


Panasonic[®]

Operating Instructions

Zoom lens **Commercial Use**

Model No. **ET-D3QW200**



ENGLISH

FRANÇAIS

日本語

Thank you for purchasing this Panasonic product.

- To ensure correct use of this lens, please read the operating instructions supplied with the lens and the projector carefully.
- **Before using this product, be sure to read “Read this first!” (➡Page 3).**
- Please save this manual for future use.

Contents

Read this first!	3
Before Use	5
Preparation	5
Before replacing the projection lens	5
Attaching and Detaching the Lens	5
Peripheral focus adjustment function	6
Lens calibration	7
Projection relationships	8
Lens shift ranges	12
Specifications	13
Dimensions	13
Projected image size and Projection distance	Appendix / Annexe / 付録 1
The "Appendix" can be found after the Japanese language section ().	

Read this first!

Always follow these precautions

WARNING:

Do not look at or place your skin into the light emitted from the lens while the projector is being used.

Doing so can cause burns or loss of sight.

- Strong light is emitted from the projector's lens. Do not look at or place your hands directly into this light.
- Turn off the power when moving away from the projection lens or projector.

Do not project an image with the lens cover attached.

- Doing so can cause fire.

CAUTION:

Before replacing the projection lens, be sure to turn off the power and disconnect the power plug from the wall outlet.

- Unexpected projection of light may cause injury to eyes.
- Replacing the projection lens without removing the power plug may result in electric shock.

Do not stand in front of the lens while the projector is being used.

Doing so can cause damage and burns to clothing.

- Strong light is emitted from the projector's lens.

Do not place objects in front of the lens while the projector is being used.

Doing so can cause fire, damage to the object, or malfunction of the lens and projector.

- Strong light is emitted from the projector's lens.

Do not open the desiccant bag. Do not eat the contents.

Inadvertently ingesting desiccant could be harmful.



- If the desiccant gets into your eyes or mouth, immediately rinse with plenty of water and seek medical attention.
- Keep desiccant out of the reach of children.

Read this first! (continued)

■ Hazard distance (IEC 62471-5:2015)

The distance from the projection lens surface, at which the emission reaches the Accessible Emission Limit (AEL) of risk group 2, is known as the hazard distance (HD) or safety distance. The area where the emission exceeds the Accessible Emission Limit of risk group 2 is called the hazard zone (HZ).

Within the hazard zone, never look into the light projected from the projector. The eyes may be damaged by direct irradiation even if you look at the light just for a moment. If you are outside the hazard zone, it is considered to be safe in all circumstances except deliberately staring into the light projected from the projector.



■ Risk group

The combination of the projector and the projection lens is categorized as risk group 2 when the hazard distance is 1 m (39-3/8") or less. It is categorized as risk group 3 when the hazard distance exceeds 1 m (39-3/8"), and it will be for professional use instead of consumer use.

In case of risk group 3, there is a possibility of damaging the eyes by direct irradiation when looking into the projection light from inside the hazard zone even for a moment.

In the case of risk group 2, safe use without damaging the eyes is possible in all circumstances except deliberately staring into the light projected from the projector.

The risk group for the combination of the projection lens and a compatible projector is as follows.

Projector model	Risk group
PT-RQ50K	Risk group 2

Before Use

This zoom lens is a projection lens equipped with an EEPROM*1 and stepping motor.

*1 EEPROM: Electrically erasable programmable read-only memory

Supported projectors


PT-RQ50K

Note

- Some of the alphabet letters at the end of projector model numbers may be omitted in this manual.
- Models other than the above may also be supported. Refer to the operating instructions for your projector or the website (<https://docs.connect.panasonic.com/projector>).

Supplied Accessories

Make sure that the following has been provided.

Part name	Appearance
Lens cover	 ● The product is delivered with a lens cover attached. 1 each for front and rear

Preparation

Before replacing the projection lens

Return the projection lens to the home position before replacing or removing it.

For details on how to return the lens to the home position, refer to the operating instructions of the projector.

Attention

- Make sure that the projector power supply is switched off before attaching or detaching the projection lens.
- After removing the projection lens, store it safely away from vibration or impacts.
- Do not touch the electrical contacts of the projection lens with your fingers. Dust and dirt on the contacts may cause contact malfunctions, while static electricity may damage the unit.
- Do not touch the surface of the lens with bare hands. Finger prints and dirt on the surface of the lens will be magnified by the lens and lower the quality of the projected image. Place the supplied lens cover on the zoom lens when the projector is not in use.
- The lens is made of glass. The lens could be damaged if brought into contact with or rubbed against hard objects. Handle the lens carefully.
- Use a clean, soft and dry cloth to wipe away dust and dirt from the projection lens. Do not use fluffy cloths containing oil, water or dust for cleaning. The lens is easily damaged, so do not apply excessive pressure when wiping it.

Attaching and Detaching the Lens


For details on attaching and detaching the projection lens, refer to the operating instructions of the projector.

Preparation (continued)

Peripheral focus adjustment function


When you change the size of the projected image, the focal balance between the center and peripheral areas of the screen may shift. This shift in balance tends to increase proportionally with smaller throw ratios.

The ET-D3QW200 is equipped with a peripheral focus adjustment function to correct the shift in focal balance between the center and peripheral areas of the screen.



Peripheral focus adjustment ring

■ Adjusting the focus



- 1) Turn the peripheral focus adjustment ring in the direction of the arrow to match the projection distance displayed on the lens to the actual distance from the lens to the screen.
- 2) Operate the projector to align the focus of the center of the projected image.

Note

- The projection distances displayed on the lens are approximate guides.
- The lens focus is not stable immediately after powering on due to the affect of heat produced by the light from the light source.
It is recommended that the focus be adjusted after the image has been projected for approximately 1 hour.

Preparation (continued)

Lens calibration

Perform lens calibration after attaching the lens.

PROJECTOR SETUP		1/2
PROJECTOR ID	ALL	
PROJECTION METHOD		
LENS		
OPERATION SETTING	NORMAL	
LIGHT OUTPUT	100.0%	
BRIGHTNESS CONTROL	AUTO	
NO SIGNAL SETTING		
INITIAL STARTUP	LAST MEMORY	
STARTUP INPUT SELECT	LAST USED	
DATE AND TIME		
SCHEDULE	OFF	
MULTI PROJECTOR SYNC		
MENU SELECT		
ENTER SUB MENU		

LENS	
LENS INFORMATION SETTING	
LENS MEMORY	
LENS HOME POSITION	
ACTIVE FOCUS OPTIMIZER	
LENS CALIBRATION	
MENU SELECT	
ENTER SUB MENU	

LENS CALIBRATION : ET-D3QW200	
SHIFT/FOCUS/ZOOM	
SHIFT/FOCUS	
ZOOM	
MENU SELECT	
ENTER EXECUTE	

LENS CALIBRATION : ET-D3QW200	
Proceed LENS CALIBRATION, and return to HOME POSITION.	
OK CANCEL	
◀▶ CHANGE	
ENTER EXECUTE	

- 1) Press the <MENU> button.
- 2) Use the ▲ and ▼ buttons to select [PROJECTOR SETUP], and press the <ENTER> button.
 - The [PROJECTOR SETUP] screen appears.
- 3) Use the ▲ and ▼ buttons to select [LENS], and press the <ENTER> button.
 - The [LENS] screen appears.
- 4) Use the ▲ and ▼ buttons to select [LENS CALIBRATION], and press the <ENTER> button.
 - The [LENS CALIBRATION] screen appears.
- 5) Use the ▲ and ▼ buttons to select [SHIFT/FOCUS/ZOOM], and press the <ENTER> button.
 - The confirmation screen appears.
- 6) Use the ◀ and ▶ buttons to select [OK], and press the <ENTER> button.
 - Lens calibration starts.
 - The projection lens moves to the home position after adjustment range calibration is complete.


Note

- If lens calibration is not performed, the available zoom range will be narrowed.

Projection relationships

The dimensional relationship between the screen and the projector is shown below.

■ Dimensional relationship diagram



Note

- This diagram assumes that the size and position of the projected image will be adjusted so that the image fills the entire screen.
- This illustration is not drawn to scale.

	L	Projection distance
	LW	Minimum distance
	LT	Maximum distance
L1	Lens protrusion dimension (distance from the front surface of the projector to the forward end of the projection lens)	
L2	Position of the lens optical axis (distance from the front surface of the projector to the lens optical axis)	
L3	Position of the lens apex (distance from the side of the projector to the lens apex)	
SH	Projected image height	
SW	Projected image width	
SD	Projected image size	

● Dimensions for L1, L2, and L3 (approximate values)


(Unit: m)

Projector model	L1	L2	L3
PT-RQ50K	0.31	0.24	0.17

Projection relationships (continued)

Note

- The illustrations of projectors in this manual are for informational purposes only and do not represent a specific projector model. Configurations may vary with the model.
- If the screen is tilted downward, extend the adjustable feet on the sides of the projector until the projected image is rectangular.
If the projector is inclined horizontally, adjust the adjustable feet until the projector is level.
You can extend the adjustable feet by turning them as shown in the diagram. To return the feet to the original position, turn them in the opposite direction.



Attention


- To prevent obstruction of the intake and exhaust vents, install the projector with a clearance at least 500 mm (1 ft. 7 in.) from walls and objects.
If you are installing the projector in a sealed space, be sure to provide additional air conditioning equipment and ventilation equipment. Insufficient ventilation will result in an accumulation of heat and may activate the projector's protection circuit.
- Avoid setting up in places which are subject to sudden temperature changes, such as near an air conditioner or lighting equipment (studio lamps, etc.).

■ Dimensional relationship

For details on the projection distance (L), refer to "Projected image size and Projection distance" and "Projection distance formulas" in the Appendix.

Projection relationships (continued)

■ [GEOMETRY] projection range



Projector model	Only [KEYSTONE] used		[KEYSTONE] and [CURVED CORRECTION] used together				Only [CURVED CORRECTION] used	
	Vertical keystone correction angle α (°)	Horizontal keystone correction angle β (°)	Vertical keystone correction angle α (°)	Horizontal keystone correction angle β (°)	Min. value of R2/L2	Min. value of R3/L3	Min. value of R2/L2	Min. value of R3/L3
PT-RQ50K	±15	±5	-	-	-	-	-	-

Projection relationships (continued)


Note

- When [GEOMETRY] is used, the focus of the entire screen may be lost as correction increases.
- Adjustment range of the [GEOMETRY] items may not match the listed projection range depending on the projection lens. Use this projector within the projection range, otherwise the correction may not work.
- The geometric adjustment function cannot be used when the video signal in simultaneous format or the video signal with vertical scanning frequency of 100 Hz or 120 Hz is input. When projecting an image in simultaneous format or an image with vertical scanning frequency of 100 Hz or 120 Hz, install the projector following the instructions below so that distortion does not occur in the projected image.
 - Use a flat screen.
 - Install the projector so that the front side of the projector is parallel to the screen.
 - Install the projector so that the image can be projected within the lens shift adjustment range.

Lens shift ranges

After moving the lens to the home position according to “Lens calibration” on page 7, you can use the lens shift adjustment function on the projector to adjust the position of the projected image within the respective lens shift ranges based on the optical screen center position (standard projection position). The optical screen center position is the screen position using the optical center of the projector as the base.

Perform lens shift adjustment within the ranges shown in the following illustrations. Moving the lens outside of the adjustment ranges may alter the focus. This occurs due to limitations in lens movement that are intended to protect the optical components. The following illustrations depict lens shift ranges for floor installations of the projector.



Note


- The home position of the projector a point of origin position for the lens shift (i.e., vertical and horizontal positions of the lens) based on the results of lens calibration. It is not the optical center position of the screen.

Specifications

F value	2.5
Focal Length (f)	17.5 mm (11/16") - 20.7 mm (13/16")
Supported screen size	100" - 1500"
Dimensions	Width 313 mm (12-5/16") Height 192 mm (7-9/16") Depth 532 mm (20-15/16")
Net Weight	11.3 kg (24.9 lb)

Dimensions

(Unit: mm)



■ Indication of the manufacturer and the importer with EU Directive requirements

English	Manufactured by: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japan Importer: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Germany Authorized Representative in EU: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Germany
Български	Производител: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Япония Вносител: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Германия Упълномощен представител в ЕС: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Германия
Čeština	Vyrobil: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japonsko Dovozce: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Německo Oprávněný zástupce v EU: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburk, Německo
Српски	Произведен од: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Јапан Увозник: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Немачка Овлашћени представник у ЕУ: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Немачка
Dansk	Fremstillet af: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japan Importer: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Tyskland Autoriseret repræsentant i EU: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Tyskland
Deutsch	Hergestellt von: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japan Importeur: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Deutschland Vertretungsberechtigter in der EU: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Deutschland
Eesti	Tootja: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Jaapan Maaletooja: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Saksamaa Volitatud esindaja ELis: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Saksamaa

Ελληνικά	Κατασκευάστηκε από: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Ιαπωνία Εισαγωγέας: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Γερμανία Εξουσιοδοτημένος αντιπρόσωπος στην ΕΕ: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Γερμανία
Español	Fabricado por: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japón Importador: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Alemania Representante Autorizado para la UE: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburgo, Alemania
Français	Fabriqué par : Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japon Importateur : Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Allemagne Représentant autorisé dans l'UE : Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hambourg, Allemagne
Gaeilge	Arna dhéanamh ag : Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, An tSeapáin Allmhaireoir : Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, An Ghearmáin Ionadaí Údaraithe san AE : Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, An Ghearmáin
Hrvatski	Proizvodi: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japan Uvoznik: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Njemačka Ovlašteni zastupnik u EU-u: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Njemačka
Íslenskur	Framleitt af: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japan Innflytjandi: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Þýskalandi Viðurkenndur fulltrúi í ESB: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Þýskalandi
Italiano	Fabbricato da: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Giappone Importatore: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Germania Rappresentante autorizzato nell'UE: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Amburgo, Germania

Latviešu	Ražotājs: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japāna Importētājs: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Vācija Oficiālais pārstāvis ES: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Vācija
Lietuvių	Gamintojas: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japonija Importuotojas: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Vokietija Igaliotasis atstovas ES: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburgas, Vokietija
Magyar	Gyártotta: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japán Importőr: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Németország Hivatalos képviselő az EU-ban: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Németország
Malti	Manifatturat minn: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, il-Gappun Importatur: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, il-Germanja Rappreżentant Awtorizzat fl-UE: Panasonic Connect Europe GmbH Panasonic Testing CentreWinsbergring 15, 22525 Hamburg, il-Germanja
Nederlands	Geproduceerd door: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japan Importeur: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Duitsland Bevoegde vertegenwoordiger in de EU: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Duitsland
Norsk	Produsert av: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japan Importør: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Tyskland Autorisert representant i EU: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Tyskland
Polski	Wyprodukowano przez: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japonia Importer: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Niemcy Upoważniony przedstawiciel w UE: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Niemcy

Português	Fabricado por: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japão Importador: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Alemanha Representante Autorizado na UE: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburgo, Alemanha
Română	Fabricat de: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japonia Importator: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Germania Reprezentant autorizat în UE: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Germania
Slovenčina	Výrobca: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japonsko Dovozca: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Nemecko Autorizovaný zástupca v EÚ: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Nemecko
Slovenščina	Proizvajala: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japonska Uvoznik: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Nemčija Pooblaščen zastopnik v EU: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Nemčija
Suomi	Valmistaja: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japani Maahantuoja: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Saksa Valtuutettu edustaja EU:ssa: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hampuri, Saksa
Svenska	Tillverkad av: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japan Importör: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Tyskland Auktoriserad representant i EU: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Tyskland
Türkçe	Tarafından Üretilmiştir: Panasonic Projector & Display Corporation 2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japonya İthalatçı: Panasonic Connect Europe GmbH Hagenauer Strasse 43, 65203 Wiesbaden, Almanya AB Yetkili Temsilcisi: Panasonic Connect Europe GmbH Panasonic Testing Centre Winsbergring 15, 22525 Hamburg, Almanya

Manufactured by: Panasonic Projector & Display Corporation

2-15 Matsuba-cho, Kadoma City, Osaka 571-8503, Japan

Importer: Panasonic Connect Europe GmbH

Hagenauer Strasse 43, 65203 Wiesbaden, Germany

Authorized Representative in EU: Panasonic Connect Europe GmbH

Panasonic Testing Centre

Winsbergring 15, 22525 Hamburg, Germany

Importer for UK:

Panasonic Connect UK,

a branch of Panasonic Connect Europe GmbH,

Maxis 2, Western Road, Bracknell, Berkshire, RG12 1RT



Disposal of Old Equipment

Only for European Union and countries with recycling systems



This symbol on the products, packaging, and/or accompanying documents means that used electrical and electronic products must not be mixed with general household waste. For proper treatment, recovery and recycling of old products, please take them to applicable collection points in accordance with your national legislation.

By disposing of them correctly, you will help to save valuable resources and prevent any potential negative effects on human health and the environment.

For more information about collection and recycling, please contact your local authority.

Penalties may be applicable for incorrect disposal of this waste, in accordance with national legislation.

Product Information (for Turkey only)

AEEE Yönetmeliğine Uygundur.

Environment care information for users in China



This symbol is only valid in China.

Panasonic Projector & Display Corporation

Web Site : <https://docs.connect.panasonic.com/projector>

© Panasonic Projector & Display Corporation 2025

Panasonic Projector & Display Americas LLC

Two Riverfront Plaza, Newark, NJ 07102

TEL: +1-201-348-7000

HS0621AM2045 -PS

Printed in Japan

Appendix / Annexe / 付録

- Projected image size and Projection distance
- Taille de l'image projetée et Distance de projection
- 投写画面サイズと投写距離

(Unit / Unités / 単位 : m)

When the screen aspect ratio is 17:9 (Throw ratio: [0.548 - 0.650:1])

Lorsque le rapport d'aspect de l'écran est 17:9 (Rapport de projection : [0.548 - 0.650:1])

アスペクト比 17:9 (スローレシオ : [0.548 - 0.650:1])

SD	SH	SW	LW	LT
2.54 (100")	1.188	2.245	1.19	1.42
3.05 (120")	1.426	2.694	1.44	1.72
3.81 (150")	1.783	3.367	1.82	2.17
5.08 (200")	2.377	4.490	2.46	2.92
6.35 (250")	2.971	5.612	3.10	3.67
7.62 (300")	3.565	6.734	3.73	4.42
8.89 (350")	4.160	7.857	4.37	5.17
10.16 (400")	4.754	8.979	5.00	5.92
12.70 (500")	5.942	11.224	6.27	7.42
15.24 (600")	7.131	13.469	7.54	8.92
17.78 (700")	8.319	15.714	8.82	10.42
20.32 (800")	9.507	17.959	10.09	11.93
22.86 (900")	10.696	20.203	11.36	13.43
25.40 (1000")	11.884	22.448	12.63	14.93
27.94 (1100")	13.073	24.693	13.90	16.43
30.48 (1200")	14.261	26.938	15.17	17.93
33.02 (1300")	15.450	29.183	16.44	19.43
35.56 (1400")	16.638	31.427	17.71	20.93
38.10 (1500")	17.827	33.672	18.98	22.43

Appendix / Annexe / 付録 (continued / suite / つづき)

(Unit / Unités / 単位 : m)

When the screen aspect ratio is 16:10 (Throw ratio: [0.652 - 0.772:1]) Lorsque le rapport d'aspect de l'écran est 16:10 (Rapport de projection : [0.652 - 0.772:1]) アスペクト比 16:10 (スローレシオ : [0.652 - 0.772:1])				
SD	SH	SW	LW	LT
2.54 (100")	1.346	2.154	1.36	1.62
3.05 (120")	1.615	2.585	1.65	1.96
3.81 (150")	2.019	3.231	2.08	2.48
5.08 (200")	2.692	4.308	2.81	3.33
6.35 (250")	3.365	5.385	3.53	4.18
7.62 (300")	4.039	6.462	4.25	5.03
8.89 (350")	4.712	7.539	4.97	5.89
10.16 (400")	5.385	8.616	5.69	6.74
12.70 (500")	6.731	10.770	7.14	8.44
15.24 (600")	8.077	12.923	8.58	10.15
17.78 (700")	9.423	15.077	10.03	11.86
20.32 (800")	10.770	17.231	11.47	13.56
22.86 (900")	12.116	19.385	12.92	15.27
25.40 (1000")	13.462	21.539	14.36	16.97
27.94 (1100")	14.808	23.693	15.80	18.68
30.48 (1200")	16.154	25.847	17.25	20.38
33.02 (1300")	17.501	28.001	18.69	22.09
35.56 (1400")	18.847	30.155	20.14	23.79
38.10 (1500")	20.193	32.309	21.58	25.50

(Unit / Unités / 単位 : m)

When the screen aspect ratio is 16:9 (Throw ratio: [0.585 - 0.693:1]) Lorsque le rapport d'aspect de l'écran est 16:9 (Rapport de projection : [0.585 - 0.693:1]) アスペクト比 16:9 (スローレシオ : [0.585 - 0.693:1])				
SD	SH	SW	LW	LT
2.54 (100")	1.245	2.214	1.25	1.49
3.05 (120")	1.494	2.657	1.52	1.81
3.81 (150")	1.868	3.321	1.92	2.28
5.08 (200")	2.491	4.428	2.59	3.07
6.35 (250")	3.113	5.535	3.26	3.86
7.62 (300")	3.736	6.641	3.93	4.65
8.89 (350")	4.358	7.748	4.59	5.44
10.16 (400")	4.981	8.855	5.26	6.23
12.70 (500")	6.226	11.069	6.60	7.81
15.24 (600")	7.472	13.283	7.93	9.38
17.78 (700")	8.717	15.497	9.27	10.96
20.32 (800")	9.962	17.710	10.60	12.54
22.86 (900")	11.207	19.924	11.94	14.12
25.40 (1000")	12.453	22.138	13.28	15.69
27.94 (1100")	13.698	24.352	14.61	17.27
30.48 (1200")	14.943	26.566	15.95	18.85
33.02 (1300")	16.188	28.779	17.28	20.43
35.56 (1400")	17.434	30.993	18.62	22.00
38.10 (1500")	18.679	33.207	19.96	23.58

Appendix / Annexe / 付録 (continued / suite / つづき)

(Unit / Unités / 単位 : m)

When the screen aspect ratio is 4:3 (Throw ratio: [0.785 - 0.929:1])

Lorsque le rapport d'aspect de l'écran est 4:3 (Rapport de projection : [0.785 - 0.929:1])

アスペクト比 4:3 (スローレシオ : [0.785 - 0.929:1])

SD	SH	SW	LW	LT
2.54 (100")	1.524	2.032	1.55	1.85
3.05 (120")	1.829	2.438	1.88	2.23
3.81 (150")	2.286	3.048	2.37	2.81
5.08 (200")	3.048	4.064	3.19	3.78
6.35 (250")	3.810	5.080	4.01	4.74
7.62 (300")	4.572	6.096	4.82	5.71
8.89 (350")	5.334	7.112	5.64	6.67
10.16 (400")	6.096	8.128	6.46	7.64
12.70 (500")	7.620	10.160	8.09	9.57
15.24 (600")	9.144	12.192	9.73	11.50
17.78 (700")	10.668	14.224	11.36	13.43
20.32 (800")	12.192	16.256	13.00	15.36
22.86 (900")	13.716	18.288	14.63	17.29
25.40 (1000")	15.240	20.320	16.27	19.22
27.94 (1100")	16.764	22.352	17.90	21.16
30.48 (1200")	18.288	24.384	19.54	23.09
33.02 (1300")	19.812	26.416	21.17	25.02
35.56 (1400")	21.336	28.448	22.81	26.95
38.10 (1500")	22.860	30.480	24.44	28.88

Note

- A ± 5 % error in listed projection distances may occur.
In addition, when [KEYSTONE] is used, distance is corrected to become smaller than the specified screen size.
- The throw ratio is based on the value during projection with the projected image size of 5.08 m (200").
- The periods used in the numbers in the tables are decimal points.

Remarque

- Une erreur de ± 5 % dans des distances de projection énumérées peut se produire.
En outre, lorsque [CORRECTION DE TRAPÈZE] est utilisé, la distance est corrigée pour devenir inférieure à la taille d'écran spécifiée.
- Le rapport de projection est basé sur la valeur en cours de projection avec une taille de l'image projetée de 5,08 m (200").
- Les points utilisés dans les nombres dans les tableaux sont des points décimaux.

お知らせ

- 記載の投写距離は $\pm 5\%$ 以下の範囲内で誤差が発生します。
また、[台形補正] 使用時は、所定の画面サイズよりも小さくなる方向で補正されます。
- スローレシオは、投写画面サイズ 200 型投写時の値を基準にしています。

Setting-up dimensions which are not given in the above table can be calculated using the formulas below. Check the projected image size SD (m) and use the following formula to determine projection distance (L).

La configuration des dimensions qui ne sont pas données dans le tableau ci-dessus peut être calculée à l'aide des formules suivantes. Vérifiez la taille de l'image projetée SD (m) et utilisez la formule suivante pour déterminer la distance de projection (L).

上記の表以外の投写寸法は次の計算式で求めることができます。画面对角サイズ SD (m) をご確認のうえ、それぞれの計算式で投写距離 (L) を求めてください。

Appendix / Annexe / 付録 (continued / suite / つづき)

- Projection distance formulas
- Formules de distance de projection
- 投写距離計算式

The dimensions of the following table contain a slight error.

Periods are used to represent decimal points in the calculation formulas in the following table.

Les dimensions du tableau suivant peuvent présenter un léger écart.

Les points sont utilisés pour indiquer les décimales dans les formules de calcul dans le tableau suivant.

次の表内の寸法は若干の誤差があります。

(Unit / Unités / 単位 : m)

	L	
	LW	LT
When the screen aspect ratio is 17:9 Lorsque le rapport d'aspect de l'écran est 17:9 画面アスペクト比 17:9 のとき	$=0.5004 \times SD - 0.0820$	$=0.5909 \times SD - 0.0827$
When the screen aspect ratio is 16:10 Lorsque le rapport d'aspect de l'écran est 16:10 画面アスペクト比 16:10 のとき	$=0.5686 \times SD - 0.0820$	$=0.6714 \times SD - 0.0827$
When the screen aspect ratio is 16:9 Lorsque le rapport d'aspect de l'écran est 16:9 画面アスペクト比 16:9 のとき	$=0.5259 \times SD - 0.0820$	$=0.6211 \times SD - 0.0827$
When the screen aspect ratio is 4:3 Lorsque le rapport d'aspect de l'écran est 4:3 画面アスペクト比 4:3 のとき	$=0.6437 \times SD - 0.0820$	$=0.7601 \times SD - 0.0827$

Panasonic Projector & Display Corporation

Web Site : <https://docs.connect.panasonic.com/projector>

Panasonic Projector & Display Americas LLC

Two Riverfront Plaza, Newark, NJ 07102

TEL: +1-201-348-7000

パナソニック プロジェクター & ディスプレイ株式会社

〒 571-8503 大阪府門真市松葉町 2 番 15 号 電話 ☎ 0120-872-601