

Professional Displays

Standard

SQ2H

4K intel

*Actual Resolution: 3840 x 2160p

• DisplayPort(Ver. 1.2)

*1: Some functions are limited.

A G *only applies for 43-65"

TH-98SQ2H	700cd/m ²	24/7 operation	4K Media Player	Portrait
TH-86SQ2H	700cd/m ²	24/7 operation	4K Media Player	Portrait
TH-75SQ2H	700cd/m ²	24/7 operation	4K Media Player	Portrait
TH-65SQ2H	700cd/m ²	24/7 operation	4K Media Player	Portrait
TH-55SQ2H	700cd/m ²	24/7 operation	4K Media Player	Portrait
TH-50SQ2H	700cd/m ²	24/7 operation	4K Media Player	Portrait
TH-43SQ2H	700cd/m ²	24/7 operation	4K Media Player	Portrait

SQE2

4K intel

*Actual Resolution: 3840 x 2160p

• DisplayPort(Ver. 1.2)

*1: Some functions are limited.

A G *only applies for 43-65"

TH-98SQE2	500cd/m ²	24/7 operation	4K Media Player	Portrait
TH-86SQE2	500cd/m ²	24/7 operation	4K Media Player	Portrait
TH-75SQE2	500cd/m ²	24/7 operation	4K Media Player	Portrait
TH-65SQE2	500cd/m ²	24/7 operation	4K Media Player	Portrait
TH-55SQE2	500cd/m ²	24/7 operation	4K Media Player	Portrait
TH-50SQE2	500cd/m ²	24/7 operation	4K Media Player	Portrait
TH-43SQE2	500cd/m ²	24/7 operation	4K Media Player	Portrait

Entry

CQE2

4K

*Actual Resolution: 3840 x 2160p

A G *only applies for 43-65"

TH-98CQE2	500cd/m ²	24/7 operation	4K Media Player	Portrait
TH-86CQE2	400cd/m ²	16h operation	4K Media Player	Portrait
TH-75CQE2	400cd/m ²	16h operation	4K Media Player	Portrait
TH-65CQE2	500cd/m ²	16h operation	4K Media Player	Portrait
TH-55CQE2	500cd/m ²	16h operation	4K Media Player	Portrait
TH-50CQE2	500cd/m ²	16h operation	4K Media Player	Portrait
TH-43CQE2	500cd/m ²	16h operation	4K Media Player	Portrait

Multi-Touch Screen

CQE2-IR

4K Multi Touch

*Actual Resolution: 3840 x 2160p

TH-86CQE2-IR	400cd/m ²	16h operation	4K Media Player	Portrait
TH-75CQE2-IR	400cd/m ²	16h operation	4K Media Player	Portrait
TH-65CQE2-IR	500cd/m ²	16h operation	4K Media Player	Portrait
TH-55CQE2-IR	500cd/m ²	16h operation	4K Media Player	Portrait

LED

AD

LED


*Specifications subject to confirmation

TL-165AD19A*	700cd/m ²	24/7 operation	intel	Portrait
TL-137AD15A	700cd/m ²	24/7 operation	intel	Portrait
TL-110AD12A	700cd/m ²	24/7 operation	intel	Portrait

Pict Descriptions

4K display (Actual resolution: 3840 x 2160p)	Capable of 24-hour continuous operation	Capable of 16-hour continuous operation
USB media player supporting 4K images	Portrait installation possible	Intel® SDM specification compatible slot

Model Number Legend



Pitch for wall hanging is VESA compliant
NOTE: The availability varies depending on model.
The specifications are subject to change without notice.



For more information about Panasonic Professional Displays, please visit Display Global Website:
<https://eu.connect.panasonic.com/gb/en/professional-displays>

Wireless Presentation System

PressIT WPS2 Series NEW



- 1 Receiver (Box) TY-WPR2
- 2 Receiver (Board) TY-SB01WP
- 3 Transmitter (HDMI™/USB-A) TY-WPB2
- 4 Transmitter (USB-C) TY-WPBC2
- 5 Transmitter case

Note: The transmitter and receiver are also available separately.

Basic set		Transmitter	
TY-WPS2	TY-WPSC2	TY-WPB2	TY-WPBC2
1	1	3	4
3 X 2	4 X 2	1	1
5	5		

360 Degree Camera Speakerphone




PressIT360

Equipped with various video modes




TY-CSP1



Dual View



Single View



Multi View



Surround View



Stable View



TY-SBPure SDM

PressIT

Plug & Play Wireless Presentation System

Dongle based wireless presentation system for fast and simple screen sharing

Lineup



	Basic Set		Receiver (Box)	Receiver (Board)	Transmitter (HDMI™/USB-A)	Transmitter (USB-C)
Model	TY-WPS2	TY-WPSC2	TY-WPR2	TY-SB01WP	TY-WPB2	TY-WPBC2
Applicable product	Flat Panel Display /Projector (Panasonic and others)			*Attachable to a display compatible with Intel® SDM specification slot.	PC/Tablet/Smartphone	
What's included?	<ol style="list-style-type: none"> Receiver (Box) x1 Transmitter (HDMI™/USB-A) x2 Transmitter case x1 	<ol style="list-style-type: none"> Receiver (Box) x1 Transmitter (USB-C) x2 Transmitter case x1 	<ol style="list-style-type: none"> Receiver (Box) x1 	<ol style="list-style-type: none"> Receiver x1 <p>*Supports only communication in the 5GHz band.</p>	<ol style="list-style-type: none"> Transmitter (HDMI™/USB-A) x1 	<ol style="list-style-type: none"> Transmitter (USB-C) x1

Connects to mobile devices <small>Genuine Digital AV adaptor by Apple is required.</small>	6GHz Wireless LAN adopted	Presents 4 screens in Full HD [supports 4K]	24 channels available
4K UHD video <small>max. resolution: 3840 x 2160 pixels, 30p transmission</small>	Low latency image	Connects up to 32 transmitters at once	Lock mode prevents interrupts
HDMI™-CEC command compatible	Supports audio transmission	Share screen without transmitter ¹	Shared Supports "Multicast" without a router

¹ Firmware update is required. For details, please contact your dealer

PressIT360

Providing a more realistic meeting with the 360-degree camera speakerphone



- High-quality images from a high-performance 360-degree camera**
Four high-performance cameras provide 360-degree immersive images.
- 360-degree orientation microphone and speaker**
Covers a 360-degree radius up to 5m/16.4ft for clear sound collection.
- Easy to carry and operate meeting**
Video and audio data can be sent to your PC with a single USB-C. Diameter 64 mm, height 285 mm, weight approx. 950 g.