

Large-Venue

### 3-Chip DLP™ Laser light source models

Lens not included with 3-Chip DLP™ models.



PT-RQ50K	50,000 lm 51,000 lm (Center)	Native 4K	4K	4K	intel
----------	---------------------------------	-----------	----	----	-------

Available from CY2026 Q2<sup>4</sup>



PT-RQ45K	42,000 lm* 43,600 lm* (Center)	4K	4K	4K	intel
----------	-----------------------------------	----	----	----	-------



PT-RZ44K	42,000 lm* 43,600 lm* (Center)	WUXGA	4K	4K	intel
----------	-----------------------------------	-------	----	----	-------

\*Brightness is tentative.

NEW



PT-RQ35K2	30,500 lm 32,000 lm (Center)	4K	4K	4K	intel
-----------	---------------------------------	----	----	----	-------



PT-RZ34K2	30,500 lm 32,000 lm (Center)	WUXGA	4K	4K	intel
-----------	---------------------------------	-------	----	----	-------



PT-RQ25K	20,000 lm 21,000 lm (Center)	4K	4K	4K	intel
----------	---------------------------------	----	----	----	-------



PT-RZ24K	20,000 lm 21,000 lm (Center)	WUXGA	4K	4K	intel
----------	---------------------------------	-------	----	----	-------



PT-RQ18K	16,000 lm 16,800 lm (Center)	4K	4K	4K	intel
----------	---------------------------------	----	----	----	-------



PT-RZ17K	16,000 lm 16,800 lm (Center)	WUXGA	4K	4K	intel
----------	---------------------------------	-------	----	----	-------

### 1-Chip DLP™ Laser light source models

Lens not included with 'L' models.



PT-HTQ20/L	20,000 lm* 20,400 lm* (Center)	4K	4K	4K	intel
------------	-----------------------------------	----	----	----	-------

\*Brightness is tentative.



Installation

### 1-Chip DLP™ Laser light source models

Lens not included with 'L' models.



PT-REQ15/L	15,000 lm 15,500 lm (Center)	4K	4K	4K	intel
------------	---------------------------------	----	----	----	-------



PT-REQ12/L	12,000 lm 12,400 lm (Center)	4K	4K	4K	intel
------------	---------------------------------	----	----	----	-------



PT-REQ10/L	10,000 lm 10,300 lm (Center)	4K	4K	4K	intel
------------	---------------------------------	----	----	----	-------



PT-REQ80/L	8,000 lm 8,200 lm (Center)	4K	4K	4K	intel
------------	-------------------------------	----	----	----	-------



PT-REZ15/L	15,000 lm 15,500 lm (Center)	WUXGA	4K	4K	intel
------------	---------------------------------	-------	----	----	-------



PT-REZ12/L	12,000 lm 12,400 lm (Center)	WUXGA	4K	4K	intel
------------	---------------------------------	-------	----	----	-------



PT-REZ10/L	10,000 lm 10,300 lm (Center)	WUXGA	4K	4K	intel
------------	---------------------------------	-------	----	----	-------



PT-REZ80/L	8,000 lm 8,200 lm (Center)	WUXGA	4K	4K	intel
------------	-------------------------------	-------	----	----	-------

Installation

### 1-Chip DLP™ Laser light source models

Lens not included with 'L' models.



PT-RQ7L	7,500 lm 7,700 lm (Center)	4K	4K	4K	intel
---------	-------------------------------	----	----	----	-------



PT-RQ6L	6,500 lm 6,700 lm (Center)	4K	4K	4K	intel
---------	-------------------------------	----	----	----	-------



PT-RZ7L	7,500 lm 7,700 lm (Center)	WUXGA	4K	4K	intel
---------	-------------------------------	-------	----	----	-------



PT-RZ6L	6,500 lm 6,700 lm (Center)	WUXGA	4K	4K	intel
---------	-------------------------------	-------	----	----	-------

### 1-Chip DLP™ Laser light source models (Lens fixed)



PT-FRQ60	6,000 lm 6,200 lm (Center)	4K	4K	4K	intel
----------	-------------------------------	----	----	----	-------



PT-FRQ50	5,200 lm 5,400 lm (Center)	4K	4K	4K	intel
----------	-------------------------------	----	----	----	-------



PT-FRZ60	6,000 lm 6,200 lm (Center)	WUXGA	4K	4K	intel
----------	-------------------------------	-------	----	----	-------



PT-FRZ50	5,200 lm 5,400 lm (Center)	WUXGA	4K	4K	intel
----------	-------------------------------	-------	----	----	-------



PT-FRZ55	5,000 lm 5,200 lm (Center)	WUXGA	4K	4K	intel
----------	-------------------------------	-------	----	----	-------

### LCD Laser light source models



Lens not included with 'L' models.



PT-MZ20KL	20,000 lm	WUXGA	4K	4K	intel
-----------	-----------	-------	----	----	-------



PT-MZ17KL	16,500 lm	WUXGA	4K	4K	intel
-----------	-----------	-------	----	----	-------



PT-MZ14KL	14,000 lm	WUXGA	4K	4K	intel
-----------	-----------	-------	----	----	-------




PT-MZ11KL	11,000 lm	WUXGA	4K	4K	intel
-----------	-----------	-------	----	----	-------



PT-MZ882/L	8,200 lm	WUXGA	4K	4K	intel
------------	----------	-------	----	----	-------



PT-MZ782/L	7,500 lm	WUXGA	4K	4K	intel
------------	----------	-------	----	----	-------



PT-MZ682/L	6,500 lm	WUXGA	4K	4K	intel
------------	----------	-------	----	----	-------

- Resolution 4096 x 2160 Pixels.
- Resolution 3840 x 2400 Pixels (Quad Pixel Drive: ON).
- Only when the optional TY-SB01DL DIGITAL LINK Terminal Board is loaded.
- Product availability varies by country or region.
- Resolution 3840 x 2160 Pixels (Quad Pixel Drive: ON).
- HDMI/DIGITAL LINK input only.
- Resolution 3840 x 2400 Pixels (achieved with 2-axis pixel-shifting technology)
- HDMI/DIGITAL LINK input only. Supports signals up to 4K/30p.
- To operate wireless projection, the optional Wireless Module AJ-WM50 is required.
- HDMI input only. Supports signals up to 4K/30p.

★: Available in black/white cabinet.  
 ⚡: The projector is able to emulate the same control commands of most previous Panasonic projectors when it is replacing.

Portable

Short Throw

Ultra Short Throw

Peripheral

### LCD Laser light source models (Lens fixed)



Available from CY2026 Q2<sup>4</sup>



PT-VMQ85	8,000 lm	4K	4K	4K	intel
----------	----------	----	----	----	-------



PT-VMQ75	7,300 lm	4K	4K	4K	intel
----------	----------	----	----	----	-------



PT-VMQ65	6,500 lm	4K	4K	4K	intel
----------	----------	----	----	----	-------



PT-VMZ82	8,000 lm	WUXGA	4K	4K	intel
----------	----------	-------	----	----	-------



PT-VMZ72	7,300 lm	WUXGA	4K	4K	intel
----------	----------	-------	----	----	-------



PT-VMZ62	6,500 lm	WUXGA	4K	4K	intel
----------	----------	-------	----	----	-------



PT-VMZ51	5,200 lm	WUXGA	4K	4K	intel
----------	----------	-------	----	----	-------



PT-VMZ51S	5,200 lm	WUXGA	4K	4K	intel
-----------	----------	-------	----	----	-------



PT-LMZ460	4,600 lm	WUXGA	4K	4K	intel
-----------	----------	-------	----	----	-------



PT-LMZ420	4,200 lm	WUXGA	4K	4K	intel
-----------	----------	-------	----	----	-------

### LCD Laser light source models (Lens fixed)



PT-VMZ75T	7,000 lm	WUXGA	4K	4K	intel
-----------	----------	-------	----	----	-------



PT-VMZ65T	6,200 lm	WUXGA	4K	4K	intel
-----------	----------	-------	----	----	-------

### LCD Laser light source models (Lens fixed)



PT-CMZ50	5,200 lm	WUXGA	4K	4K	intel
----------	----------	-------	----	----	-------

### Media Processor



ET-FMP50	ET-SBFMP10	Function board type
ET-FMP20		

Note: [L] Lens-less model. The specifications are subject to change without notice.  
 Regarding light output, measurement, measuring conditions, and the method of notation all comply with ISO/IEC 21118:2020 international standards. The results of brightness measurements that comply with ISO/IEC 21118:2020 and ANSI will be the same. Regarding center lumens, luminance is measured at the center of the screen.

For more information, please visit the website >>>

