



BT-LH1710

BT-LH1710

17 Type LCD HD/SD Monitor



BT-LH1710

<https://eu.connect.panasonic.com/sk/en/products/broadcast-proav/bt-lh1710>

Power Requirement	AC 100 V to 240 V 50/60 Hz, 0.6 A to 0.3 A
Dimensions (W x H x D)	430 mm x 323.5 mm x 198mm (16-15/16 inches x 12-3/4 inches x 7-13/16 inches, Including stand)
Weight	7.1 kg (15.7 lbs) (Including stand)
Operating Temperature	5°C to 35°C (41°F to 95°F)
Operating Humidity	20 % to 80 % (non dew)
Storage Temperature	-20°C to 60°C (Ñ4°F to 140°F)
Panel Size	431.8 mm (17 inches)
Aspect Ratio	15:09
Double Speed Drive (100Hz/120Hz)	-
Resolution	1,280 x 768 pixels (WUXGA)
Display Colors	Approx. 16,770,000 colors
Viewing Angle	178; both of horizontal and vertical (contrast >10:1)
Video Input/Output	Video: BNC x 2, (with through-out connector x 1)
Audio Input	Pinjack x 2 (stereo)
Headphone Output	M3 stereo mini jack x 1
Remote	GPI: D-SUB, 9 pin RS-232C: D-SUB, 9 pin
External DC Power Input	XLR, 4pin
Video	SYNC signal level: 0.3 Vp-p to 4.0 Vp-p
Audio	Audio input signal level: 0.5 Vrms
SDI Embedded Audio	HD-SDI : SMPTE299M standard, 48 kHz, 8CH synchronous/asynchronous
Supplied Accessories	Power cord, power cord hook, screw
Option	Rack mount adaptor, Wall Mount Adaptor,