



## High Performance LCD Monitor

# BT-LH1850

Powerful 469.9 mm (18.5 inches) LCD monitor developed for field and studio applications. High-Quality Images, Advanced Functions, Low Power Consumption and Excellent Cost-Performance. A 47 cm (18.5 inches) LCD Monitor for Diverse Broadcasting Needs.

### Key Features

---

High performance, low cost monitor

---

3D LUT for accurate colours

---

Versatile connectivity



## BT-LH1850

<https://eu.connect.panasonic.com/sk/en/products/broadcast-proav/bt-lh1850>

<b>General</b>	
<b>Power Requirement</b>	AC 100 V to 240 V, 50 Hz/60 Hz, 0.3 A to 0.15 A DC 12 V (11 V to 17 V), 1.8 A
<b>Dimensions (W x H x D)</b>	479 mm x 390.7 mm x 240 mm (including stand) (18-7/8 inches x 15-3/8 inches x 9-7/16 inches) 479 mm x 339 mm x 76.5 mm (unit only, not including stand) (18-7/8 inches x 13-3/8 inches x 3 inches)
<b>Weight</b>	Approx. 7.0 kg (15.43 lb) (including stand) Approx. 5.6 kg (12.35 lb) (unit only, not including stand)
<b>Operating Temperature</b>	5 °C to 35 °C (41 °F to 95 °F)
<b>Operating Humidity</b>	20 % to 80 % (no condensation)
<b>Storage Temperature</b>	-20 °C to 60 °C (-4 °F to 140 °F)
<b>LCD Panel</b>	
<b>Panel Size</b>	470 mm (18.5 inches)
<b>Aspect Ratio</b>	16:9
<b>Resolution</b>	1,366 pixels x 768 pixels (WXGA)
<b>Display Colors</b>	Approx. 16,770,000 colors
<b>Viewing Angle</b>	170° horizontal, 160° vertical (contrast > 10:1)
<b>Video Input</b>	Video: BNC x 1 SDI: BNC x 2, SMPTE274M/296M/259M-C/ITU-R BT.656-4 compliant, embedded audio supported, HD SDI: SMPTE299M compliant, 48 kHz, 8 CH, synchronous supported, SD SDI: SMPTE272M compliant, 48 kHz, 4 CH, synchronous supported, HDMI: HDMI x 1 (TypeA), HDCP supported, embedded audio supported, VIERA Link not supported DVI-I: DVI-I x 1, HDCP supported, TMDS single link
<b>Video Output</b>	Video: BNC x 1, through-out (75 Ω auto) SDI: BNC x 1, switched-out
<b>Audio Input</b>	Pinjack x 2 (stereo)
<b>Headphone Output</b>	M3 stereo mini jack x 1
<b>Remote</b>	GPI: D-SUB, 9 pin RS-232C: D-SUB, 9 pin RS-485: RJ-45 x 2 (input, output)
<b>External DC Power Input</b>	XLR, 4 pin
<b>Signal Level</b>	
<b>Video</b>	HD/VD Signal level: TTL level
<b>Audio</b>	Audio input signal level: 0.31 Vrms Speaker output: 0.5 W, Monaural Head phone output: 32 Ω, Variable Level
<b>Others</b>	Power cord, Tilt stand, Tilt stand screw, Protective panel screw
<b>Optional Accessories</b>	Wall mount adaptor