



Laser 1-Chip DLP, 6200 lumens (centre), WUXGA, 360 degrees free installation, long lasting laser engine

PT-RZ660

6,200 lumens Solid Shine laser projector Designed for intensive usage and long lasting brightness in education, museums, exhibitions and digital signage applications

Key Features

Laser 1-Chip DLP, 6200 lumens (centre), WUXGA

High brightness and excellent image quality with laser light source

Maintenance free up to 20,000 hours with dust-resistant optical block and long lasting laser engine

Free 360 degrees installation and Geometric Manager Pro function

10,000:1 contrast ratio





PT-RZ660

<https://eu.connect.panasonic.com/tr/en/products/projectors/pt-rz660>

Power Supply	AC100 - 240V 7.1A 50Hz/60Hz
Power Consumption	700W NORMAL: 499W ECO: 428W LONG LIFE1: 287 - 402W LONG LIFE 2: 262 - 402W LONG LIFE 3: 238 - 402W SHUTTER: 69W STANDBY MODE [ECO]*1: 10.2W STANDBY MODE [NORMAL]: 3W STANDBY MODE (When the [QUICK STARTUP] function is enabled): Approx. 85 W *Operating Temperature: 25 °C (77 °F), Altitude: 700m (2,297 ft), ICE62087: 2008 Broadcast contents, Picture mode: Standard, Dynamic Contrast2
BTU Value	Max 2389BTU
DLP™ Chip Panel Size	17.0 mm (0.67 in) diagonal (16:10 aspect ratio)
DLP™ Chip Display Method	DLP™ chip x 1, DLP™ system
DLP™ Chip Pixels	2,304,000 (1920 x 1200) x 3, total of 6,912,000 pixels
Lens PT-RZ660B/W	Powered zoom/focus lenses (1.7-2.4:1), F 1.7-1.9, f 25.6-35.7 mm
Lens PT-RZ660LB/LW	Optional powered zoom/focus lenses and xed-focus lens
Light Source	Laser Diode Laser class 1(Class3R for US models) Luminance life for set: 20,000 hours at half luminance (normal)/ 24,000 hours at half luminance (Eco) * Temperature: 30°C (86°F), Altitude 700m (2,297 ft), Dust: 0.15mg/m3 Dynamic Contrast3 43,800 hours at constant luminance (LONG LIFE1) 61,320 hours at constant luminance (LONG LIFE2) 87,600 hours at constant luminance (LONG LIFE3)
Screen Size	1.27- 15.24 m (50-600 inches) (16:10 aspect ratio) *1.27 - 5.08 m (50 - 200 inches) with the ET-DLE055 (16:10 aspect ratio) *2.54 - 7.62 m (100 - 350 inches) with the ET-DLE030 (16:10 aspect ratio)
Brightness*3	6,200 lumens (Center)*2/ 6,000 lumens*3 6,000 lumens (Half luminance) (NORMAL) 4,800 lumens (Half luminance) (ECO) 2,400 lumens (Constant luminance) (LONG LIFE1) 2,000 lumens (Constant luminance) (LONG LIFE2) 1,600 lumens (Constant luminance) (LONG LIFE3)
Center-to-Corner Uniformity*3	90%
Contrast*3	10,000:1 (All White/All Black) (Dynamic Contrast3)
Resolution	WUXGA 1,920 x 1,200 pixels (Input signals that exceed this resolution will be converted to 1,920 x 1,200 pixels.)
Scanning Frequency SDI	3G-SDI signal (RGB 4:4:4 12-bit/10-bit): SMPTE ST 424 compliant: 1125(1080)/60i, 1125(1080)/50i, 1125(1080)/25p, 1125(1080)/24p, 1125(1080)/24sF, 1125(1080)/30p, [2K/24p], [2K/25p], [2K/30p] 3G-SDI signal (YPBPR4:2:2 10-bit): SMPTE ST 424 compliant: 1125(1080)/60p, 1125(1080)/50p, [2K/48p], [2K/50p], [2K/60p] HD-SDI signal (YPBPR4:2:2 10-bit): SMPTE ST 292 compliant: 750(720)/60p, 750(720)/50p, 1125(1080)/60i, 1125(1080)/50i, 1125(1080)/25p, 1125(1080)/24p, 1125(1080)/24sF, 1125(1080)/30p SD-SDI signal (YCBCR4:2:2 10-bit): SMPTE ST 259 compliant: 525i(480i), 625i(576i)

Scanning Frequency HDMI/DVI-D	fH: 15- 100kHz, fV: 24 - 120Hz, dot clock: 25 - 162 MHz 525i (480i)*4, 625i (576i)*4, 525p (480p), 625p (576p), 750 (720)/60p, 750 (720)/50p, 1125 (1080)/60i, 1125 (1080)/50i, 1125 (1080)/25p, 1125 (1080)/24p, 1125 (1080)/24sF, 1125 (1080)/30p, 1125 (1080)/60p, 1125 (1080)/50p, VGA (640 x 480) - WUXGA (1920 x 1200) compatible with non-interlaced signals only
Scanning Frequency RGB	fH: 15- 100kHz, fV: 24 - 120Hz, dot clock: 20 - 162 MHz
Scanning Frequency YPBPR (YCBCR)	525i (480i): fH 15.73 kHz; fV 59.9 Hz, 625i (576i): fH 15.63 kHz; fV 59.9 Hz, 525p (480p): fH 31.50 kHz; fV 60 Hz, 625p (576p): fH 31.25 kHz; fV 50 Hz, 750 (720)/60p: fH 45.00 kHz; fV 60 Hz, 750 (720)/50p: fH 37.50 kHz; fV 50 Hz, 1125 (1080)/60i: fH 33.75 kHz; fV 60 Hz, 1125 (1080)/50i: fH 28.13 kHz; fV 50 Hz, 1125 (1080)/25p: fH 28.13 kHz; fV 25 Hz, 1125 (1080)/24p: fH 27.00 kHz; fV 24 Hz, 1125 (1080)/24sF: fH 27.00 kHz; fV 48 Hz, 1125 (1080)/30p: fH 33.75 kHz; fV 30 Hz, 1125 (1080)/60p: fH 67.50 kHz; fV 60 Hz, 1125 (1080)/50p: fH 56.25 kHz; fV 50 Hz
Scanning Frequency Video/S-Video	fH: 15.73 kHz, fV: 59.9 Hz [NTSC/NTSC4.43/PAL-M/PAL60] fH: 15.63 kHz, fV: 50 Hz [PAL/PAL-N/SECAM]
Optical Axis Shift	Vertical: +50%, -16%(powered), Horizontal: +30%, -10% (When using the ET-DLE085/ET-DLE105, +28%, -10%) (powered) NOTE: Optical axis shift function cannot be operated when used with the ET-DLE055. If using the ET-DLE030, the optical axis is fixed.
Installation	Ceiling/floor, front/rear, 360 degree free installation
Terminals SDI In	BNC x 1, 3G-SDI signal: SMPTE ST 424 compliant HD-SDI signal: SMPTE ST 292 compliant SD-SDI signal: SMPTE ST 259 compliant
Terminals HDMI In	HDMI 19-pin x 1, Deep Color, compatible with HDCP
Terminals DVI-D In	DVI-D 24-pin x 1, DVI 1.0 compliant, compatible with HDCP, for single link only
Terminals RGB 1 In	BNC x 5
Terminals RGB 1 In R, G, B	R: 0.7 Vp-p, 75 ohms, G: 0.7 Vp-p (G: 1.0 Vp-p for sync on G), 75 ohms, B: 0.7 Vp-p, 75 ohms HD, VD/SYNC: TTL, high impedance, positive/negative automatic
Terminals RGB 1 In Y, PB, PR (Y, CB, CR)	Y: 1.0 Vp-p (including sync signal), PB/PR (CB/CR): 0.7 Vp-p, 75 ohms
Terminals RGB 1 In Y/C	Y: 1.0 Vp-p, C: 0.286 Vp-p, 75 ohms
Terminals RGB 1 In Video	1.0Vp-p, 75 ohms
Terminals RGB 2 In	D-sub HD 15-pin (female) x 1
Terminals RGB 2 In R, G, B	R: 0.7 Vp-p, 75 ohms, G: 0.7 Vp-p (G: 1.0 Vp-p for sync on G), 75 ohms, B: 0.7 Vp-p, 75 ohms HD, VD/SYNC: TTL, high impedance, positive/negative automatic
Terminals RGB 2 In Y, PB, PR (Y, CB, CR)	Y: 1.0 Vp-p (including sync signal), PB/PR (CB/CR): 0.7 Vp-p, 75 ohms
Terminals Serial/Multi Projector Sync In	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
Terminals Serial/Multi Projector Sync Out	D-sub 9-pin (male) x 1 for link control
Terminals Remoter 1 In	M3 jack x 1 for wired remote control
Terminals Remoter 1 Out	M3 jack x 1 for link control (for wired remote control)
Terminals Remoter 2 In	D-sub 9-pin (female) x1 for external control (parallel)
Terminals LAN/DIGITAL LINK	RJ-45 x 1 for network and DIGITAL LINK (video/network/serial control) connection, 100Base-TX, compliant with PLink™(Class 1) Deep Color, HDCP
Power Cord Length	3.0 m (9 ft 10 in)
Cabinet Materials	Molded plastic
Dimensions (W x H x D) PT-RZ660B/RZ660W	498 x 200*5 x 581 mm (19-19/32 x 7-7/8*5 x 22-7/8in) with supplied lens
Dimensions (W x H x D) PT-RZ660LB/RZ660LW	498 x 200*5 x 538 mm (19-19/32 x 7-7/8*5 x 21-3/16in) without lens
Weight PT-RZ660B/RZ660W	Approx. 23.1 kg (50.9lbs) with supplied lens

Weight PT-RZ660LB/RZ660LW	Approx. 22.3kg (49.2lbs) without lens
Operation Noise	35 dB
Operating Temperature	0-45 °C (32-113 °F) * 6
Operating Humidity	10%-80% (no condensation)
Note	<p>*1 When the STANDBY MODE is set to Eco, network functions such as power on over the LAN will not operate.</p> <p>*2 The value of the light output at the center region of the projected image is extracted based on the light output measurement method defined by the ISO/IEC 21118:2012 international standards.</p> <p>*3 Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards.</p> <p>*4 Only compatible with dot clock frequency of 27 MHz (pixel repetition signal).</p> <p>*5 with legs at shortest position.</p> <p>*6 Limits the luminance when used in locations from 0m to 2,700m (0ft to 8858ft) above sea level at ambient temperatures of 35°C (95°F) or higher, or from 2,700m to 4,200m (8,858ft to 13,780ft) above sea level at ambient temperatures of 25°C (77°F) or higher.</p>
Technology	1-Chip DLP Laser
Brightness	6,200 lumens (Center)/ 6,000 lumens