



High cost-to-performance display for professional users seeking a 4K video wall solution. 55" frameless D-LED LCD, 500 cd/m², 3.5 mm bezel to bezel, 24/7 operation, portrait mode, anti-glare surface and robust display

TH-55LFV8

Highly reliable frameless video wall display. High cost-to-performance display for professional users seeking a 4K video wall solution.

Key Features

55", 500 cd/m², 3,5 mm bezel to bezel, anti-glare surface

DisplayPort UHD daisy chain functionality

A super narrow frame for optimal multi-screen layouts

Ideal for installation in standard indoor places, wide colour viewing angle and high visibility





TH-55LFV8

<https://eu.connect.panasonic.com/tr/en/products/professional-displays/th-55lfv8>

Screen Size	55-inch (1387 mm)
Panel Type	LCD IPS Panel/D-LED
Aspect Ratio	16:9
Effective Display Area (W x H)	1209 x 680 mm(47.6" x 26.8")
Number of Pixels (H x V)	1920 x 1080 pixels
Brightness	500 cd/m2
Contrast Ratio	1400:1
Response Time	12 ms(G to G)
Viewing Angle	178°/178°(CR \geq 10)
Panel Surface Treatment	Anti-Glare treatment (Haze 10%)
Power Requirements	110-240 V AC, 50/60 Hz
Power Consumption	320 W
Standby Condition	Approx. 0.5 W
Dimensions (W x H x D)	1213.4 x 684.2 x 95 mm(47.8" x 26.9" x 3.7")
Bezel Width	L/T:2.25 mm(0.088"),R/B:1.25 mm(0.049")
Weight	Approx. 30.0 kg (66.1lbs)
Wall-Hanging Pitch	VESA compliant 400 x 400 mm(15.8" x 15.8")