



Indoor Pan-Tilt Head

AW-PH400

High performance indoor pan-tilt head

Key Features

Pan range:400°, Tilt range:300°

Memory of last position

Maximum load:Approx. 8 kg



AW-PH400

<https://eu.connect.panasonic.com/tr/en/products/broadcast-proav/aw-ph400>

Power Supply/Power Consumption	AC 120 V (60 Hz), AC 220 to 240 V (50/60 Hz) / 145 W
Weight	Approx. 10.2 kg (Approx. 22.5 lb)
Dimensions (W x H x D) (Pan-Tilt Head only, Excluding Protrusions)	315 mm x 534 mm x 188 mm (12-3/8 inches x 21 inches x 7-3/8 inches)
Maximum Load (Including with a Camera, a Lens and a Teleprompter)	Approx. 8 kg (Approx. 17.6 lb)
Pan/Tilt Angle (Maximum Pan/Tilt Speed)	Pan Approx. $\pm 200^\circ$ (90°/s) Tilt Approx. $\pm 150^\circ$ (90°/s)
Stop Accuracy	under ± 30 arcseconds (0.008°)
Maximum Control Distance (when using AW-RP120G/AW-RP50)	1500 m (when using the protocol converter AW-IF400G*)
Interface RS232C	-
Maximum Preset Memories	50
Applicable Lens	Standard equipment (removable)
Teleprompter Output	Standard equipment
Accessory	Camera cable (Approx. 0.6 m)
AC Adaptor/Power Cable	AC adaptor built in (power cable (2 m) included)