



İş ve eğitim uygulamaları için ideal 50 inç  
Profesyonel 4K ekran

## TH-50EQ2

İş ve eğitim uygulamaları için ideal 50 inç Profesyonel 4K ekran

### Key Features

Çevre birimlerini (kamera/hoparlör) doğrudan ekrana bağlamak kolaydır

Artırılmış giriş türü ve kullanılabilir giriş sayısı

Daha fazla işlevsellik için işlev yuvası

Tipik olarak daha yüksek uç ürünlerde bulunan parlaklık nedeniyle daha yüksek görünürlük

Kurulum esnekliği - dikey ve eğim destekli





## TH-50EQ2

<https://eu.connect.panasonic.com/tr/tr/products/professional-displays/th-50eq2>

<b>Screen size (diagonal) (inch)</b>	49.5-inch (1257.3 mm)
<b>Screen size (diagonal) (mm)</b>	49.5-inch (1257.3 mm)
<b>Aspect Ratio</b>	16:9
<b>Effective display area (W x H) (mm)</b>	1095.8 x 616.4 mm (43.14" x 24.26")
<b>Effective display area (W x H) (inch)</b>	1095.8 x 616.4 mm (43.14" x 24.26")
<b>Resolution</b>	3840 x 2160
<b>Brightness (typ.)</b>	500 cd/m2
<b>Contrast Ratio</b>	5000:1
<b>Response Time</b>	9.5 ms
<b>Viewing angle [(T/B)/(L/R)]</b>	178°/178° (CR>10)
<b>Panel Surface Treatment</b>	Anti-glare type (Haze 25%)
<b>Terminals   HDMI In</b>	TYPE A Connector x 3 (HDCP2.2 supported)
<b>Terminals   PC IN/AUDIO IN (L/R)</b>	Mini D-sub 15-pin x 1 (Female)/Stereo Mini Jack (M3) x 1
<b>Terminals   Serial</b>	D-sub 9-pin x 1, RS232C Compatible
<b>Terminals   Audio Out</b>	Stereo Mini Jack (M3) x 1
<b>Terminals   LAN</b>	RJ45 x 1, RJ45 10BASE-T/100BASE-TX
<b>Terminals   USB</b>	Type A: DC 5 V/1 A, USB 3.0 is supported, Type A: DC 5 V/2 A, USB 2.0 is supported, Type C: max ~ 60W (Power Delivery compatible), USB2.0 is supported, DisplayPort Alternate mode compatible
<b>Terminals   Slot</b>	SDM-S / SDM-L, 3.3 V/max.1.1 A, 12 V/max 5.5 A
<b>Built-in Speaker</b>	20W [10 W + 10 W]
<b>Power Requirements</b>	AC 110 - 240 V 50 Hz / 60 Hz
<b>Power Consumption</b>	255 W
<b>Power Off Condition</b>	Approx. 0.3 W
<b>Standby Condition</b>	Approx. 0.5 W
<b>Weight (kg)</b>	15.5 kg (34.2 lbs.)
<b>Weight (lbs.)</b>	15.5 kg (34.2 lbs.)
<b>Bezel width (mm)</b>	14.9 mm (0.59") (T/R/L/B)
<b>Bezel width (inch)</b>	14.9 mm (0.59") (T/R/L/B)
<b>Wall-hanging pitch (mm)</b>	VESA Compliant 400 x 400 mm (15.8" x 15.8"), M6
<b>Wall-hanging pitch (inch)</b>	VESA Compliant 400 x 400 mm (15.8" x 15.8"), M6
<b>Orientation</b>	Landscape/Portrait
<b>Operating Environment</b>	Temperature: 0 °C to 40 °C (32 °F to 104 °F)/Humidity: 20-80 % (Non condensation)/for up to 0-1400 m (4593 ft) altitude. Temperature: 0 °C to 35 °C (32 °F to 95 °F)/Altitude 1400-2800 m (4593 ft to 9186 ft)
<b>Tilting angle*2</b>	0 - 20 degrees forward/backward with landscape/portrait setting
<b>Operating time*3</b>	18 h/day
<b>Note</b>	1: Including handles. 2: Please contact your sales representative with regard to the tilt angle before installation. 3: In case of long time, the moving image is recommended to be displayed. If you display a still picture for an extended period, the image retention might remain on the screen. However, image retention can gradually disappear by displaying a moving images.
<b>Dimensions (W x H x D*1)</b>	1129 x 649 x 66 mm (44.43" x 25.56" x 2.60")